

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	Gratam Starting Setup				
TRACK	Graha Tamiya Serpong				
NAME	Bowie	DATE	04/2024		
QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME	
		/sec	/		

TRACK			
TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT	
TRACK LAYOUT	<input checked="" type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED	<input type="checkbox"/> FAST
TRACTION	<input checked="" type="checkbox"/> LOW	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	SPUR GEAR	FINAL DRIVE RATIO
32 /T	110 /T	6.5

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
400	OIL /Cst	450
25	REBOUND %	25
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH		SHOCK LENGTH	
8.5 /mm		8.5 /mm	

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

TP ITC 23	TIRES
MG Yellow	ADDITIVE
10	ADDITIVE TIMING
Timing: -	WIPE OFF TIME
Temp.:	TIRE WARMERS
FRONT LEFT	FRONT RIGHT
REAR LEFT	REAR RIGHT
TREATED AREA	

TOTAL WEIGHT	1320 /g	WEIGHT BALANCE	FRONT 49 %	REAR 51 %
--------------	---------	----------------	------------	-----------

MOTOR	Zombie Insane4	TIMING	48
ESC	Tz-01	BATTERIES	Zombie 6250
BODY	Twister L	WING	Twister L

67 /mm	Dimension from body post to window bottom line	BODY POSITION
7+1	Dimension from body post to upper holder	WING SIDE PLATE
64 /mm	Dimension from edge to surface	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>

1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
2.0mm	<input type="checkbox"/> 1.6mm	
NONE <input type="checkbox"/> BEARING <input type="checkbox"/>		

COMMENTS

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
Adjust with eccentric bushings	BUMP STEER 1.5 /mm	Adjust with eccentric bushings
HEIGHT 20 /mm	SHIM 2 /mm	TOE GAIN 2 /mm
2.5 /mm FF	4.8 /mm FR	3 /mm RF
RIDE HEIGHT	SERVO SAVER	5.2 /mm RR
SERVO HORN		RIDE HEIGHT

1.25 /deg. CAMBER	Left = Right	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHOCK HOLDERS SHIM 2.5 /mm	FRONT SHIM 2 /mm	3 /mm	FRONT HUB MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
DRIVE SHAFT 58mm 59mm	BEARING BLADE	SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHIM 0.5 /mm	DOWNSTOP 5.6 /mm		

2 /deg. CAMBER	Left = Right	BODY POST VERTICAL <input checked="" type="checkbox"/> HORIZONTAL <input type="checkbox"/>	SHOCK HOLDERS FIXED <input checked="" type="checkbox"/> ACTIVE <input type="checkbox"/>	SHIM 3 /mm	REAR SHIM 1 /mm	3 /mm	REAR HUB MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
DRIVE SHAFT 52mm 54mm	BEARING BLADE	SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHIM 0.5 /mm	DOWNSTOP 4.8 /mm			

1 TOE OUT	Left = Right	ACKERMANN SHIM 1 /mm	SHORT LiPo BRASS WEIGHT YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	TOE IN 2.25	Right = Left
DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>	10 40g	BRASS WEIGHT FOR MOTOR MOUNT 40g	5 40g	DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>	
UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>	STEERING BRIDGE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	STEERING SHIM 1 /mm	PLATE 8.0mm 7.5mm STD.	UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>	
HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm				HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	

FRONT BOTTOM VIEW	REAR
STEER. LOCK 27 /deg.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
SERVO HOLDER	CHASSIS T-BRACE
FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>
CHASSIS GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU 1.5mm	