

RACE			
TRACK	Arena 33		
NAME	Boyd Chwartacki	DATE	2019-12-15
TEMPERATURE AIR	22	TEMPERATURE TRACK	4123
RACE LENGTH	/min 8	BEST LAP TIME	/sec
QUALIFYING POSITION		FINAL POSITION	3

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HIGH

CENTER SHOCK ABSORBER	
CENTER SHOCK OIL	600 /cSt
CENTER SHOCK REBOUND	15 %
CENTER SHOCK SPRING	
<input type="checkbox"/> SILVER C=1.5 <input type="checkbox"/> GOLD C=1.8 <input type="checkbox"/> BLACK C=2.1 <input type="checkbox"/> BLACK C=1.4-1.9 <input type="checkbox"/> BLACK C=2.0-2.5	

SIDE DAMPING	
<input checked="" type="checkbox"/> SIDE TUBE	OIL 10K /cSt
<input type="checkbox"/> SIDE SHOCK	OIL /cSt

FRONT	TIRES	REAR
Jaco Blue	TIRES TYPE	Jaco Green
40.5	DIAMETER /mm	41.5
Spider Grip Blue	ADDITIVE	Spider Grip Blue
5 minutes	ADDITIVE TIMING	20 minutes

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
ADDITIVE TREATED AREA			

TRANSMISSION		
BALL DIFF	GEAR DIFF	SOLID AXLE
<input type="checkbox"/> LOOSE <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> TIGHT	OIL /cSt	<input type="checkbox"/>

GEARING	
PINION / T	33
SPUR GEAR/T	80
FINAL DRIVE RATIO	
ROLLOUT	

ELECTRONICS	
MOTOR	Xerun 6.5
SPEEDO	Xerun
SERVO	Sanwa
BATTERIES	LRP

BODY	
TYPE	Protoform AMR Prolite

100 mm front width, kimbrough servo saver, custom front titanium wheel axles. Battery held down with Hudy tape.

