

SET-UP SHEET

XRAY XB2'20

RACE	CRCRC Midwest Champs	
TRACK	The Ohio Rc Factory	
NAME		DATE 2020-01-14

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION		FINAL POSITION	

TRACK			
SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT
TRACTION			
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> BUMPY
TYPE	<input checked="" type="checkbox"/> CLAY	<input type="checkbox"/> CARPET	<input type="checkbox"/> ASTRO
CONDITION	<input checked="" type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED	<input type="checkbox"/> DRY
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY	<input type="checkbox"/> WET

TRANSMISSION			
DIFFERENTIAL	BALL DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input type="checkbox"/>	OIL <input type="text" value="cst"/>
SATELLITE GEARS	COMPOSITE <input type="checkbox"/>	STEEL <input type="checkbox"/>	GEARS 2 <input type="checkbox"/> 4 <input type="checkbox"/>
SLIPPER	2 PAD <input checked="" type="checkbox"/>	3 PAD <input type="checkbox"/>	mm

GEARING			
PINION	23	SPUR GEAR	78

GEAR BOX	
FRONT LCG	<input checked="" type="checkbox"/> FRONT LCG <input type="checkbox"/> REAR LCG

FRONT	SHOCKS	REAR
1 dot	SPRINGS	500
cst 500	OIL	cst
<input checked="" type="checkbox"/> 2 HOLES	PISTONS	<input checked="" type="checkbox"/> 2 HOLES
<input type="checkbox"/> 3 HOLES	<input checked="" type="checkbox"/> ø1.6mm	<input type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	<input type="checkbox"/> ø1.7mm	<input type="checkbox"/> 6 HOLES
	OTHER: <input type="text" value="mm"/> <input type="text" value="mm"/>	
SHOCK BODY		
LONG <input type="checkbox"/> SHORT (KIT) <input checked="" type="checkbox"/>		
SHOCK SHAFT		
LONG <input type="checkbox"/> SHORT (KIT) <input checked="" type="checkbox"/>		
DOWNSTOP SHIM		
INSERT UNDER PISTON		
LENGTH 22.3 mm		
UPSTOP SHIM		
INSERT ABOVE COLLAR		
OTHER: <input type="text" value="mm"/> <input checked="" type="checkbox"/> KIT BALL JOINT <input checked="" type="checkbox"/> 1 OTHER		

FRONT	SHOCK TOWER	REAR
ALU <input type="checkbox"/>	GRAPHITE <input type="checkbox"/>	ALU <input type="checkbox"/>

FRONT	ANTI ROLL BAR	REAR
	THICKNESS	

FRONT	TIRES	REAR
	BRAND	
	COMPOUND	
	INSERTS	
	WHEELS	

ELECTRONICS			
MOTOR	7.5	SPEEDO	
MOTOR TIMING		BATTERY	

BODY			
ALPHA2 <input checked="" type="checkbox"/>	BETA2 <input type="checkbox"/>	OTHER: Standard	LIGHT <input type="checkbox"/>

COMMENT	

FRONT	APPLIED <input type="radio"/> <input checked="" type="checkbox"/> APPLIED	REAR
STEERING BLOCK MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/>	LONGER BUSHINGS UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	REAR UPRIGHT SHIM <input type="text" value="mm"/>
CASTER BLOCK MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	CAMBER LINK LOCATION SHIM <input type="text" value="mm"/>	SHIM DRIVE SHAFT Length 77 /mm SHIM 4.5 /mm ADJUSTABLE DRIVE AXLE XB2D SUSP. ARM XB4 SUSP. ARM

FRONT	WING POSITION	WING CUTTING LINE / SIDE LINE	WING TYPE
CASTER BUSHINGS 0° <input type="checkbox"/> 2.5° <input type="checkbox"/> 5° <input type="checkbox"/>	UPPER DECK <input checked="" type="checkbox"/> FRONT WING YES <input type="checkbox"/> NO <input type="checkbox"/> SHOCK TOWER	SHOCK POSITION FRONT <input type="checkbox"/> REAR <input type="checkbox"/>	CENTER FIN YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
KICK-UP KIT 26° <input type="checkbox"/>	BUMP STEER SHIM 3 /mm	WING POSITION UP <input type="checkbox"/> MIDDLE <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>	

FRONT	BATTERY PLACEMENT	REAR
FRONT TOE OUT <input type="checkbox"/> IN <input type="checkbox"/>	LONG SIDE FRONT <input checked="" type="checkbox"/> LONG SIDE REAR <input type="checkbox"/>	REAR TOE IN <input type="checkbox"/> OUT <input type="checkbox"/>
OFFSET 0 /slots <input type="checkbox"/> 1 /slots <input type="checkbox"/> 2 /slots <input checked="" type="checkbox"/>	BATTERY SIZE STD. SHORT <input type="checkbox"/> LOW SHORT <input type="checkbox"/>	OFFSET 6 /slots <input type="checkbox"/>
WHEELBASE SHIM <input type="text" value="mm"/>	GUARD BRACE FLEX YES <input type="checkbox"/> NO <input type="checkbox"/>	WHEELBASE SHIM 2 /mm
ROLL CENTER MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	UPPER BRACE YES <input type="checkbox"/> NO <input type="checkbox"/>	ROLL CENTER COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>

FRONT	SHIMS	REAR ROLL CENTER HOLDERS
SHIMS 3 /mm	SHIMS 4 /mm	ECCENTRIC BUSHINGS RF 0.5° <input type="checkbox"/> 1° <input type="checkbox"/>
STEERING ARMS COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	BUMP STEER SHIM 1 /mm	RR 0.5° <input type="checkbox"/> 1° <input type="checkbox"/>

FRONT	DIFF HEIGHT	REAR
FRONT CAMBER 1°	1°	REAR CAMBER 1°
FRONT ARM MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	DIFF HEIGHT 18 /mm	REAR ARM MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>

FRONT	ARM MOUNT	REAR
ARM MOUNT COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/>	ECCENTRIC SHOCK BALL FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/>	ARM SHIM /mm
CHASSIS BRACE MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	SERVO POSITION BALANCE 100 g	CHASSIS ALU 2.5mm <input type="checkbox"/>
SERVO WEIGHT STANDARD <input type="checkbox"/> LOW PROFILE <input checked="" type="checkbox"/>	CHASSIS FLEX SCREW USED <input type="checkbox"/> SCREW NOT USED <input type="checkbox"/>	