

**XRAY X1'20**

**FRONT**

**BUMP STEER**  
SHIM 4 /mm

**DROOP** 0.8

**4.2 FRONT RIDE HEIGHT**

**MID RIDE HEIGHT** 4.6

**DROOP** 1.3

**REAR RIDE HEIGHT**

**SHOCK PYTE** SHORT LONG

**SHIM** /mm

**WHEELBASE ADJUSTMENT**  
LONG (+4mm) STANDARD (0mm) SHORT (-4mm)

**FRONT**

**SHIM** 1 /mm

**ALU MOUNT** YES NO

**UPPER ARM** SHIM 1 /mm

**SHIM** 2.5 /mm

**SHIM** 0.5 /mm

**LUBE** 15k cSt

**SHIM** 0.5 /mm

**SPRING** 2.0

**LOWER ARM** SHIM 1.5 /mm

**SIDE SPRING**  
SILVER C=0.6 GOLD C=0.9 BLACK C=1.2 SILVER C=1.5 GOLD C=1.8

**RIDE HEIGHT** SHIM /mm

**WING** SHIM /mm

**ARM MOUNT PLATE**  
STANDARD WIDE

**CASTER**  
3° 6° 9° 12°

**LOWER ARMS**  
STANDARD GRAPHITE SOFT GRAPHITE ARMS

**CAMBER**  
1.0° 1.5° 2.0° 2.5°

**CHASSIS**  
GRAPHITE 2.5mm (KIT) HARD GRAPHITE ALU ALU FLEX

**BATTERY POSITION**  
INLINE CROSS CHASSIS

**POD LINK** Left-Right

**REAR WING**  
STANDARD OTHER: Serpent ADJUSTABLE

**REAR AXLE**  
STEEL GRAPHITE

**WING POSITION**  
2 3

**GRAPHITE BRACE**  
YES NO

**SHIM USED**  
YES NO

**BACKSTOP**

**ACKERMANN POSITION**  
SERVO LINKAGE OUTER ACKERMANN

**TOE**  
OUT 1.5 /deg.

**STEERING ANGLE**  
26 °

**FRONT SPOILER**  
LOW DOWNFORCE HIGH DOWNFORCE

**FRONT WIDTH**  
SHIM 0.5 /mm

**TOP DECK**  
YES NO

**TOP DECK FLEX**  
SOFT MEDIUM STIFF

**REAR WIDTH**  
SHIM 3 /mm

**REAR WING POSITION**  
Left-Right  
1 2 3 4 5 6

**BATTERY PLACEMENT**  
4 3 2 1