

SET-UP SHEET

XRAY X1'20

RACE				
TRACK	ETS Rd2 Daun - F1			
NAME	Jan Ratheisky	DATE	9.2.2020	

TEMPERATURE AIR	X	TEMPERATURE TRACK	X
-----------------	---	-------------------	---

QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
1	2	X /sec	X /	X

TRACK			
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT	
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	

CENTER SHOCK ABSORBER		
SPRING	OIL /cSt	REBOUND %
2.3-2.6	1000	
PISTON	PISTON HOLES DIAMETER	FOAM INSERT
<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> ø1.1mm	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> ø1.2mm	
	<input type="checkbox"/> ø1.3mm	

ANTI-ROLL BAR	
THICKNESS/mm	

SIDE DAMPING	
<input checked="" type="checkbox"/> SIDE TUBE	OIL 30000 /cSt
<input type="checkbox"/> SIDE SHOCK	OIL /cSt

FRONT	TIRES	REAR
volante spec	TIRES	volante spec
mr spec	ADDITIVE	mr spec
20	ADDITIVE TIMING	20
FRONT LEFT	ADDITIVE TREATED AREA	REAR LEFT
FRONT RIGHT		REAR RIGHT

TRANSMISSION		
BALL DIFF	SOLID AXLE	GEAR DIFF
<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
LOOSE		OIL 3000 /cSt

GEARING		
PINION /T	SPUR GEAR /T	FINAL DRIVE RATIO
36	84	2.33

ELECTRONICS	
MOTOR	scorpion handout
SPEEDO	
BATTERIES	dadad

BODY	

FRONT		REAR	
BUMP STEER	SHOCK PYTE	SHIM	nut/mm
SHIM 5 /mm	<input checked="" type="checkbox"/> SHORT	<input checked="" type="checkbox"/> LONG	
DROOP 0.6		4.0 FRONT RIDE HEIGHT	MID RIDE HEIGHT 4.2
		DROOP 1.8	REAR RIDE HEIGHT

WHEELBASE ADJUSTMENT	
LONG (+4mm)	SHORT (-4mm)
STANDARD (0mm)	

SHIM 1 /mm	ALU MOUNT YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	UPPER ARM SHIM 1 /mm	0mm <input checked="" type="checkbox"/> CENTER
SHIM 2.5 /mm			+1mm <input type="checkbox"/> REARWARD
SHIM 0.5 /mm			-1mm <input type="checkbox"/> FRONTWARD
LUBE 10000 /cSt	SPRING 1.5	LOWER ARM SHIM 2.5 /mm	SIDE SPRING
SHIM 0.5 /mm			SILVER C=0.6 <input checked="" type="checkbox"/> GOLD C=0.9 <input type="checkbox"/> BLACK C=1.2 <input type="checkbox"/> SILVER C=1.5 <input type="checkbox"/> GOLD C=1.8 <input type="checkbox"/>
			RIDE HEIGHT SHIM 1.25 /mm
			WING SHIM /mm

ARM MOUNT PLATE	CAMBER	
STANDARD <input checked="" type="checkbox"/>	1.0° <input type="checkbox"/> 1.5° <input checked="" type="checkbox"/> 2.0° <input type="checkbox"/> 2.5° <input type="checkbox"/>	
WIDE <input type="checkbox"/>		
CASTER	LOWER ARMS	
3° <input type="checkbox"/> 6° <input type="checkbox"/> 9° <input type="checkbox"/> 12° <input checked="" type="checkbox"/>	STANDARD GRAPHITE <input checked="" type="checkbox"/> SOFT GRAPHITE ARMS <input type="checkbox"/>	

CHASSIS	BATTERY POSITION	REAR WING
GRAPHITE 2.5mm (KIT) <input type="checkbox"/>	<input type="checkbox"/> INLINE	STANDARD <input checked="" type="checkbox"/>
HARD GRAPHITE <input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> CROSS CHASSIS	OTHER:
ALU <input type="checkbox"/>		ADJUSTABLE <input type="checkbox"/>
ALU FLEX <input type="checkbox"/>		REAR AXLE
		STEEL <input type="checkbox"/>
		GRAPHITE <input checked="" type="checkbox"/>
TOE	POD LINK	WING POSITION
OUT 2 /deg.	Left=Right	1 2 3
GRAPHITE BRACE	ACKERMANN POSITION	BATTERY PLACEMENT
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>		4 3 2 1
SHIM USED	SERVO LINKAGE	REAR WING POSITION
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>		Left=Right
FRONT SPOILER	STEERING ANGLE	
LOW DOWNFORCE <input type="checkbox"/>	26 /°	
HIGH DOWNFORCE <input checked="" type="checkbox"/>	FRONT WIDTH	
	SHIM /mm	

COMMENTS