

# SET-UP SHEET

# XRAY T4'20

RACE/TRACK	TITC 2020 - Starting Set-up			
NAME	Alexander Hagberg			
DATE	2020-02-11			
QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
		/sec	/	
<b>TRACK</b>				
TRACK SURFACE <input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT				
TRACK LAYOUT <input type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST				
TRACTION <input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HIGH				
FRONT		TRANSMISSION		REAR
SOLID AXLE <input checked="" type="checkbox"/> YES				
GEAR DIFFERENTIAL - OIL		/cst	GEAR DIFFERENTIAL - OIL 10.000 /cst	
PINION / T		SPUR GEAR / T		FINAL DRIVE RATIO
29		110		
FRONT		SHOCKS		REAR
ULTRA LOW PROFILE <input checked="" type="checkbox"/> SUPER LOW PROFILE <input type="checkbox"/>		SHOCK TYPE		ULTRA LOW PROFILE <input checked="" type="checkbox"/> SUPER LOW PROFILE <input type="checkbox"/>
2.7		XRAY SPRINGS		2.7
450		OIL /cst		450
REBOUND %				
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		FOAM INSERTS		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS		PISTONS 1.0mm ..... 1.1mm ..... 1.2mm ..... PROGRESSIVE		<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS
1.3		THICKNESS/mm ANTI-ROLL BAR		1.2
Sweep		TIRES		Sweep
Hudy Red		ADDITIVE		Hudy Red
10		ADDITIVE TIMING		10
FRONT LEFT	FRONT RIGHT	TREATED AREA		REAR LEFT REAR RIGHT
<b>FRONT ROLL CENTER REAR</b>				
<b>ARS - ACTIVE REAR SUSPENSION™</b>				
MOTOR HW G3 4.5T		TIMING 35		
ESC HW XR10 PRO G2		BATTERIES Sunpadow 5200 Platin		
BODY Twister 0.5		WING Twister 0.7		
COMMENTS 20g of weight near receiver. Set screw in T-brace rear center point.				

<b>FRONT</b>		<b>REAR</b>	
CASTER 0° <input type="checkbox"/> 2° <input type="checkbox"/> 4° <input checked="" type="checkbox"/> 6° <input type="checkbox"/> SHIM /mm RIDE HEIGHT /mm WHEELBASE /mm TOE OUT 1		SHIMS UNDER TOP DECK /mm RIDE HEIGHT /mm TOE IN 2.25 OUTBOARD TOE LOWER /mm UPPER /mm	
SHIMS UNDER SHOCK 1.5 /mm 4 /mm LOWER UPPER ROLL CENTER UPPER CLAMP 2 1		ACKERMANN /mm STEERING ARM STANDARD <input type="checkbox"/> ALU <input checked="" type="checkbox"/> STEERING PLATE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> SHIMS UNDER SHOCK 3 /mm LOWER UPPER ROLL CENTER UPPER CLAMP 1 2	
DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> BALANCE 10 /g BATT. BACKSTOP COMPOSITE <input type="checkbox"/> ALU <input type="checkbox"/> ALU ADJ. <input type="checkbox"/> BRASS ADJ. <input checked="" type="checkbox"/> BALANCE 10 /g TOP DECK FLEX NO POST <input type="checkbox"/> BEARING <input type="checkbox"/> BUSHING <input checked="" type="checkbox"/> BALANCE /g STEERING SHIM SHIM SIZE 6 BALANCE 10 /g SERVO HORN SERVO SAVER <input type="checkbox"/> ALU <input checked="" type="checkbox"/> TOP DECK 2.0mm <input type="checkbox"/> 1.6mm <input checked="" type="checkbox"/>		BALANCE 5 /g DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> BALANCE 10 /g TOP DECK FLEX NO POST <input type="checkbox"/> BEARING <input type="checkbox"/> BUSHING <input checked="" type="checkbox"/> BALANCE /g CHASSIS BRACE BRASS <input type="checkbox"/> ALU <input checked="" type="checkbox"/> SUSP. HOLDERS FRONT SERVO HOLDER FORWARD STANDARD MOTOR MOUNT CHASSIS GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> ALU-FLEX <input checked="" type="checkbox"/> OTHER RF STD <input type="checkbox"/> ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/> RR STD <input type="checkbox"/> ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/>	
C-HUB M <input type="checkbox"/> H <input type="checkbox"/> G <input checked="" type="checkbox"/> ALU <input type="checkbox"/> STEER.BLOCK M <input type="checkbox"/> H <input checked="" type="checkbox"/> G <input type="checkbox"/> ALU <input type="checkbox"/> OFFSET STANDARD <input checked="" type="checkbox"/>		SHIM 2 /mm DRIVE SHAFT 52mm <input checked="" type="checkbox"/> 51mm <input type="checkbox"/> 50mm <input type="checkbox"/> OTHER SHIM 1.5 /mm SHIM 2 /mm DRIVE SHAFT ECS <input checked="" type="checkbox"/> CVD <input type="checkbox"/> OTHER SHIM 4 /mm CAMBER LINK LOCATION OPTIONAL ALU HUB MEASURE UNDER ARM DOWNSTOP/mm CAMBER 2.25 /deg. FRONT ARM HARD (H) <input type="checkbox"/> GRAPHITE (G) <input checked="" type="checkbox"/> SHORT <input checked="" type="checkbox"/> LONG SHOCK TOWERS HIGHER SLP <input type="checkbox"/> STANDARD ULP <input checked="" type="checkbox"/> LOWER ULP <input type="checkbox"/> OTHER REAR ARM HARD (H) <input type="checkbox"/> GRAPHITE (G) <input checked="" type="checkbox"/> SHORT <input checked="" type="checkbox"/> LONG	