

SET-UP SHEET

XRAY X1'20

RACE				
TRACK	M R Jedovnice			
NAME	Aleš Horák		DATE	16.2.2020
TEMPERATURE AIR	22-24		TEMPERATURE TRACK	20-21
QUAL POSITION	3	FINAL POSITION	3	BEST LAP TIME
				13,716 /sec
			LAPS	22 / 5:12.106
TRACK				
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET		<input type="checkbox"/> ASPHALT	
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL		<input checked="" type="checkbox"/> MIXED	
TRACTION	<input type="checkbox"/> LOW		<input checked="" type="checkbox"/> MEDIUM	
CENTER SHOCK ABSORBER				
SPRING	2,3		OIL /cSt	800
REBOUND %	-			
PISTON	<input checked="" type="checkbox"/> 3 HOLES		PISTON HOLES DIAMETER	<input checked="" type="checkbox"/> ø1.1mm
	<input checked="" type="checkbox"/> 4 HOLES			<input type="checkbox"/> ø1.2mm
				<input type="checkbox"/> ø1.3mm
FOAM INSERT	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>			
ANTI-ROLL BAR				
THICKNESS/mm	1,1			
SIDE DAMPING				
<input checked="" type="checkbox"/> SIDE TUBE			OIL	50tis /cSt
<input type="checkbox"/> SIDE SHOCK			OIL	/cSt
TIRES				
FRONT	Volante		TIRES	Volante
	Hudy		ADDITIVE	Hudy
	8		ADDITIVE TIMING	20+8
FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT	
TRANSMISSION				
BALL DIFF	<input type="checkbox"/>		SOLID AXLE	<input type="checkbox"/>
LOOSE	MEDIUM	TIGHT	GEAR DIFF	<input checked="" type="checkbox"/>
			OIL	800 a 3000 /cSt
GEARING				
PINION /T	27		SPUR GEAR /T	84
			FINAL DRIVE RATIO	3,11
ELECTRONICS				
MOTOR	Muchmore ZX V2 21,5T			
SPEEDO	Hobbywing XeRun XR10 STOCK SPEC			
BATTERIES				
BODY				

FRONT		REAR	
SHOCK PYTE <input checked="" type="checkbox"/> SHORT <input type="checkbox"/> LONG <input type="checkbox"/> SHIM nut/mm		SHIM nut/mm	
BUMP STEER SHIM 4 /mm		SHIM 1 /mm	
DROOP 1,4		4,6 FRONT RIDE HEIGHT	
MID RIDE HEIGHT 4,7		DROOP 1	
REAR RIDE HEIGHT		WHEELBASE ADJUSTMENT	
LONG (+4mm)		SHORT (-4mm)	
STANDARD (0mm)		CENTER <input checked="" type="checkbox"/> REARWARD <input type="checkbox"/> FRONTWARD <input type="checkbox"/>	
SHIM 0,5 /mm		SHIM 1 /mm	
SHIM 6 /mm		SHIM 0,5 /mm	
SHIM 0,5 /mm		LUBE 600 /cSt	
SHIM 0,5 /mm		SPRING 1,5	
SHIM 1 /mm		LOWER ARM SHIM 1 /mm	
SIDE SPRING		RIDE HEIGHT SHIM 1,5 /mm	
SILVER C=0.6		GOLD C=0.9	
BLACK C=1.2		SILVER C=1.5	
GOLD C=1.8		WING SHIM - /mm	
ARM MOUNT PLATE		CAMBER	
STANDARD <input type="checkbox"/> WIDE <input checked="" type="checkbox"/>		1.0° <input type="checkbox"/> 1.5° <input checked="" type="checkbox"/> 2.0° <input type="checkbox"/> 2.5° <input type="checkbox"/>	
CASTER		LOWER ARMS	
3° <input type="checkbox"/> 6° <input type="checkbox"/> 9° <input type="checkbox"/> 12° <input checked="" type="checkbox"/>		STANDARD GRAPHITE <input checked="" type="checkbox"/> SOFT GRAPHITE ARMS <input type="checkbox"/>	
CHASSIS		BATTERY POSITION	
GRAPHITE 2.5mm (KIT) <input checked="" type="checkbox"/> HARD GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input type="checkbox"/>		<input type="checkbox"/> INLINE <input checked="" type="checkbox"/> CROSS CHASSIS	
TOE OUT 2,5 /deg.		REAR WING STANDARD <input checked="" type="checkbox"/> OTHER:	
GRAPHITE BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> SHIM USED YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>		REAR AXLE STEEL <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	
ACKERMANN POSITION		ADJUSTABLE <input type="checkbox"/> WING POSITION	
SERVO LINKAGE		BATTERY PLACEMENT	
BACKSTOP		REAR WIDTH SHIM 3,5 /mm	
OUTER ACKERMANN		REAR WING POSITION Left=Right	
TOP DECK YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		TOP DECK FLEX SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> STIFF <input type="checkbox"/>	
FRONT SPOILER LOW DOWNFORCE <input type="checkbox"/> HIGH DOWNFORCE <input type="checkbox"/>		REAR WING POSITION 1 2 3 4 5 6	
STEERING ANGLE 26 /°		FRONT WIDTH SHIM 1 /mm	
FRONT SPOILER Montech 2Kl		FRONT WIDTH SHIM 1 /mm	

COMMENTS Protoform F26