

SET-UP SHEET

XRAY XB2'20

| | | |
|-------|----------------|-----------------|
| RACE | NW Hobbies | |
| TRACK | | |
| NAME | Shannon Houfek | DATE 2020-02-20 |

| | | | |
|---------------------|--|----------------|-----|
| LAPS | | BEST LAP TIME | sec |
| QUALIFYING POSITION | | FINAL POSITION | |

| TRACK | |
|-----------|---|
| SIZE | <input type="checkbox"/> OPEN <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> TIGHT |
| TRACTION | <input type="checkbox"/> VERY-LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> VERY-HIGH |
| SURFACE | <input checked="" type="checkbox"/> SMOOTH <input type="checkbox"/> MEDIUM <input type="checkbox"/> BUMPY |
| TYPE | <input type="checkbox"/> CLAY <input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASTRO |
| CONDITION | <input type="checkbox"/> BLUE GROOVE <input type="checkbox"/> HARD PACKED <input checked="" type="checkbox"/> DRY |
| | <input type="checkbox"/> DUSTY <input type="checkbox"/> LOAMY <input type="checkbox"/> WET |

| TRANSMISSION | |
|-----------------|--|
| DIFFERENTIAL | BALL DIFF <input type="checkbox"/> <input checked="" type="checkbox"/> GEAR DIFF OIL 60 cst |
| SATELLITE GEARS | COMPOSITE <input type="checkbox"/> <input checked="" type="checkbox"/> STEEL GEARS 2 <input checked="" type="checkbox"/> 4 |
| SLIPPER | 2 PAD <input type="checkbox"/> 3 PAD <input checked="" type="checkbox"/> mm |

| GEARING | |
|-----------|------|
| PINION | 20 T |
| SPUR GEAR | 81 T |

| GEAR BOX | |
|-----------|---|
| FRONT LCG | <input checked="" type="checkbox"/> <input type="checkbox"/> REAR LCG |

| FRONT | SHOCKS | REAR |
|---|--|---|
| 3 | SPRINGS | 450 |
| cst 650 | OIL | cst |
| <input checked="" type="checkbox"/> 2 HOLES <input type="checkbox"/> 3 HOLES <input type="checkbox"/> 6 HOLES | PISTONS | <input type="checkbox"/> 2 HOLES <input checked="" type="checkbox"/> 3 HOLES <input type="checkbox"/> 6 HOLES |
| | OTHER | |
| | 1.5 mm 1.6 mm | |
| SHOCK BODY | | |
| LONG <input type="checkbox"/> <input checked="" type="checkbox"/> SHORT (KIT) | | |
| SHOCK SHAFT | | |
| LONG <input type="checkbox"/> <input checked="" type="checkbox"/> SHORT (KIT) | | |
| DOWNSTOP SHIM | | |
| INSERT UNDER PISTON | | |
| LENGTH 23 mm | | LENGTH 30 mm |
| UPSTOP SHIM | | UPSTOP SHIM |
| INSERT ABOVE COLLAR | | INSERT ABOVE COLLAR |
| 1 mm | | 2 mm |
| OTHER | <input checked="" type="checkbox"/> KIT BALL JOINT | OTHER |
| | | 2 |

| FRONT | SHOCK TOWER | REAR |
|--|-------------|--|
| ALU <input checked="" type="checkbox"/> GRAPHITE | | GRAPHITE <input checked="" type="checkbox"/> ALU |

| FRONT | ANTI ROLL BAR | REAR |
|-------|---------------|--------|
| | THICKNESS | 1.2 mm |

| FRONT | TIRES | REAR |
|----------|----------|------------|
| PL Wedge | BRAND | PL pyramid |
| Z4 | COMPOUND | Z3 |
| No | INSERTS | OC |
| PL | WHEELS | |

| ELECTRONICS | |
|--------------|-------------------------------|
| MOTOR | Maclan 6.5 Maclan MMRH SPEEDO |
| MOTOR TIMING | 30 Maclan 4K V3 BATTERY |

| BODY | |
|--|---------------------------------------|
| ALPHA2 <input checked="" type="checkbox"/> BETA2 | OTHER: <input type="checkbox"/> LIGHT |

| COMMENT | |
|---------|--|
| | |

| FRONT | APPLIED <input type="radio"/> <input checked="" type="checkbox"/> APPLIED | REAR |
|---|---|--|
| STEERING BLOCK MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> | LONGER BUSHINGS UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> | REAR UPRIGHT SHIM 2 /mm HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> |
| CAMBER LINK LOCATION SHIM /mm FLAT ARM LSM ARM | SHIM 3 /mm DRIVE SHAFT Length 75 /mm SHIM 2 /mm ADJUSTABLE DRIVE AXLE XB2D SUSP. ARM XB4 SUSP. ARM | SHOCK POSITION FRONT <input type="checkbox"/> REAR <input type="checkbox"/> |

| FRONT | WING POSITION | WING CUTTING LINE / SIDE LINE | WING TYPE |
|---|--|---|---|
| CASTER BUSHINGS 0° <input type="checkbox"/> 2.5° <input type="checkbox"/> 5° <input type="checkbox"/> | YES <input type="checkbox"/> NO <input type="checkbox"/> | 1 2 3 4 5 SHOCK POSITION FRONT <input type="checkbox"/> REAR <input type="checkbox"/> | CENTER FIN YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> |
| KICK-UP KIT 26° <input checked="" type="checkbox"/> | BUMP STEER SHIM /mm | WING POSITION UP <input type="checkbox"/> MIDDLE <input type="checkbox"/> DOWN <input type="checkbox"/> | |

| FRONT TOE | OUT | EXTENSION | REAR TOE | IN |
|---|-----|--|---|----|
| 1 | | 0 SLOTS <input type="checkbox"/> 1 SLOT <input checked="" type="checkbox"/> 2 SLOTS <input type="checkbox"/> | | |
| OFFSET -0.75 /slots | | | OFFSET 6 /slots | |
| WHEELBASE SHIM 2 /mm | | | WHEELBASE SHIM 3 /mm | |
| ROLL CENTER | | | ROLL CENTER | |
| MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> ALU <input type="checkbox"/> | | | COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> | |
| UPPER DECK | | | UPPER BRACE | |
| MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> | | | YES <input type="checkbox"/> NO <input type="checkbox"/> | |
| | | | BATTERY SIZE | |
| | | | STD. SHORT <input type="checkbox"/> LOW SHORT <input type="checkbox"/> | |

| FRONT | SHIMS | REAR ROLL CENTER HOLDERS |
|---|---|--|
| SHIMS /mm ACKERMANN LEFT = RIGHT | 2 /mm | ECCENTRIC BUSHINGS RF 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/> RR 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/> |
| STEERING ARMS COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> | BUMP STEER SHIM 1 /mm LEFT = RIGHT | STEERING PLATE COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> |

| FRONT CAMBER | DIFF HEIGHT | REAR CAMBER |
|--|-------------|--|
| 3 | | |
| FRONT ARM | | REAR ARM |
| MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> | | MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> |
| RIDE HEIGHT 15 /mm | | RIDE HEIGHT 16 /mm |

| ARM MOUNT | ECCENTRIC SHOCK BALL | ARM SHIM |
|---|---|--|
| COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/> | FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/> | No /mm |
| CHASSIS BRACE MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> | BALANCE 50 g | CHASSIS ALU 2.5mm <input type="checkbox"/> No |
| SERVO WEIGHT STANDARD <input type="checkbox"/> LOW PROFILE <input checked="" type="checkbox"/> | CHASSIS FLEX SCREW USED <input type="checkbox"/> SCREW NOT USED <input type="checkbox"/> | |