

SET-UP SHEET

XRAY XB2'20

RACE	XRS Round 4 Poland		
TRACK	Lodz		
NAME	Atlas Arena	DATE	2020-02-22

LAPS	17	BEST LAP TIME	16.960 sec
QUALIFYING POSITION	1	FINAL POSITION	1

TRACK			
SIZE	<input type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> TIGHT
TRACTION	<input type="checkbox"/> VERY-LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> VERY-HIGH		
SURFACE	<input checked="" type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
TYPE	<input type="checkbox"/> CLAY	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASTRO
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED	<input checked="" type="checkbox"/> DRY
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY	<input type="checkbox"/> WET

TRANSMISSION			
DIFFERENTIAL	BALL DIFF <input type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>	OIL 15 cSt
SATELLITE GEARS	COMPOSITE <input type="checkbox"/>	STEEL <input checked="" type="checkbox"/>	GEARS 2 <input checked="" type="checkbox"/> 4 <input type="checkbox"/>
SLIPPER	2 PAD <input type="checkbox"/>	3 PAD <input checked="" type="checkbox"/>	mm

GEARING			
PINION	22	SPUR GEAR	78

GEAR BOX	
FRONT LCG	<input checked="" type="checkbox"/> FRONT LCG <input type="checkbox"/> REAR LCG

FRONT	SHOCKS	REAR
2dot	SPRINGS	500
cSt 450	OIL	cSt
<input checked="" type="checkbox"/> 2 HOLES	PISTONS	<input checked="" type="checkbox"/> 2 HOLES
<input type="checkbox"/> 3 HOLES	<input checked="" type="checkbox"/> ø1.6mm	<input type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	<input type="checkbox"/> ø1.7mm	<input type="checkbox"/> 6 HOLES
OTHER: mm mm		
SHOCK BODY		
LONG <input type="checkbox"/> SHORT (KIT) <input checked="" type="checkbox"/>		
SHOCK SHAFT		
LONG <input type="checkbox"/> SHORT (KIT) <input checked="" type="checkbox"/>		
DOWNSTOP SHIM		
INSERT UNDER PISTON		
1	2	
LENGTH 23 mm	LENGTH 28 mm	
UPSTOP SHIM		
INSERT ABOVE COLLAR		
OTHER: mm	<input checked="" type="checkbox"/> KIT BALL JOINT	1

FRONT	SHOCK TOWER	REAR
ALU <input type="checkbox"/>	GRAPHITE <input type="checkbox"/>	ALU <input type="checkbox"/>

FRONT	ANTI ROLL BAR	REAR
mm	THICKNESS	1,1 mm

FRONT	TIRES	REAR
Schumacher	BRAND	Schumacher
	COMPOUND	
	INSERTS	
Preglued	WHEELS	

ELECTRONICS			
MOTOR	6,5	Hobbywing	SPEEDO
MOTOR TIMING	35	Sunpadow 38	BATTERY

BODY	
ALPHA2 <input type="checkbox"/>	BETA2 <input checked="" type="checkbox"/> OTHER: <input checked="" type="checkbox"/> LIGHT

COMMENT

FRONT	APPLIED <input type="radio"/> <input checked="" type="checkbox"/> APPLIED	REAR
STEERING BLOCK MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/>	LONGER BUSHINGS UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	REAR UPRIGHT SHIM /mm SHIM 5 /mm DRIVE SHAFT Length 75 /mm SHIM 2 /mm HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
CASTER BLOCK MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	CAMBER LINK LOCATION SHIM /mm FLAT ARM LSM ARM	ADJUSTABLE DRIVE AXLE XB2D SUSP. ARM XB4 SUSP. ARM

FRONT	WING POSITION	WING CUTTING LINE / SIDE LINE	WING TYPE
CASTER BUSHINGS 0° <input type="checkbox"/> 2.5° <input checked="" type="checkbox"/> 5° <input type="checkbox"/>	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SHOCK POSITION FRONT <input type="checkbox"/> REAR <input type="checkbox"/>	tec CENTER FIN YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
KICK-UP KIT 26° <input checked="" type="checkbox"/>	BUMP STEER SHIM /mm	WING POSITION UP <input type="checkbox"/> MIDDLE <input type="checkbox"/> DOWN <input type="checkbox"/>	

FRONT TOE	EXTENSION	BATTERY PLACEMENT	REAR TOE
0.5	0 SLOTS <input type="checkbox"/> 1 SLOT <input checked="" type="checkbox"/> 2 SLOTS <input type="checkbox"/>	LONG SIDE FRONT <input checked="" type="checkbox"/> LONG SIDE REAR <input type="checkbox"/>	IN
OFFSET 2 /slots	WHEELBASE SHIM 2 /mm	BATTERY SIZE STD. SHORT <input type="checkbox"/> LOW SHORT <input type="checkbox"/>	OFFSET 5 /slots
ROLL CENTER MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	GUARD BRACE FLEX	UPPER BRACE YES <input type="checkbox"/> NO <input type="checkbox"/>	WHEELBASE SHIM /mm
UPPER DECK MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/>		ROLL CENTER COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	

FRONT	SHIMS	REAR ROLL CENTER HOLDERS
SHIMS 2 /mm	4 /mm	ECCENTRIC BUSHINGS
ACKERMANN LEFT = RIGHT	BUMP STEER SHIM 1 /mm	RF 0.5° <input checked="" type="checkbox"/> 1° <input type="checkbox"/>
STEERING ARMS COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	STEERING PLATE COMPOSITE <input type="checkbox"/> ALU <input type="checkbox"/>	RR 0.5° <input checked="" type="checkbox"/> 1° <input type="checkbox"/>

FRONT CAMBER	DIFF HEIGHT	REAR CAMBER
	2	
FRONT ARM MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	RIDE HEIGHT 16 /mm #107721 GAUGE	REAR ARM MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>

ARM MOUNT	ECCENTRIC SHOCK BALL	ARM SHIM
COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> BRASS <input type="checkbox"/>	FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/>	/mm
CHASSIS BRACE MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	SERVO POSITION BALANCE 35 g	CHASSIS ALU 2.5mm <input type="checkbox"/> Short
SERVO WEIGHT STANDARD <input type="checkbox"/> LOW PROFILE <input checked="" type="checkbox"/>	CHASSIS FLEX SCREW USED <input type="checkbox"/> SCREW NOT USED <input checked="" type="checkbox"/>	