

SET-UP SHEET

XRAY X1'20

RACE				
TRACK	MIBOSPORT CUP R5			
NAME	Lukas Hoch	DATE	29.2.2020	
TEMPERATURE AIR		TEMPERATURE TRACK		
QUAL POSITION	1	FINAL POSITION	1	BEST LAP TIME
				13.37 /sec
LAPS	/			
TIME				
TRACK				
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET		<input type="checkbox"/> ASPHALT	
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL		<input checked="" type="checkbox"/> MIXED	
	<input type="checkbox"/> FAST			
TRACTION	<input type="checkbox"/> LOW		<input checked="" type="checkbox"/> MEDIUM	
	<input type="checkbox"/> HIGH			
CENTER SHOCK ABSORBER				
SPRING	OIL /cSt		REBOUND %	
2.3-2.6	1000			
PISTON	PISTON HOLES DIAMETER		FOAM INSERT	
<input type="checkbox"/> 3 HOLES	<input checked="" type="checkbox"/> ø1.1mm		YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	
<input checked="" type="checkbox"/> 4 HOLES	<input type="checkbox"/> ø1.2mm			
	<input type="checkbox"/> ø1.3mm			
ANTI-ROLL BAR				
THICKNESS/mm	No			
SIDE DAMPING				
<input checked="" type="checkbox"/> SIDE TUBE			OIL	15k /cSt
<input type="checkbox"/> SIDE SHOCK			OIL	/cSt
TIRES				
FRONT	TIRES		REAR	
Volante				
Hudy red	ADDITIVE			
12min	ADDITIVE TIMING			
FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT	
TRANSMISSION				
BALL DIFF	SOLID AXLE		GEAR DIFF	
<input type="checkbox"/> LOOSE	<input type="checkbox"/>		<input checked="" type="checkbox"/>	
<input type="checkbox"/> MEDIUM			OIL 6k /cSt	
<input type="checkbox"/> TIGHT				
GEARING				
PINION /T	SPUR GEAR /T		FINAL DRIVE RATIO	
27	84		3.11	
ELECTRONICS				
MOTOR	HW G3R			
SPEEDO	HW StocSpec			
BATTERIES	Gensace 6000mah redline			
BODY				
COMMENTS Gonzo L				

FRONT		REAR	
BUMP STEER		SHOCK PYTE	
SHIM 4 /mm		SHIM Nut/mm	
SERVO ARM		LONG	
DROOP 1.5		4.2 FRONT RIDE HEIGHT	
		MID RIDE HEIGHT 4.4	
		DROOP 1.6	
		REAR RIDE HEIGHT	
LONG (+4mm)		SHORT (-4mm)	
STANDARD (0mm)		WHEELBASE ADJUSTMENT	
SHIM /mm		SHIM 2 /mm	
SHIM 3.5 /mm		SHIM 2 /mm	
SHIM /mm		SHIM 2 /mm	
LUBE 10k /cSt		SHIM 1.25 /mm	
SPRING 1.5		SHIM 2 /mm	
SHIM 1.25 /mm		SHIM 2 /mm	
SIDE SPRING		RIDE HEIGHT	
SILVER C=0.6		SHIM 1.5 /mm	
GOLD C=0.9		WING SHIM 10 /mm	
BLACK C=1.2			
SILVER C=1.5			
GOLD C=1.8			
ARM MOUNT PLATE		CAMBER	
STANDARD		1.0°	
WIDE		1.5°	
CASTER		2.0°	
3°		2.5°	
6°			
9°			
12°			
LOWER ARMS			
STANDARD GRAPHITE			
SOFT GRAPHITE ARMS			
CHASSIS		REAR WING	
GRAPHITE 2.5mm (KIT)		STANDARD	
HARD GRAPHITE		OTHER: Serpent	
ALU		ADJUSTABLE	
ALU FLEX		1 2 3 WING POSITION	
BATTERY POSITION		REAR AXLE	
INLINE		STEEL	
CROSS CHASSIS		GRAPHITE	
POD LINK		BATTERY PLACEMENT	
Left=Right		4 3 2 1	
GRAPHITE BRACE		REAR WIDTH	
YES		SHIM 2.5 /mm	
NO			
SHIM USED		REAR WING POSITION	
YES		Left=Right	
NO			
BACKSTOP			
ACKERMANN POSITION			
SERVO LINKAGE			
OUTER ACKERMANN			
STEERING ANGLE			
22			
FRONT SPOILER			
LOW DOWNFORCE			
HIGH DOWNFORCE			
FRONT WIDTH			
SHIM 1 /mm			
TOP DECK			
YES			
NO			
TOP DECK FLEX			
SOFT			
MEDIUM			
STIFF			