

XRAY X1'20

FRONT

BUMP STEER
SHIM 4 /mm

SERVOMOUNT

SHIM /mm

SHOCK PYTE

SHORT

LONG

SHIM /mm

DROOP 0.5

4 FRONT RIDE HEIGHT

MID RIDE HEIGHT

4 DROOP 1

REAR RIDE HEIGHT

WHEELBASE ADJUSTMENT
LONG (+4mm) SHORT (-4mm) STANDARD (0mm)

FRONT

SHIM
1 /mm

ALU MOUNT
YES ☐ NO ☒

UPPER ARM
SHIM 2 /mm

SHIM
2.5 /mm

SHIM
0.5 /mm

LUBE
10K

SHIM
0.5 /mm

SPRING
C=2.0

LOWER ARM
SHIM /mm

SIDE SPRING
☐ SILVER C=0.6 ☒ GOLD C=0.9 ☐ BLACK C=1.2 ☐ SILVER C=1.5 ☐ GOLD C=1.8

RIDE HEIGHT
SHIM 1 /mm

WING
SHIM 2 /mm

0mm ☒ CENTER
+1mm ☐ REARWARD
-1mm ☐ FRONTWARD

ARM MOUNT PLATE
STANDARD ☒
WIDE ☐

CASTER
3° ☐ 6° ☐ 9° ☒ 12° ☐

LOWER ARMS
STANDARD GRAPHITE ☒
SOFT GRAPHITE ARMS ☐

CAMBER
1.0° ☐ 1.5° ☐ 2.0° ☒ 2.5° ☐

CHASSIS
GRAPHITE 2.5mm (KIT) ☒
HARD GRAPHITE ☐
ALU ☐
ALU FLEX ☐

BATTERY POSITION
☐ INLINE
☒ CROSS CHASSIS

POD LINK
Left = Right

REAR WING
STANDARD ☒
OTHER:

REAR AXLE
STEEL ☒
GRAPHITE ☐

ADJUSTABLE
WING POSITION

GRAPHITE BRACE
YES ☐ NO ☒

SHIM USED
YES ☐ NO ☒

ACKERMANN POSITION

SERVOLINKAGE

OUTER ACKERMANN

BACKSTOP

TOE
OUT 1.5 /deg.

FRONT SPOILER
LOW DOWNFORCE ☐
HIGH DOWNFORCE ☒

STEERING ANGLE
25 °

FRONT WIDTH
SHIM 0.5 /mm

TOP DECK
YES ☒ NO ☐

TOP DECK FLEX
SOFT ☐
MEDIUM ☐
STIFF ☒

REAR WIDTH
SHIM 2 /mm

BATTERY PLACEMENT
4 3 2 1

REAR WING POSITION
Left = Right
1 2 3 4 5 6

REAR