

SET-UP SHEET

RACE/TRACK	MRcup	Svitavy - smallest
NAME	Lukas Hoch	
DATE	2020-06-28	

QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
1.	1.	/sec	/	

TRACK				
TRACK SURFACE		<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT	
TRACK LAYOUT		<input type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED	<input checked="" type="checkbox"/> FAST
TRACTION		<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH
FRONT		TRANSMISSION		REAR
GEAR DIFFERENTIAL - OIL		2mil /cst		
PINION / T		SPUR GEAR / T		FINAL DRIVE RATIO
42		100		4.52

FRONT		SHOCKS		REAR
ULTRA LOW PROFILE	<input checked="" type="checkbox"/>	SUPER LOW PROFILE	<input type="checkbox"/>	
2.5-2.8		SHOCK TYPE		
550		XRAY SPRINGS		2.6
		OIL /Cst		550
		REBOUND %		
<input type="checkbox"/> YES	<input checked="" type="checkbox"/> NO	FOAM INSERTS		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
3 HOLES		PISTONS		3 HOLES
4 HOLES		1.0mm		
		1.1mm		
		1.2mm		
PSS		PROGRESSIVE		PSS
1.4	THICKNESS/mm	ANTI-ROLL BAR		THICKNESS/mm 1.3

Ride	TIRES	Ride
Hudy red	ADDITIVE	Hudy red
15	ADDITIVE TIMING	15

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

FRONT		ROLL CENTER		REAR
FF	FF	1	1	RR
		0.5	0.5	RR
FR	FR	1	1	RF
		0.5	0.5	STD 25

ARS - ACTIVE REAR SUSPENSION™	
SHIM 2 /mm	SHIM 1 /mm
LINKS UP	LINKS DOWN
STEERING BLOCK	OFFSET
MEDIUM	STANDARD
HARD	
GRAPHITE	
ALU	
C-HUB	0° 2° 4°

MOTOR	TIMING
ESC	BATTERIES
BODY	WING

COMMENTS

FRONT		REAR	
CASTER	0° 2° 4° 6°	SHIMS UNDER TOP DECK	/mm
SHIM 2 /mm			
WHEELBASE/mm	Maximum		
RIDE HEIGHT/mm	5.2		5.4

FRONT		REAR	
TOE OUT	1.5	FINAL TOE IN	2.5
ACKERMANN	/mm	OUTBOARD + INBOARD TOE	
SHIMS UNDER SHOCK		OUTBOARD TOE	
STEERING ARM	STANDARD	ANTI ROLL-BAR	
ALU	<input checked="" type="checkbox"/>	SHIMS UNDER SHOCK	

DIFF POSITION	UP	DOWN
BALANCE	10 /g	
BATT. BACKSTOP	COMPOSITE	
ALU	<input type="checkbox"/>	
ALU ADJ.	<input type="checkbox"/>	
BRASS ADJ.	<input type="checkbox"/>	
FR. CHASSIS WEIGHT 30g	YES	NO
+ BALANCE	10 /g	
STEER. SHIM	SHIM SIZE 1.5	
BALANCE	5 /g	
SERVO HORN	SERVO SAVER	
ALU	<input checked="" type="checkbox"/>	
TOP DECK	STANDARD	
TOP DECK FLEX	NO POST	
BEARING	<input type="checkbox"/>	
BUSHING	<input checked="" type="checkbox"/>	
BALANCE	5 /g	

STEERING LOCK	23 /degr.
CHASSIS BRACE	BRASS
ALU	<input type="checkbox"/>
MOTOR MOUNT	
CHASSIS	GRAPHITE
ALU	<input type="checkbox"/>
OTHER	

C-HUB		DRIVE SHAFT		SHIM		SHIM		SHIM		REAR HUB	
M	<input type="checkbox"/>	52mm	<input type="checkbox"/>	2	/mm	2	/mm	1	/mm	M	<input type="checkbox"/>
H	<input checked="" type="checkbox"/>	51mm	<input checked="" type="checkbox"/>							H	<input type="checkbox"/>
G	<input type="checkbox"/>	50mm	<input type="checkbox"/>							G	<input type="checkbox"/>
ALU	<input type="checkbox"/>	OTHER								ALU	<input checked="" type="checkbox"/>
STEER. BLOCK	M									OPTIONAL ALU HUB	
H	<input type="checkbox"/>										
G	<input type="checkbox"/>										
ALU	<input checked="" type="checkbox"/>										
OFFSET	STANDARD										
5.2											
DOWNSTOP/mm	4.4										

FRONT		REAR	
CAMBER	2 /degr.	CAMBER	/degr.
FRONT ARM	HARD (H)	SHOCK TOWER	STANDARD ULP
GRAPHITE (G)	<input type="checkbox"/>	LOWER ULP	<input checked="" type="checkbox"/>
		OTHER	
		REAR ARM	HARD (H)
		GRAPHITE (G)	<input type="checkbox"/>