

# XRAY T4'20

**FRONT**

CASTER 0° 2° 4° 6° SHIM 0.0 /mm

BODY POSITION

RIDE HEIGHT /mm

WHEELBASE /mm

SHIMS UNDER TOP DECK /mm

REAR

TOE OUT 1.25

ACKERMANN 0.5 /mm

FINAL TOE IN 2.75

OUTBOARD + INBOARD TOE

OUTBOARD TOE 0.0

LOWER 0.0 /mm

UPPER 3.0 /mm

STEERING ARM STANDARD ALU

STEERING PLATE YES NO

ROLL CENTER UPPER CLAMP

DIFF POSITION UP DOWN

BALANCE 5 /g

BATT. BACKSTOP COMPOSITE ALU ALU ADJ. BRASS ADJ.

BALANCE 12 /g

BALANCE 10 /g

DIFF POSITION UP DOWN

BALANCE /g

STEERING SHIM SHIM SIZE 6

BALANCE 5 /g

SERVO HORN SERVO SAVER ALU

TOP DECK 2.0mm 1.6mm

TOP DECK FLEX NO POST BEARING BUSHING

BALANCE 10 /g

STEERING LOCK 29 /degr.

CHASSIS BRACE BRASS ALU

SUSP. HOLDERS FRONT REAR

SERVO HOLDER FORWARD STANDARD

MOTOR MOUNT

CHASSIS GRAPHITE ALU ALU-FLEX OTHER

FF FR RF RR

STEERING PLATE 8mm 8.5mm

C-HUB M H G ALU

SHIM 1.0 /mm

DRIVE SHAFT 52mm 51mm 50mm BB OTHER

SHIM 1.0 /mm

SHIM 1.0 /mm

DRIVE SHAFT ECS CVD OTHER

SHIM 4 /mm

REAR HUB M H G ALU

OPTIONAL ALU HUB

STEER.BLOCK M H G ALU

OFFSET STANDARD -0.75

MEASURE UNDER ARM

DOWNSTOP/mm

FRONT CAMBER 2 /degr.

SHOCK TOWERS HIGHER SLP STANDARD ULP LOWER ULP

REAR CAMBER 2 /degr.

FRONT ARM HARD (H) GRAPHITE (G) SHORT LONG

REAR ARM HARD (H) GRAPHITE (G) SHORT LONG