

SET-UP SHEET

XRAY XB8'20 PIVOT BALL

RACE		
TRACK	ALC longvic	
NAME		DATE

TEMPERATURE AIR	15	TEMPERATURE TRACK	
-----------------	----	-------------------	--

LAPS	FINAL POSITION	BEST LAPTIME	RACE LENGTH
		/sec	/min

TRACKS			
SIZE	<input checked="" type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT

TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH
----------	------------------------------	--	-------------------------------

SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> BUMPY
---------	---------------------------------	---------------------------------	---

TYPE	<input checked="" type="checkbox"/> HARD PACKED	<input type="checkbox"/> SOFT DIRT	<input type="checkbox"/> CLAY
	<input type="checkbox"/> BLUE GROVE	<input checked="" type="checkbox"/> ASTRO TURF	<input type="checkbox"/> GRASS

CONDITION	<input checked="" type="checkbox"/> DRY	<input type="checkbox"/> DUSTY	<input type="checkbox"/> WET	<input type="checkbox"/> MUD
-----------	---	--------------------------------	------------------------------	------------------------------

DIFFERENTIAL					
FRONT		CENTER		REAR	
CASE MATERIAL	STD	STD	STD	CASE MATERIAL	
OIL	7	10	3	OIL	
CROWN GEAR				CROWN GEAR	

GEARING			
CLUTCH BELL	13	/T	48
SHOE	3x H alu		3x 1.0
			SPUR GEAR

FRONT	SHOCKS		REAR
2018	TYPE	2018	
3dot	SPRINGS	3dot	
soft clear	MEMBRANE	soft clear	
700	OIL	750	

STANDARD PISTONS			
<input type="checkbox"/> 6 HOLES	<input type="checkbox"/> 1.1 mm	<input type="checkbox"/> 6 HOLES	<input type="checkbox"/>
<input checked="" type="checkbox"/> 8 HOLES	<input checked="" type="checkbox"/> 1.2 mm	<input checked="" type="checkbox"/> 8 HOLES	<input checked="" type="checkbox"/>
<input type="checkbox"/> 10 HOLES	<input type="checkbox"/> 1.3 mm	<input type="checkbox"/> 10 HOLES	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/> 1.4 mm	<input type="checkbox"/>	<input type="checkbox"/>
OTHER			
VALVE PISTONS			
<input type="checkbox"/> 5+2 HOLES	<input type="checkbox"/> 1.5 mm	<input type="checkbox"/> 5+2 HOLES	<input type="checkbox"/>
<input type="checkbox"/> 6+2 HOLES	<input type="checkbox"/> 1.3 mm	<input type="checkbox"/> 6+2 HOLES	<input type="checkbox"/>
<input type="checkbox"/> 8+2 HOLES	<input type="checkbox"/> 1.4 mm	<input type="checkbox"/> 8+2 HOLES	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/> 1.2 mm	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/> 1.3 mm	<input type="checkbox"/>	<input type="checkbox"/>

FRONT	ANTI-ROLL BAR		REAR
2.4	THICKNESS	2.6	
	/mm	/mm	

FRONT	TIRES		REAR
PC CLAYMORE	BRAND	PC CLAYMORE	
C1	COMPOUND	C1	
STD	INSERTS	STD	
STD	WHEELS	STD	

ENGINE	
TYPE	FX K301 EC
MUFFLER	FX 2108
MANIFOLD	FX medium
PLUG	FX X3
FUEL	SIGMA 25%

BODY		WEIGHT	
HS	HS-LIGHT	TOTAL	/g
<input type="checkbox"/>	<input checked="" type="checkbox"/>		
OTHER			

