

SET-UP SHEET

XRAY XB4'21

RACE	Practice	
TRACK	ELCERAM	
NAME	Max	DATE 17.1.

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION		FINAL POSITION	

TRACK		
SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM
TRACTION	<input type="checkbox"/> VERY-LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> VERY-HIGH	
SURFACE	<input checked="" type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM
TYPE	<input type="checkbox"/> CLAY	<input checked="" type="checkbox"/> CARPET
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY

DIFFERENTIAL TYPE		
FRONT ↓	MIDDLE ↓	REAR ↓
GEAR DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
BALL DIFF <input type="checkbox"/>	SLIPPER <input checked="" type="checkbox"/>	BALL DIFF <input type="checkbox"/>
ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>
60° 90° 120°	60° 90° 120°	60° 90° 120°
OIL 30k cst	OIL cst	OIL 60k cst

SATELLITE GEARS		
COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>
STEEL <input checked="" type="checkbox"/>	STEEL <input type="checkbox"/>	STEEL <input checked="" type="checkbox"/>
CROWN GEAR	SLIPPER	CROWN GEAR
40T <input checked="" type="checkbox"/> 41T	1 mm SLIPPING ADJUSTMENT	40T <input checked="" type="checkbox"/> 41T

FRONT	SLIPPER SETTING	REAR
PAD	LOCK ALU DISC	PAD
yell	<input checked="" type="checkbox"/>	yell
	81 T	black
	YES NO	

GEARING	
PINION 20 T	CENTER DIFF SPUR

FRONT	SHOCKS	REAR
368195 cut	SPRINGS	368294
cst 750	OIL	cst 550
REBOUND		
<input checked="" type="checkbox"/> 2 HOLES	PISTONS	<input checked="" type="checkbox"/> 2 HOLES
<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> ø1.2mm <input type="checkbox"/> ø1.3mm <input checked="" type="checkbox"/> ø1.4mm <input type="checkbox"/> ø1.6mm <input type="checkbox"/> ø1.7mm	<input type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	CUSTOM PISTONS	<input type="checkbox"/> 6 HOLES
HOLES	mm mm	HOLES

FRONT	ANTI ROLL BAR	REAR
2 mm	THICKNESS	2 mm

FRONT	TIRES	REAR
	BRAND	
	COMPOUND	
	INSERTS	
	WHEELS	

ELECTRONICS		
MOTOR	HW 5.5	XR10 Pro G2
MOTOR TIMING	35	Sunpadow 3800
BATTERY SIZE		SPEEDO
STD. SHORT <input type="checkbox"/> LOW SHORT <input checked="" type="checkbox"/>		BATTERY

BODY	
TYPE	XB4C
	STANDARD <input type="checkbox"/> LIGHT <input checked="" type="checkbox"/>

COMMENTS

FRONT	APPLIED <input type="radio"/> <input checked="" type="checkbox"/> APPLIED	REAR
STEERING BLOCK MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	SHIM mm DRIVE SHAFT CVD <input checked="" type="checkbox"/> ECS Length 83 /mm	REAR UPRIGHT DRIVE SHAFT Length 75 /mm SHIM 2 mm SHIMS 2 /mm HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>
LONGER BUSHINGS UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	LOWER SHOCK POSITION #107711 GAUGE mm DOWNSTOP	#325341 ADJ. DRIVE AXLE 1 2 3 4 1° <input checked="" type="checkbox"/> 0.5° #107711 GAUGE

FRONT	CASTER	CASTER BLOCK	WING CUTTING LINE	WING SIDE LINE
CASTER 6° <input type="checkbox"/> 9° <input checked="" type="checkbox"/> 12° <input type="checkbox"/>	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	1 2 3 4 5 1 <input checked="" type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> 5 <input type="checkbox"/>	HIGHER <input type="checkbox"/> LOWER <input checked="" type="checkbox"/>	
OFFSET 3	BUMP STEER SHIM 2 mm	OFFSET 4 /slots	WING POSITION UP <input type="checkbox"/> MIDDLE <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	
		UPRIGHT WHEELBASE SHIM 1 /mm IN FRONT OF ARM	WING THICKNESS 0.75 <input type="checkbox"/> 1 <input checked="" type="checkbox"/> 1.5 TYPE TEC	

FF	FR	ROLL CENTER	RF	RR 2°
1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>	1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>	1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>	1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>	1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>
		ECCENTRIC BUSHINGS UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>		

FRONT TOE	STEER. PLATE	REAR TOE	GRAPHITE FOR REAR BRACE	REAR BRACE	ARM SHIM
1	HARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	2	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	2 mm
FRONT TOE OUT IN	BUMP STEER SHIM UNDER STEER PLATE SERVO SAVER SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/> TIGHT <input checked="" type="checkbox"/> MATERIAL STANDARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	REAR TOE IN OUT			

FRONT CAMBER	FRONT DIFF HEIGHT	REAR DIFF HEIGHT	REAR CAMBER
1.5°	DOWNSTOP SHIM mm LENGTH 22 mm UPSTOP SHIM 2 mm	DOWNSTOP SHIM mm LENGTH 28 mm UPSTOP SHIM 2 mm	2
	COLLAR STANDARD <input checked="" type="checkbox"/> -2mm	COLLAR STANDARD <input type="checkbox"/> -2mm	
	RIDE HEIGHT 13 mm #107720 GAUGE	RIDE HEIGHT 13 mm #107720 GAUGE	

FRONT ARMS	BALANCE	CHASSIS	BALANCE	REAR ARMS
LONG <input checked="" type="checkbox"/> SHORT <input type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	g T-BRACE	STANDARD <input checked="" type="checkbox"/> 2.5mm	fan ~10g	LONG <input checked="" type="checkbox"/> SHORT <input type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>
		SIDE GUARDS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	35g	CHASSIS FLEX SCREW USED <input type="checkbox"/> SCREW NOT USED <input checked="" type="checkbox"/>