

SET-UP SHEET

XRAY XB8'20 PIVOT BALL

RACE	Nordsvenskan 2020, NS4, Final		
TRACK	Alvik Ring		
NAME	Fredrik Kling	DATE	2020-08-29
TEMPERATURE AIR	20	TEMPERATURE TRACK	18
LAPS	45	FINAL POSITION	8
BEST LAPTIME	36,763 /sec	RACE LENGTH	30 /min
TRACKS			
SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> BUMPY
TYPE	<input checked="" type="checkbox"/> HARD PACKED	<input type="checkbox"/> SOFT DIRT	<input type="checkbox"/> CLAY
	<input type="checkbox"/> BLUE GROVE	<input checked="" type="checkbox"/> ASTRO TURF	<input type="checkbox"/> GRASS
CONDITION	<input checked="" type="checkbox"/> DRY	<input type="checkbox"/> DUSTY	<input type="checkbox"/> WET
	<input type="checkbox"/> MUD		
DIFFERENTIAL			
CASE MATERIAL	FRONT Stock	CENTER Stock	REAR Stock
OIL	6K	7K	3K
CROWN GEAR	46		46
GEARING			
CLUTCH BELL	13T	/T	48T
SHOE	4xAlu	1 mm	SPRING
	REDS Quattro	M tension	
SHOCKS			
FRONT	Stock	TYPE	Stock
	4 dot	SPRINGS	3 dot
	Honeycomb	MEMBRANE	Honeycomb
	550 /cSt	OIL	600 /cSt
STANDARD PISTONS			
<input type="checkbox"/> 6 HOLES	<input type="checkbox"/> 1.1 mm	<input type="checkbox"/> 6 HOLES	<input type="checkbox"/>
<input checked="" type="checkbox"/> 8 HOLES	<input checked="" type="checkbox"/> 1.2 mm	<input checked="" type="checkbox"/> 8 HOLES	<input checked="" type="checkbox"/>
<input type="checkbox"/> 10 HOLES	<input type="checkbox"/> 1.3 mm	<input type="checkbox"/> 10 HOLES	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/> 1.4 mm	<input type="checkbox"/>	<input type="checkbox"/>
VALVE PISTONS			
<input type="checkbox"/> 5+2 HOLES	<input type="checkbox"/> 1.5 mm	<input type="checkbox"/> 5+2 HOLES	<input type="checkbox"/>
<input type="checkbox"/> 6+2 HOLES	<input type="checkbox"/> 1.3 mm	<input type="checkbox"/> 6+2 HOLES	<input type="checkbox"/>
<input type="checkbox"/> 8+2 HOLES	<input type="checkbox"/> 1.4 mm	<input type="checkbox"/> 8+2 HOLES	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/> 1.2 mm	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/> 1.3 mm	<input type="checkbox"/>	<input type="checkbox"/>
ANTI-ROLL BAR			
FRONT	2,5 /mm	THICKNESS	2,6 /mm
TIRES			
FRONT	AKA	BRAND	AKA
	S LW	COMPOUND	S LW
	Red	INSERTS	Red
	Impact	WHEELS	Impact
ENGINE			
TYPE	REDS 721 S Gen 2		
MUFFLER	3143 x-one Torque		
MANIFOLD			
PLUG	P3		
FUEL	Runnertime 25%		
BODY			
HS	<input checked="" type="checkbox"/>	HS-LIGHT	<input type="checkbox"/>
OTHER		TOTAL	/g

FRONT		REAR	
STEERING BLOCK HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> UPPER ARM SHIM 0 1mm 2mm OTHER <input type="checkbox"/> OFFSET 0 +1 +2 <input checked="" type="checkbox"/> PIVOT NUT ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/> FRONT DROOP MEASURE UNDER WHEEL AXLE #107717 GAUGE		SHOCK TOWERS FRONT ALU <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> REAR ALU <input checked="" type="checkbox"/> UPPER SHOCK POSITION 1 2 3 4 5 6 7 8 REAR ROLL CENTER 1 2 3 LOWER ROLL CENTER 1 2 3 REAR DROOP MEASURE UNDER WHEEL AXLE #107717 GAUGE	
FRONT 		REAR 	
UPPER ROLL CENTER 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> CASTER SHIM 0 1.0 1.0 2.0 BUMP STEER SHIM STEERING PLATE /mm STEERING BLOCK /mm WHEELBASE SHIM POSITION 0mm 2mm 4mm SHIMS BEHIND FRONT ARM SHIMS IN FRONT OF REAR ARM		REAR WING STANDARD <input checked="" type="checkbox"/> LEXAN <input type="checkbox"/> FRONT MIDDLE REAR OTHER GRAPHITE BRACE WITHOUT <input type="checkbox"/> 1-PIECE <input type="checkbox"/> 2-PIECES <input checked="" type="checkbox"/> WHEELBASE SHIM POSITION 0mm 2mm 4mm SHIMS IN FRONT OF REAR ARM	
FRONT 		REAR 	
1 FRONT TOE OUT STEERING PLATE 1 DOTS <input type="checkbox"/> 2 DOTS <input checked="" type="checkbox"/> WHEELBASE 0mm 1mm 2mm 3mm 4mm SHIMS IN FRONT OF UPRIGHT 2 REAR TOE IN		FRONT DRIVE SHAFT CVD <input checked="" type="checkbox"/> UNIVERSAL <input type="checkbox"/> ACKERMANN POSITION 4 3 2 1 TOP DECK COMPOSITE <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> DRIVE SHAFT CVD <input checked="" type="checkbox"/> UNIVERSAL <input type="checkbox"/> GRAPHITE BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> DRIVE SHAFT CVD <input checked="" type="checkbox"/> UNIVERSAL <input type="checkbox"/> REAR DRIVE SHAFT CVD <input checked="" type="checkbox"/> UNIVERSAL <input type="checkbox"/> REAR WING STANDARD <input checked="" type="checkbox"/> LEXAN <input type="checkbox"/> FRONT MIDDLE REAR OTHER	
FRONT 		REAR 	
FRONT CAMBER -3 LENGTH mm UPPER ARM SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> LOWER ARM SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> RIDE HEIGHT 23 /mm #107717 GAUGE		REAR CAMBER -1,5 LENGTH /mm RIDE HEIGHT 27 /mm #107717 GAUGE	