

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE	US Indoor Champs		
TRACK	VTA		
NAME	Cory Craig	DATE	11-26-21

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
	2		13.7 /sec	/	

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
SOLID AXLE	<input checked="" type="checkbox"/> YES	
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 10000 /cSt
PINION 46 /T	SPUR GEAR 88 /T	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
2.7	XRAY SPRINGS	2.7
500	OIL /cSt	500
	REBOUND %	
<input type="checkbox"/> YES <input type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input type="checkbox"/> NO

PISTONS	
<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS	<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS
1.0mm	1.1mm
1.2mm	

SHOCK LENGTH FRONT	8.7 /mm	SHOCK LENGTH REAR	8.7 /mm
--------------------	---------	-------------------	---------

1.4	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.4
-----	--------------	---------------	--------------	-----

VTA	TIRES	VTA
SXT black	ADDITIVE	SXT Black
2 mins	ADDITIVE TIMING	2 mins

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT	1425 /g	WEIGHT BALANCE	FRONT 50 % REAR 50 %
--------------	---------	----------------	----------------------

MOTOR	Motiv MC4	TIMING	
-------	-----------	--------	--

ESC	Tekin RS Pro	BATTERIES	Motiv Defy 6000
-----	--------------	-----------	-----------------

BODY	camaro	WING	
------	--------	------	--

	BODY POSITION Dimension from body post to window bottom line /mm
	WING SIDE PLATE YES <input type="checkbox"/> NO <input type="checkbox"/> Dimension from body post to upper holder /mm
Dimension from edge to surface /mm	

COMMENTS	droop: front : 1.5mm override height rear : 2.0mm over ride height dual rate (DR) @ 84
----------	---

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
5° 4° 3° Adjust with eccentric bushings	BUMP STEER 4 /mm HEIGHT 17 /mm SHIM 5 /mm	0.5° 1.5° 2.5° 3.5° 4.5° 5.5° Adjust with eccentric bushings
2 /mm FF 5.2 /mm FR 2 /mm RIDE HEIGHT SERVO SAVER SERVO HORN	TOE GAIN 5 /mm 2.5 /mm RF 5.4 /mm RR 2.5 /mm RIDE HEIGHT	

FRONT	FRONT SUSPENSION	FRONT HUB
-2 /deg. CAMBER Left = Right BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> /mm	5 /mm SHIM 2 /mm FRONT SHOCK POSITION FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> BULKHEAD SHIMS YES <input type="checkbox"/> 3mm <input checked="" type="checkbox"/> NO <input type="checkbox"/> DRIVE SHAFT 58mm 59mm STD. BEARING #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge	SHIM .5 /mm COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>

REAR	REAR SUSPENSION	REAR HUB
-2 /deg. CAMBER Left = Right BODY POST VERTICAL <input checked="" type="checkbox"/> HORIZONTAL <input type="checkbox"/> 1.0 /mm SHIM 2.0 /mm REAR SHOCK POSITION DRIVE SHAFT 52mm 54mm STD. BEARING #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge	SHIM .5 /mm COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	

FRONT TOP VIEW	REAR
-1 TOE OUT Left = Right ACKERMANN SHIM /mm DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> SHIM /mm	2.5 TOE IN Left = Right SHIM /mm DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> SHIM /mm
TOP DECK FLEX NONE <input type="checkbox"/> BEARING <input checked="" type="checkbox"/> TOP DECK 1.6mm <input type="checkbox"/> 2.0mm <input checked="" type="checkbox"/> TOP DECK CUTTING	

FRONT BOTTOM VIEW	REAR
STEER. LOCK 25 @ 100DR /deg. STEER. SHIM SIZE 7.5 /mm FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> FR RE SERVO HOLDER CHASSIS GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU FLEX <input type="checkbox"/> REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	T-BRACE ALU <input type="checkbox"/> BRASS <input checked="" type="checkbox"/> MOTOR MOUNT CHASSIS T-BRACE STEER. PLATE STANDARD <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>