

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE	Start Setup Gvk	
TRACK		
NAME	GastonvK	DATE 26-11-2021

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
			/sec	/	

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
SOLID AXLE	<input checked="" type="checkbox"/> YES	
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 7000 /cSt
PINION 30 /T	SPUR GEAR 79 /T	FINAL DRIVE RATIO 5.00

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.6
400	OIL /cSt	400
	REBOUND %	
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input type="checkbox"/> 3 HOLES	PISTONS	3 HOLES <input type="checkbox"/>
<input checked="" type="checkbox"/> 4 HOLES	1.0mm	4 HOLES <input checked="" type="checkbox"/>
<input type="checkbox"/> PSS	1.1mm	<input type="checkbox"/> PSS
	1.2mm	

SHOCK LENGTH FRONT 9 /mm	SHOCK LENGTH REAR 9 /mm
--------------------------	-------------------------

1.4	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
-----	--------------	---------------	--------------	-----

Matrix carpet	TIRES	Matrix carpet
MR33	ADDITIVE	MR33
	ADDITIVE TIMING	

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT 1325 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
----------------------	----------------	------------	-----------

MOTOR Orca 17.5	TIMING
-----------------	--------

ESC Orca ETS	BATTERIES	LRP 6100
--------------	-----------	----------

BODY Brutale 0.7	WING
------------------	------

	BODY POSITION Dimension from body post to window bottom line Dimension from body post to upper holder WING SIDE PLATE YES <input type="checkbox"/> NO <input type="checkbox"/>
--	---

COMMENTS
 Futuba BLS 571 servo (41G), R304SB-E RX, 30 MM Hudy Fan
 Hiro Seiko Titanium screws on top,
 Steel in Bottom

FRONT CASTER	BUMP STEER	HEIGHT	SHIM	FRONT & REAR SUSPENSION	REAR CASTER	TOE GAIN
Adjust with eccentric bushings	5 /mm	/mm	4 /mm		Adjust with eccentric bushings	5 /mm
2 /mm FF	5.2 /mm	FR 2 /mm	<input checked="" type="checkbox"/> SERVO SAVER		2 /mm RF	5.4 /mm
<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> SERVO HORN				<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/>

2 /deg. CAMBER	Left = Right	BODY STOP	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	FRONT SUSPENSION	1.5 /mm SHIM 2 /mm	FRONT HUB	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
			/mm				
				FRONT BRACE	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>		
				BULKHEAD SHIMS	YES <input checked="" type="checkbox"/> 3mm <input type="checkbox"/> NO		
				DRIVE SHAFT			
				58mm 59mm	STD. BEARING		
				#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	6.2 /mm	DOWNSTOP

2 /deg. CAMBER	Left = Right	BODY POST	VERTICAL <input type="checkbox"/> HORIZONTAL <input type="checkbox"/>	REAR SUSPENSION	1 /mm SHIM 2 /mm	REAR HUB	COMPOSITE <input type="checkbox"/> ALU <input type="checkbox"/>
				REAR SHOCK POSITION			
				DRIVE SHAFT			
				52mm 54mm	STD. BEARING		
				#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	4.2 /mm	DOWNSTOP

FRONT TOP VIEW	REAR
1 TOE OUT	2.5 TOE IN
Left = Right	Left = Right
ACKERMANN	SHIM
SHIM 1 /mm	/mm
DIFF POSITION	DIFF POSITION
UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>
UPPER ARM	UPPER ARM
STANDARD <input checked="" type="checkbox"/>	STANDARD <input checked="" type="checkbox"/>
STEERING BRIDGE	TOP DECK FLEX
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	NONE <input type="checkbox"/> BEARING <input checked="" type="checkbox"/>
TOP DECK	TOP DECK
STANDARD <input checked="" type="checkbox"/> SPLITTED <input type="checkbox"/>	1.6mm <input type="checkbox"/> 2.0mm <input checked="" type="checkbox"/>
OFFSET	OFFSET
STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/>	STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/>
SHIM/mm	SHIM/mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK	T-BRACE
/deg.	ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/>
STEER. SHIM	
SIZE 7.5 /mm	
FRONT BRACE	MOTOR MOUNT
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	FR RE
SERVO HOLDER	CHASSIS T-BRACE
FRONT ARMS	CHASSIS
MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input checked="" type="checkbox"/>
STEER. PLATE	REAR ARMS
STANDARD <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>