

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE	Practice		
TRACK	HOTLAP		
NAME	Hayate3009	DATE	07/01/2022

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
			9.5 /sec	30/	5:00

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
SOLID AXLE <input checked="" type="checkbox"/> YES		
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 50000 /cSt
PINION 38 /T	SPUR GEAR 100 /T	FINAL DRIVE RATIO 5.0

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
#350	OIL /cSt	#350
	REBOUND %	
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS	PISTONS 1.0mm <input type="checkbox"/> 1.1mm <input checked="" type="checkbox"/> 1.2mm	<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS
SHOCK LENGTH FRONT 9.0 /mm		SHOCK LENGTH REAR 9.0 /mm

1.4	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
-----	--------------	---------------	--------------	-----

RUSH 30CPM	TIRES	RUSH 30CPM
HOTLAP	ADDITIVE	HOTLAP
5	ADDITIVE TIMING	5

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT 1290 /g	WEIGHT BALANCE	FRONT %	REAR %
MOTOR HOTLAP 13.5	TIMING		
ESC XR10PRO G2S	BATTERIES	GSTILE 5600	
BODY BWOAH	WING	RC-MISSION	

BODY POSITION

WING SIDE PLATE
YES ☐ NO ☐

COMMENTS

FRONT & REAR SUSPENSION
<div> <p>FRONT CASTER Adjust with eccentric bushings 5° 4° 3°</p> <p>BUMP STEER 5 /mm</p> <p>HEIGHT 17.5 /mm</p> <p>SHIM 3 /mm</p> <p>TOE GAIN 6 /mm</p> <p>TOE IN 0.5 /mm</p> <p>TOE OUT 5.4 /mm</p> <p>FRIDE HEIGHT 5.2 /mm</p> <p>RRIDE HEIGHT 5.4 /mm</p> <p>RRIDE HEIGHT 0.5 /mm</p> <p><input type="checkbox"/> SERVO SAVER</p> <p><input checked="" type="checkbox"/> SERVO HORN</p> </div> <div> <p>REAR CASTER Adjust with eccentric bushings 0.5° 1.5° 2.5° 3.5° 4.5° 5.5°</p> <p>FRONT HUB COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/></p> <p>SHIM 1.5 /mm</p> <p>REAR HUB COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/></p> <p>SHIM 1.5 /mm</p> </div>

FRONT SUSPENSION	REAR SUSPENSION
<p>1 /deg. CAMBER Left = Right</p> <p>BODY STOP YES <input type="checkbox"/> NO <input checked="" type="checkbox"/></p> <p>FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/></p> <p>BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm <input type="checkbox"/> NO</p> <p>DRIVE SHAFT 58mm <input checked="" type="checkbox"/> 59mm <input type="checkbox"/> STD. BEARING <input checked="" type="checkbox"/></p> <p>FRONT SHOCK POSITION 1 2 3 4</p> <p>SHIM 2 /mm</p> <p>SHIM 1 /mm</p> <p>DOWNSTOP 6 /mm</p>	<p>1.5 /deg. CAMBER Left = Right</p> <p>BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/></p> <p>REAR SHOCK POSITION 1 2 3 4</p> <p>SHIM 1 /mm</p> <p>SHIM 2 /mm</p> <p>DOWNSTOP 5.4 /mm</p>

FRONT TOP VIEW	REAR
<p>1 TOE OUT Left = Right</p> <p>ACKERMANN SHIM /mm</p> <p>DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/></p> <p>UPPER ARM STANDARD <input checked="" type="checkbox"/></p> <p>STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/></p> <p>TOP DECK FLEX NONE <input type="checkbox"/> BEARING <input type="checkbox"/></p> <p>TOP DECK 1.6mm <input type="checkbox"/> 2.0mm <input type="checkbox"/></p> <p>OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/></p> <p>SHIM/mm</p>	<p>1 TOE IN Left = Right</p> <p>SHIM /mm</p> <p>DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/></p> <p>UPPER ARM STANDARD <input checked="" type="checkbox"/></p> <p>STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/></p> <p>TOP DECK FLEX NONE <input type="checkbox"/> BEARING <input type="checkbox"/></p> <p>TOP DECK 1.6mm <input type="checkbox"/> 2.0mm <input type="checkbox"/></p> <p>OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/></p> <p>SHIM/mm</p>

FRONT BOTTOM VIEW	REAR
<p>STEER. LOCK 24 /deg.</p> <p>STEER. SHIM SIZE 6 /mm</p> <p>FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/></p> <p>FR SERVO HOLDER FR RE</p> <p>CHASSIS GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU FLEX <input type="checkbox"/></p> <p>FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/></p> <p>STEER. PLATE STANDARD <input checked="" type="checkbox"/> +1mm <input type="checkbox"/></p>	<p>T-BRACE ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/></p> <p>CHASSIS T-BRACE</p> <p>REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/></p>