

# SET-UP SHEET

VER.01 ©XRAY

# XRAY X4'22

RACE	RCCA	
TRACK	RCCA	
NAME	Viet Ta	DATE 1/13/22

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
	Last	Last	/sec	/	

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
SOLID AXLE	<input checked="" type="checkbox"/> YES	
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 6000 /cSt
PINION 48 /T	SPUR GEAR 96 /T	FINAL DRIVE RATIO 3.8

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
450	OIL /cSt	450
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

PISTONS	
<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS	<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS
1.0mm	1.1mm
1.2mm	

SHOCK LENGTH FRONT 9.0 /mm	SHOCK LENGTH REAR 9.0 /mm
----------------------------	---------------------------

1.4	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
-----	--------------	---------------	--------------	-----

Hudy C3-28	TIRES	Hudy C3-28
SXT 3.0	ADDITIVE	SXT 3.0
5:00	ADDITIVE TIMING	5.00

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT 1320 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
----------------------	----------------	------------	-----------

MOTOR 21.5	TIMING
------------	--------

ESC HW XR10 Pro G2	BATTERIES Sunpadow 6000
--------------------	-------------------------

BODY Twister Speciale	WING	Included
-----------------------	------	----------

 Dimension from body post to window bottom line /mm	BODY POSITION
 Dimension from body post to upper holder /mm WING SIDE PLATE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	
 Dimension from edge to surface /mm	

COMMENTS
I need help.

FRONT CASTER	BUMP STEER	HEIGHT	SHIM	REAR CASTER	TOE GAIN
<input type="checkbox"/> 5° <input checked="" type="checkbox"/> 4° <input type="checkbox"/> 3° Adjust with eccentric bushings	4 /mm	16 /mm	6 /mm	<input type="checkbox"/> 0.5° <input checked="" type="checkbox"/> 1.5° <input type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° Adjust with eccentric bushings	7.5 /mm
 1.5 /mm FF 5.2 /mm RIDE HEIGHT FR 1.5 /mm <input checked="" type="checkbox"/> SERVO SAVER <input type="checkbox"/> SERVO HORN				 2 /mm RF 5.4 /mm RIDE HEIGHT RR 2 /mm	

FRONT	REAR
CAMBER -2 /deg. Left=Right BODY STOP YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> FRONT SUSPENSION FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm <input type="checkbox"/> NO DRIVE SHAFT 58mm <input checked="" type="checkbox"/> 59mm <input type="checkbox"/> STD. BEARING #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 6.6 /mm DOWNSTOP	CAMBER -2 /deg. Left=Right BODY POST VERTICAL <input checked="" type="checkbox"/> HORIZONTAL <input type="checkbox"/> REAR SUSPENSION SHIM 1.5 /mm SHIM 2 /mm FRONT SHOCK POSITION 1 2 3 4 FRONT HUB COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> SHIM .5 /mm #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 6.6 /mm DOWNSTOP

FRONT	REAR
CAMBER -2 /deg. Left=Right BODY POST VERTICAL <input checked="" type="checkbox"/> HORIZONTAL <input type="checkbox"/> REAR SUSPENSION SHIM 1 /mm SHIM 1.5 /mm REAR SHOCK POSITION 1 2 3 4 REAR HUB COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> SHIM 1.5 /mm #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.0 /mm DOWNSTOP	

FRONT TOP VIEW	REAR
TOE OUT -1 Left=Right ACKERMANN SHIM 1 /mm DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm TOP DECK STANDARD <input type="checkbox"/> SPLITTED <input checked="" type="checkbox"/> TOP DECK FLEX NONE <input type="checkbox"/> BEARING <input checked="" type="checkbox"/> TOP DECK 1.6mm <input type="checkbox"/> 2.0mm <input checked="" type="checkbox"/>	TOE IN -3 Left=Right SHIM /mm DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm TOP DECK CUTTING <input type="checkbox"/>

FRONT BOTTOM VIEW	REAR
STEER. LOCK 26 /deg. STEER. SHIM SIZE /mm FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> FR SERVO HOLDER CHASSIS GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU FLEX <input type="checkbox"/> FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	T-BRACE ALU <input type="checkbox"/> BRASS <input checked="" type="checkbox"/> MOTOR MOUNT CHASSIS T-BRACE REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>