

SET-UP SHEET

XRAY XB4'22

RACE	Basic for DIRT	
TRACK	Trencin	
NAME	XRAY	DATE

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION		FINAL POSITION	

TRACK		
SIZE	<input type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM
TRACTION	<input type="checkbox"/> VERY-LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> VERY-HIGH	
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM
TYPE	<input checked="" type="checkbox"/> CLAY	<input type="checkbox"/> CARPET
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY

DIFFERENTIAL TYPE		
FRONT ↓	MIDDLE ↓	REAR ↓
GEAR DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
BALL DIFF <input type="checkbox"/>	SLIPPER <input type="checkbox"/>	BALL DIFF <input type="checkbox"/>
ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>
60° 90° 120°	60° 90° 120°	60° 90° 120°
OIL 7K cSt	OIL 100K cSt	OIL 7K cSt

SATELLITE GEARS		
COMPOSITE <input checked="" type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/>
STEEL <input type="checkbox"/>	STEEL <input type="checkbox"/>	STEEL <input type="checkbox"/>
40T <input checked="" type="checkbox"/> 41T	CROWN GEAR	40T <input checked="" type="checkbox"/> 41T

CENTRAL SLIPPER & ONE-WAY SETTING	
	ONE-WAY TIGHTNESS
SLIPPING ADJUSTMENT	LOOSE
	1 CCW TURN (BASIC SETUP)
	FULLY TIGHTEN

GEARING	
PINION	81
CENTER DIFF SPUR	

FRONT	SHOCKS	REAR
45mm/2dots	SPRINGS	60mm/2dots
cSt 600	OIL	cSt 500
% 0	REBOUND	% 0
<input checked="" type="checkbox"/> 2 HOLES	PISTONS	<input checked="" type="checkbox"/> 2 HOLES
<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> ø1.2mm	<input type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	<input type="checkbox"/> ø1.3mm	<input type="checkbox"/> 6 HOLES
	<input checked="" type="checkbox"/> ø1.4mm	
	<input type="checkbox"/> ø1.6mm	
	<input checked="" type="checkbox"/> ø1.7mm	
	CUSTOM PISTONS	
	mm	

FRONT	ANTI ROLL BAR	REAR
1.2 mm	THICKNESS	1.3 mm

FRONT	TIRES	REAR
	BRAND	
	COMPOUND	
	INSERTS	
XRAY	WHEELS	XRAY

ELECTRONICS	
MOTOR	SPEEDO
MOTOR TIMING	BATTERY
BATTERY SIZE	
STD. SHORT <input type="checkbox"/> LOW SHORT <input type="checkbox"/>	

BODY	
TYPE	XRAY GAMMA 4D STANDARD <input checked="" type="checkbox"/> LIGHT <input type="checkbox"/>

COMMENTS

FRONT	APPLIED <input type="radio"/> <input checked="" type="checkbox"/> APPLIED	REAR
ALU C-HUB SHIM UP /mm DOWN /mm LONGER BUSHINGS UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> DRIVE SHAFT CVD <input checked="" type="checkbox"/> ECS <input type="checkbox"/> Length 83 /mm SHIM 2 mm LOWER SHOCK POSITION #107711 GAUGE DOWNSTOP mm #107701 SUPPORT BLOCKS #107711 GAUGE	REAR UPRIGHT DRIVE SHAFT Length 75 /mm SHIM 4 mm SHIMS 2 /mm HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> #325341 ADJ. DRIVE AXLE 1 2 3 4 1° 0.5° DOWNSTOP mm #107711 GAUGE	

FRONT	CASTER	CASTER BLOCK	WING CUTTING LINE	WING SIDE LINE
CASTER 6° <input type="checkbox"/> 7° <input checked="" type="checkbox"/> 9° <input type="checkbox"/> 12° <input type="checkbox"/> OFFSET 0 #107711 GAUGE	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> BUMP STEER SHIM 2 mm	1 2 3 4 5 1 2 3 4 5 OFFSET 0 /slots UPRIGHT WHEELBASE SHIM 1 /mm IN FRONT OF ARM	HIGHER <input checked="" type="checkbox"/> LOWER <input type="checkbox"/> WING POSITION UP <input checked="" type="checkbox"/> MIDDLE <input type="checkbox"/> DOWN <input type="checkbox"/> WING THICKNESS 0.75 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 1.5 <input type="checkbox"/> TYPE Rank	

FF	FR	ROLL CENTER	RF	RR
1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>	1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>	1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>	1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>	2° <input checked="" type="checkbox"/> 1° <input type="checkbox"/> 0.5° <input type="checkbox"/>

FRONT TOE	STEER. PLATE	REAR TOE	GRAPHITE FOR REAR BRACE	REAR BRACE	ARM SHIM
1	HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> BUMP STEER SHIM 5 mm SHIM UNDER STEER PLATE SERVO SAVER SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> TIGHT <input type="checkbox"/> MATERIAL STANDARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	2	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	2 mm

FRONT CAMBER	FRONT DIFF HEIGHT	REAR DIFF HEIGHT	REAR CAMBER
2	DOWNSTOP SHIM 0 mm LENGTH 22 mm UPSTOP SHIM 1 mm COLLAR STANDARD <input checked="" type="checkbox"/> -2mm	2 DOWNSTOP SHIM 2 mm LENGTH 27 mm UPSTOP SHIM 0 mm COLLAR STANDARD <input checked="" type="checkbox"/> -2mm	2

FRONT ARMS	BALANCE	SIDE GUARDS	BALANCE	REAR ARMS
LONG <input checked="" type="checkbox"/> SHORT <input type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	g	HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	g	LONG <input checked="" type="checkbox"/> SHORT <input type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>
CHASSIS FLEX SCREW USED <input checked="" type="checkbox"/> SCREW NOT USED <input type="checkbox"/>				