

# SET-UP SHEET

VER.01 ©XRAY

# XRAY X4'22

RACE	Essex winter series		
TRACK	EWS Round 3		
NAME	Harley Eldridge	DATE	16/1/22

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
	5	5	14.4 /sec	21/	5:10

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
SOLID AXLE	<input checked="" type="checkbox"/> YES	
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 8k /cSt
PINION 23 /T	SPUR GEAR 84 /T	FINAL DRIVE RATIO 7.2

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.6
350	OIL /cSt	300
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

PISTONS	
<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS	<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS
1.0mm 1.1mm 1.2mm	1.0mm 1.1mm 1.2mm

SHOCK LENGTH FRONT	9 /mm	SHOCK LENGTH REAR	9 /mm
--------------------	-------	-------------------	-------

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
-----	--------------	---------------	--------------	-----

Rush	TIRES	Rush
Mr33	ADDITIVE	Mr33
10 mins	ADDITIVE TIMING	10 mins

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT	13:24 /g	WEIGHT BALANCE	FRONT 50 % REAR 50 %
--------------	----------	----------------	----------------------

MOTOR	LRP 5.0	TIMING	
-------	---------	--------	--

ESC	LRP Flow X	BATTERIES	LRP 4000
-----	------------	-----------	----------

BODY	Triester SP 0.5	WING	0.5 SP
------	-----------------	------	--------

67 /mm	Dimension from body post to window bottom line	BODY POSITION
6 hole /mm	Dimension from body post to upper holder	WING SIDE PLATE
		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
N/A /mm	Dimension from edge to surface	

COMMENTS

FRONT CASTER	BUMP STEER	HEIGHT	SHIM	FRONT & REAR SUSPENSION	REAR CASTER	TOE GAIN
Adjust with eccentric bushings	4 /mm	19 /mm	8 /mm		Adjust with eccentric bushings	5 /mm
2 /mm FF	5.2 /mm	FR 2 /mm	<input type="checkbox"/> SERVO SAVER		2.5 /mm RF	5.4 /mm
<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> SERVO HORN		<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT

FRONT CAMBER	BODY STOP	FRONT SUSPENSION	FRONT HUB
2 /deg. Left=Right	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> 11 /mm	FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm NO <input type="checkbox"/>	SHIM 2 /mm 2.5 /mm COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
		FRONT SHOCK POSITION 1 2 3 4	SHIM 0.5 /mm
		DRIVE SHAFT 58mm 59mm STD. BEARING	SHIM 6.6 /mm DOWNSTOP

REAR CAMBER	BODY POST	REAR SUSPENSION	REAR HUB
2 /deg. Left=Right	VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>	SHIM 1 /mm 2.5 /mm REAR SHOCK POSITION 1 2 3 4	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
		DRIVE SHAFT 52mm 54mm STD. BEARING	SHIM 1.5 /mm
		SHIM 4.4 /mm DOWNSTOP	

FRONT TOP VIEW	REAR TOP VIEW
1 TOE OUT Left=Right	2.5 TOE IN Left=Right
ACKERMANN SHIM 0.5 /mm	SHIM /mm
DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>	DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/>
UPPER ARM STANDARD <input checked="" type="checkbox"/>	UPPER ARM STANDARD <input checked="" type="checkbox"/>
STEERING BRIDGE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	TOP DECK FLEX NONE <input checked="" type="checkbox"/> BEARING <input type="checkbox"/>
TOP DECK STANDARD <input checked="" type="checkbox"/> SPLITTED <input type="checkbox"/>	TOP DECK 1.6mm <input checked="" type="checkbox"/> 2.0mm <input type="checkbox"/>
OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm	OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm

FRONT BOTTOM VIEW	REAR BOTTOM VIEW
STEER. LOCK 26 /deg.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
STEER. SHIM SIZE 7.5 /mm	FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	REAR BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>
STEER. PLATE STANDARD <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>	CHASSIS GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input checked="" type="checkbox"/>