

SET-UP SHEET

SET-UP VER.01 ©XRAY

XRAY XB8E'21 PIVOT BALL

RACE	Portuguese Open		
TRACK	Vilela		
NAME	Ricardo Monteiro	DATE	27/03/2022
TEMPERATURE AIR		TEMPERATURE TRACK	
LAPS	FINAL POSITION	BEST LAPTIME	RACE LENGTH
		/sec	/min
TRACKS			
SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH
SURFACE	<input type="checkbox"/> SMOOTH	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
TYPE	<input checked="" type="checkbox"/> HARD PACKED <input checked="" type="checkbox"/> BLUE GROVE	<input checked="" type="checkbox"/> SOFT DIRT <input type="checkbox"/> ASTRO TURF	<input type="checkbox"/> CLAY <input type="checkbox"/> GRASS
CONDITION	<input checked="" type="checkbox"/> DRY	<input type="checkbox"/> DUSTY	<input type="checkbox"/> WET <input type="checkbox"/> MUD
DIFFERENTIAL			
CASE MATERIAL	FRONT: std	CENTER: std	REAR: CASE MATERIAL
OIL	10k	7k	OIL
CROWN GEAR	46		CROWN GEAR
GEARING			
MOTOR PINION	16	/T	46 /T SPUR GEAR
SHOCKS			
FRONT	std	TYPE	std
4 dot	SPRINGS	3 dot	
std	MEMBRANE	std	
350 /cSt	OIL	350 /cSt	
<input checked="" type="checkbox"/> 6 HOLES	PISTONS	<input checked="" type="checkbox"/> 6 HOLES	
<input type="checkbox"/> 8 HOLES	1.1 mm	<input type="checkbox"/> 8 HOLES	
<input type="checkbox"/> 10 HOLES	1.2 mm	<input type="checkbox"/> 8 HOLES	
	1.3 mm	<input type="checkbox"/> 10 HOLES	
	1.4 mm	<input type="checkbox"/> 10 HOLES	
	OTHER	1.35	
VALVE PISTONS			
5+2 HOLES	1.5 mm	5+2 HOLES	
6+2 HOLES	1.3 mm	6+2 HOLES	
8+2 HOLES	1.4 mm	8+2 HOLES	
	1.2 mm	8+2 HOLES	
	1.3 mm		
ANTI-ROLL BAR			
FRONT	2.3 /mm	THICKNESS	2.6 /mm
TIRES			
FRONT	Hot Race	BRAND	Sahara
	Clay	COMPOUND	Clay
	Hot Race	INSERTS	Hot Race
	Hot Race	WHEELS	Hot Race
ELECTRONICS			
MOTOR	1900kv		
SPEEDO	1900kv		
BATTERY TYPE	XTR 6300 Shorty		
SADDLE PACK	<input type="checkbox"/>	BRICK PLATE	<input type="checkbox"/>
FR	STANDARD BATT.	RR	BATT. ESC
FR	SHORT BATT.	RR	ESC BATT.
SHORT <input type="checkbox"/> STANDARD <input type="checkbox"/>			
BODY			
HS	HS-LIGHT	OTHER	WEIGHT
<input type="checkbox"/>	<input type="checkbox"/>	Eazy	/g

FRONT		REAR	
STEERING BLOCK HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> UP STEEL <input checked="" type="checkbox"/> ALU <input type="checkbox"/> DOWN STEEL <input checked="" type="checkbox"/> ALU <input type="checkbox"/> PIVOT BALLS UP STEEL <input checked="" type="checkbox"/> ALU <input type="checkbox"/> DOWN STEEL <input checked="" type="checkbox"/> ALU <input type="checkbox"/> OFFSET 0 +1 +2 <input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> PIVOT NUT ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/> FRONT DROOP MEASURE UNDER WHEEL AXLE #107717 GAUGE LOWER ARM SHIM <input checked="" type="checkbox"/> 0 1mm 2mm		SHOCK TOWERS FRONT ALU <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> REAR ALU <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> UPPER SHOCK POSITION 1 2 3 4 5 6 7 8 REAR SHOCK POSITION 1 2 3 4 5 6 7 8 REAR ROLL CENTER 1 2 3 LOWER ROLL CENTER 1 2 3 REAR DROOP MEASURE UNDER WHEEL AXLE #107717 GAUGE UPRIGHT MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> OFFSET 0 +1 +2 <input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>	
FRONT 		REAR 	
UPPER ROLL CENTER 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> CASTER SHIM 0 1.0 1.0 2.0 UPPER ARM POSITION BUMP STEER SHIM STEERING PLATE /mm STEERING BLOCK /mm SHIMS PLACE ALWAYS UNDER WHEELBASE SHIM POSITION 0mm <input checked="" type="checkbox"/> 2mm <input type="checkbox"/> 4mm <input type="checkbox"/> SHIMS BEHIND FRONT ARM LOWER ROLL CENTER ECCENTRIC BUSHINGS FRONT 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> REAR 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>		REAR WING STANDARD <input checked="" type="checkbox"/> LEXAN <input type="checkbox"/> FRONT MIDDLE REAR OTHER WING HOLDER FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/> WHEELBASE SHIM POSITION 0mm <input checked="" type="checkbox"/> 2mm <input type="checkbox"/> 4mm <input type="checkbox"/> SHIMS IN FRONT OF REAR ARM RF 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> +2mm <input type="checkbox"/> 0mm <input type="checkbox"/> RR 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> +2mm <input type="checkbox"/> 0mm <input type="checkbox"/>	
FRONT TOE OUT 		REAR TOE IN 	
FRONT FRONT CAMBER LENGTH mm UPPER ARM SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> LOWER ARM SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> RIDE HEIGHT 23 /mm #107717 GAUGE		REAR REAR CAMBER LENGTH mm FULL TRAVEL SHOCKS LENGTH 123 /mm RIDE HEIGHT 27 /mm #107717 GAUGE	