

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE			
TRACK	AUSTINTOWN HOBBY		
NAME	MARC LIVERMORE	DATE	

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
			/sec	/	

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
SOLID AXLE	<input checked="" type="checkbox"/> YES	
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 8000 /cSt
PINION	/T	SPUR GEAR /T
		FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
2.5 / 2.8	XRAY SPRINGS	2.7
350	OIL /cSt	350
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 3 HOLES	PISTONS	3 HOLES <input checked="" type="checkbox"/>
<input type="checkbox"/> 4 HOLES	1.0mm	<input type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	1.1mm	<input type="checkbox"/> PSS
	1.2mm	

SHOCK LENGTH FRONT	8.5 /mm	SHOCK LENGTH REAR	8.5 /mm
--------------------	---------	-------------------	---------

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
-----	--------------	---------------	--------------	-----

FRONT	TIRES	REAR
SXT	ADDITIVE	SXT
4 MIN	ADDITIVE TIMING	4 MIN

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT
------------	-------------	--------------	-----------	------------

TOTAL WEIGHT	1322 /g	WEIGHT BALANCE	FRONT 51 %	REAR 49 %
--------------	---------	----------------	------------	-----------

MOTOR		TIMING	
-------	--	--------	--

ESC	R1 Super Stock	BATTERIES	R1 6000
-----	----------------	-----------	---------

BODY		WING	
------	--	------	--

	BODY POSITION Dimension from body post to window bottom line /mm Dimension from body post to upper holder /mm WING SIDE PLATE YES <input type="checkbox"/> NO <input type="checkbox"/>
--	---

COMMENTS
10mm ballstud required to run 8mm shims on ARS

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
5° 4° 3° Adjust with eccentric bushings	BUMP STEER 5 /mm HEIGHT 19 /mm SHIM 6 /mm TOE GAIN 8 /mm RIDE HEIGHT 5.2 /mm SERVO SAVER <input type="checkbox"/> SERVO HORN <input checked="" type="checkbox"/>	0.5° 1.5° 2.5° 3.5° 4.5° 5.5° Adjust with eccentric bushings

FRONT	FRONT SUSPENSION	FRONT HUB
2.25 /deg. CAMBER Left = Right BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> /mm FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm <input type="checkbox"/> NO <input type="checkbox"/> DRIVE SHAFT 58mm <input checked="" type="checkbox"/> 59mm <input type="checkbox"/> STD. BEARING <input checked="" type="checkbox"/> #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 6.4 /mm DOWNSTOP	1.5 /mm SHIM 2 /mm FRONT SHOCK POSITION 1 2 3 4 SHIM .75 /mm	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>

REAR	REAR SUSPENSION	REAR HUB
2.75 /deg. CAMBER Left = Right BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/> REAR SHOCK POSITION 1 2 3 4 SHIM 1 /mm DRIVE SHAFT 52mm <input checked="" type="checkbox"/> 54mm <input type="checkbox"/> STD. BEARING <input checked="" type="checkbox"/> #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 6 /mm DOWNSTOP	1 /mm SHIM 2 /mm SHIM 1 /mm	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>

FRONT TOP VIEW	REAR TOP VIEW
.8 TOE OUT Left = Right ACKERMANN SHIM 1 /mm BRASS WEIGHT FOR MOTOR MOUNT 12 15 15 10 DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> UPPER ARM STANDARD <input type="checkbox"/> HARD <input checked="" type="checkbox"/> OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> SHIM/mm TOP DECK STANDARD <input type="checkbox"/> SPLITTED <input checked="" type="checkbox"/> TOP DECK FLEX NONE <input checked="" type="checkbox"/> BEARING <input type="checkbox"/> TOP DECK 1.6mm <input checked="" type="checkbox"/> 2.0mm <input type="checkbox"/>	2.5 TOE IN Left = Right SHIM /mm 12 10 DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> UPPER ARM STANDARD <input type="checkbox"/> HARD <input checked="" type="checkbox"/> OFFSET STANDARD <input type="checkbox"/> -0.5mm <input type="checkbox"/> SHIM/mm .5

FRONT BOTTOM VIEW	REAR BOTTOM VIEW
STEER. LOCK 24 /deg. STEER. SHIM SIZE kit /mm FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> FR RE SERVO HOLDER CHASSIS GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input checked="" type="checkbox"/> FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/> MOTOR MOUNT CHASSIS T-BRACE REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>