

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE	P&F Hobbies		
TRACK			
NAME	Raymond McCoy	DATE	5/14/2022

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
	2	1	9.99 /sec	29/	5:00

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
SOLID AXLE	<input checked="" type="checkbox"/> YES	
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 10k /cSt
PINION 47 /T	SPUR GEAR 96 /T	FINAL DRIVE RATIO 3.88

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
400	OIL /cSt	400
0	REBOUND %	0
<input type="checkbox"/> YES <input type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input type="checkbox"/> NO

PISTONS	
<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS	<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS
1.0mm	1.1mm
1.2mm	

SHOCK LENGTH FRONT	8.7 /mm	SHOCK LENGTH REAR	8.7 /mm
--------------------	---------	-------------------	---------

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
-----	--------------	---------------	--------------	-----

Volante V8's	TIRES	Volante V8's
Sxt	ADDITIVE	Sxt
5	ADDITIVE TIMING	5

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	1321 /g	WEIGHT BALANCE	FRONT %	REAR %
--------------	---------	----------------	---------	--------

MOTOR	Trinity X-factor 21.5	TIMING	
-------	-----------------------	--------	--

ESC	Trinity MX Pro	BATTERIES	Trinity ULCG 5900
-----	----------------	-----------	-------------------

BODY	OG twister .4	WING	Stock
------	---------------	------	-------

68 /mm	Dimension from body post to window bottom line	BODY POSITION
WING SIDE PLATE	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	

COMMENTS	Rc-Maker 1.6 split top decks (not cut)
----------	--

FRONT CASTER	BUMP STEER	HEIGHT	SHIM	FRONT & REAR SUSPENSION	REAR CASTER	TOE GAIN
Adjust with eccentric bushings	2.5 /mm	19 /mm	4 /mm		Adjust with eccentric bushings	6 /mm
2 /mm FF	5 /mm	FR 2 /mm	<input checked="" type="checkbox"/> SERVO SAVER		2 /mm RF	5.4 /mm
<input checked="" type="checkbox"/> RIDE HEIGHT		<input checked="" type="checkbox"/> SERVO HORN			<input checked="" type="checkbox"/> RIDE HEIGHT	

1 /deg. CAMBER	BODY STOP	FRONT SUSPENSION	FRONT HUB
Left = Right	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
		BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm <input type="checkbox"/> NO <input type="checkbox"/>	SHIM .5 /mm
DRIVE SHAFT			
<input checked="" type="checkbox"/> 58mm <input type="checkbox"/> 59mm	<input checked="" type="checkbox"/> STD. BEARING		
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
			6.0 /mm DOWNSTOP

2 /deg. CAMBER	BODY POST	REAR SUSPENSION	REAR HUB
Left = Right	VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>	REAR SHOCK POSITION	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
			SHIM 1.5 /mm
DRIVE SHAFT			
<input type="checkbox"/> 52mm <input checked="" type="checkbox"/> 54mm	<input checked="" type="checkbox"/> STD. BEARING		
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
			4.6 /mm DOWNSTOP

FRONT TOP VIEW	REAR
TOE OUT Left = Right	TOE IN Left = Right
ACKERMANN SHIM .5 /mm	SHIM /mm
DIFF POSITION UP <input type="checkbox"/> DOWN <input type="checkbox"/>	DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/>
UPPER ARM STANDARD <input checked="" type="checkbox"/>	UPPER ARM STANDARD <input checked="" type="checkbox"/>
STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	TOP DECK FLEX NONE <input checked="" type="checkbox"/> BEARING <input type="checkbox"/>
TOP DECK	TOP DECK 1.6mm <input checked="" type="checkbox"/> 2.0mm
OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm	OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> SHIM/mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK 27 /deg.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
STEER. SHIM SIZE /mm	
FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	MOTOR MOUNT
FR SERVO HOLDER	CHASSIS T-BRACE
FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>
STEER. PLATE STANDARD <input type="checkbox"/> +1mm <input checked="" type="checkbox"/>	
	CHASSIS GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU FLEX <input type="checkbox"/>