

SET-UP SHEET

X1'21 SET-UP SHEET VER.1 ©XRAY

XRAY X1'21

RACE	French Nats Round 3				
TRACK	RACG				
NAME	Varinard Jean-Michel	DATE	22/05/2022		

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
2	1	22,0 /sbc	/	

TRACK

TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

CENTER SHOCK ABSORBER




SPRING	OIL /cSt	REBOUND /%
2,3-2,6	800	0





PISTON <input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS	PISTON HOLES DIAMETER <input type="checkbox"/> ø1.1mm <input type="checkbox"/> ø1.2mm <input checked="" type="checkbox"/> ø1.3mm	FOAM INSERT YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
---	---	--

ANTI-ROLL BAR

THICKNESS/mm	0
--------------	---

DAMPING

<input checked="" type="checkbox"/> SIDE TUBE		OIL 60000 /cSt
<input type="checkbox"/> SIDE SHOCK		OIL /cSt
<input type="checkbox"/> FRONT TUBE		OIL /cSt

FRONT	TIRES	REAR
<div style="border: 1px solid black; padding: 5px; text-align: center;"> Volante FMS <small>Trinity Tire Tweak + Dirt destroyer</small> 40' and 10' </div> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> FRONT LEFT  </div> <div style="text-align: center;"> FRONT RIGHT  </div> </div>	<div style="border: 1px solid black; padding: 5px; text-align: center;"> Tires ADDITIVE ADDITIVE TIMING ADDITIVE TREATED AREA </div>	<div style="border: 1px solid black; padding: 5px; text-align: center;"> Ride GR <small>Trinity Tire Tweak + Dirt destroyer</small> 40' and 10' </div> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> REAR LEFT  </div> <div style="text-align: center;"> REAR RIGHT  </div> </div>

TRANSMISSION

BALL DIFF <input checked="" type="checkbox"/> <input type="checkbox"/> LOOSE <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> TIGHT	SOLID AXLE <input type="checkbox"/>	GEAR DIFF <input type="checkbox"/> OIL /cSt
---	---	---

GEARING

PINION /T	SPUR GEAR /T	FINAL DRIVE RATIO
37	80	2,16

ELECTRONICS

MOTOR	PRT Air X
SPEEDO	ORCA OE101
SERVO	Sanwa
BATTERIES	MARKA 6000

BODY

Gonzo

COMMENTS
 Upper arm: shim 2 mm only on rear to have active caster

