

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE	Swedish Cup		
TRACK	Flatenbanan		
NAME	Alexander Hagberg	DATE	04/06/22

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
25-35	1	1	17.8 /sec	17/	5:15

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
SOLID AXLE <input checked="" type="checkbox"/> YES		
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 7000 /cSt
PINION 29 /T	SPUR GEAR 110 /T	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
300	OIL /cSt	300
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

PISTONS	
<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS	<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS
1.0mm 1.1mm 1.2mm	1.0mm 1.1mm 1.2mm

SHOCK LENGTH FRONT 9.0 /mm	SHOCK LENGTH REAR 9.0 /mm
----------------------------	---------------------------

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
Sweep EXP 36	TIRES	Sweep EXP 36		
Hudy Asphalt	ADDITIVE	Hudy Asphalt		
10	ADDITIVE TIMING	10		

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT 1335 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
MOTOR HW G3 4.5T	TIMING		
ESC HW XR10 G2S	BATTERIES	Sunpadow 5500 LCG	
BODY Speciale 0.5	WING	Speciale 0.5	

67 /mm	Dimension from body post to window bottom line	BODY POSITION
7th hole +1 + o-ring /mm	Dimension from body post to upper holder	WING SIDE PLATE
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>		
66 /mm	Dimension from edge to surface	

COMMENTS

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
5° 4° 3° Adjust with eccentric bushings	BUMP STEER 3 /mm HEIGHT 19 /mm SHIM 6 /mm	0.5° 1.5° 2.5° 3.5° 4.5° 5.5° Adjust with eccentric bushings
2.5 /mm FF 5.2 /mm RIDE HEIGHT FR 2.5 /mm <input type="checkbox"/> SERVO SAVER <input checked="" type="checkbox"/> SERVO HORN	TOE GAIN 6.5 /mm 3.0 /mm RF 5.4 /mm RIDE HEIGHT RR 3.0 /mm	3.0 /mm RF 5.4 /mm RIDE HEIGHT RR 3.0 /mm

FRONT	FRONT SUSPENSION	FRONT HUB
2.0 /deg. CAMBER Left = Right BODY STOP YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> /mm FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm <input type="checkbox"/> NO DRIVE SHAFT 58mm 59mm STD. BEARING <input checked="" type="checkbox"/>	1.0 /mm SHIM 3.0 /mm FRONT SHOCK POSITION 1 2 3 4 SHIM 0.5 /mm #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.6 /mm DOWNSTOP	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>

REAR	REAR SUSPENSION	REAR HUB
2.0 /deg. CAMBER Left = Right BODY POST VERTICAL <input checked="" type="checkbox"/> HORIZONTAL <input type="checkbox"/> REAR SHOCK POSITION 1 2 3 4 SHIM 0.5 /mm #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.4 /mm DOWNSTOP	1.5 /mm SHIM 3.0 /mm REAR SHOCK POSITION 1 2 3 4 SHIM 0.5 /mm #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.4 /mm DOWNSTOP	COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>

FRONT TOP VIEW	REAR
1 TOE OUT Left = Right ACKERMANN SHIM 0.5 /mm 5 10 12 BRASS WEIGHT FOR MOTOR MOUNT DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm TOP DECK STANDARD <input type="checkbox"/> SPLITTED <input checked="" type="checkbox"/> STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> TOP DECK FLEX NONE <input type="checkbox"/> BEARING <input type="checkbox"/> TOP DECK 1.6mm <input type="checkbox"/> 2.0mm	2.5 TOE IN Left = Right SHIM /mm 10 12 DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm TOP DECK CUTTING TOP DECK FLEX

FRONT BOTTOM VIEW	REAR
STEER. LOCK 27 /deg. STEER. SHIM SIZE 7.5 /mm FR RE SERVO HOLDER FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/> STEER. PLATE STANDARD <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>	T-BRACE ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/> MOTOR MOUNT CHASSIS T-BRACE CHASSIS GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input type="checkbox"/> REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>