

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE	USGT - 2022 Summer Sizzler		
TRACK	Soda City RC		
NAME	Cory Craig	DATE	6-4-22

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
80	3	2	7.87 /sec	/	

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input checked="" type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
SOLID AXLE	<input checked="" type="checkbox"/> YES	
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 10,000 /cSt
PINION 50 /T	SPUR GEAR 82 /T	FINAL DRIVE RATIO 3.12

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
450	OIL /cSt	450
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input type="checkbox"/> 3 HOLES	PISTONS	3 HOLES <input type="checkbox"/>
<input type="checkbox"/> 4 HOLES	1.0mm	4 HOLES <input type="checkbox"/>
<input checked="" type="checkbox"/> PSS	1.1mm	PSS <input checked="" type="checkbox"/>
	1.2mm	
solid piston		solid piston

SHOCK LENGTH FRONT	SHOCK LENGTH REAR
8.7 /mm	8.7 /mm

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.3
-----	--------------	---------------	--------------	-----

Gravity USGT	TIRES	Gravity USGT
SXT white	ADDITIVE	SXT white
2 minutes	ADDITIVE TIMING	2 minutes

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT 1366 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
----------------------	----------------	------------	-----------

MOTOR	USGT Spec	TIMING
-------	-----------	--------

ESC	Tekin RS Pro	BATTERIES	Motiv Defy LCG 6000
-----	--------------	-----------	---------------------

BODY	Zoo Bwoah	WING	Zoo Bwoah
------	-----------	------	-----------

<p>Dimension from body post to window bottom line</p>	BODY POSITION
<p>Dimension from body post to upper holder</p>	WING SIDE PLATE YES <input type="checkbox"/> NO <input type="checkbox"/>
<p>Dimension from edge to surface</p>	

COMMENTS
droop set over ride height. split deck front : 1.6 front plate split deck rear : 2.0 rear plate

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
<p>Adjust with eccentric bushings</p>		<p>Adjust with eccentric bushings</p>
5° 4° 3° BUMP STEER 5 /mm HEIGHT /mm SHIM 6 /mm	TOE GAIN 5 /mm 2.0 /mm FF 5.2 /mm FR 2.0 /mm RIDE HEIGHT <input checked="" type="checkbox"/> SERVO SAVER <input type="checkbox"/> <input checked="" type="checkbox"/> SERVO HORN <input type="checkbox"/>	0.5° 1.5° 2.5° 3.5° 4.5° 5.5° 2.0 /mm RF 5.4 /mm RR 2.0 /mm RIDE HEIGHT <input checked="" type="checkbox"/>

FRONT	FRONT SUSPENSION	FRONT HUB
<p>-2 /degr. CAMBER Left=Right</p>	<p>2.0 /mm SHIM 1.5 /mm</p>	<p>COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/></p>
BODY STOP YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm <input type="checkbox"/> NO <input type="checkbox"/>	DRIVE SHAFT <input checked="" type="checkbox"/> 58mm <input type="checkbox"/> 59mm <input type="checkbox"/> STD. BEARING <input checked="" type="checkbox"/> #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge	SHIM 1.0 /mm #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge

REAR	REAR SUSPENSION	REAR HUB
<p>-2 /degr. CAMBER Left=Right</p>	<p>2.5 /mm SHIM 2.0 /mm</p>	<p>COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/></p>
BODY POST VERTICAL <input checked="" type="checkbox"/> HORIZONTAL <input type="checkbox"/>	DRIVE SHAFT <input type="checkbox"/> 52mm <input checked="" type="checkbox"/> 54mm <input type="checkbox"/> STD. BEARING <input checked="" type="checkbox"/> #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge	SHIM 0.5 /mm #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge

FRONT TOP VIEW	REAR
<p>-1 TOE OUT Left=Right</p>	<p>1.5 TOE IN Left=Right</p>
ACKERMANN SHIM 1.0 /mm DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	SHIM 1.0 /mm DIFF POSITION <input type="checkbox"/> UP <input checked="" type="checkbox"/> DOWN
UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> SHIM/mm	UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> SHIM/mm
TOP DECK TOP DECK FLEX TOP DECK CUTTING	TOP DECK TOP DECK FLEX TOP DECK CUTTING

FRONT BOTTOM VIEW	REAR
<p>STEER. LOCK 22 /degr. STEER. SHIM SIZE 6 /mm FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> FR SERVO HOLDER</p>	<p>T-BRACE ALU <input type="checkbox"/> BRASS <input checked="" type="checkbox"/> MOTOR MOUNT CHASSIS T-BRACE</p>
FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> STEER. PLATE STANDARD <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>	CHASSIS GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU FLEX <input type="checkbox"/> REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>