

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE	Hungarian Nats 1		
TRACK			
NAME	Zsolt Bajusz Junior	DATE	

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
	1	1	/sec	/	

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST
TRACTION	<input checked="" type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
SOLID AXLE	<input type="checkbox"/> YES	
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 5000 /cSt
PINION 38 /T	SPUR GEAR 100 /T	FINAL DRIVE RATIO 5.0

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
400	OIL /cSt	400
	REBOUND %	
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> 1.0mm	<input type="checkbox"/> 3 HOLES
<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS

SHOCK LENGTH FRONT	/mm	SHOCK LENGTH REAR	/mm
--------------------	-----	-------------------	-----

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
LRP	TIRES	CPX V22		
HUDY	ADDITIVE	Red		
10	ADDITIVE TIMING	10		

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT
------------	-------------	--------------	-----------	------------

TOTAL WEIGHT	/g	WEIGHT BALANCE	FRONT	%	REAR	%
--------------	----	----------------	-------	---	------	---

MOTOR	17.5	TIMING
-------	------	--------

ESC	BATTERIES
-----	-----------

BODY	Twister	WING
------	---------	------

	BODY POSITION Dimension from body post to window bottom line /mm Dimension from body post to upper holder /mm WING SIDE PLATE YES <input type="checkbox"/> NO <input type="checkbox"/> Dimension from edge to surface /mm
--	--

COMMENTS

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
<input checked="" type="checkbox"/> 5° <input type="checkbox"/> 4° <input type="checkbox"/> 3° Adjust with eccentric bushings	BUMP STEER 5 /mm HEIGHT /mm SHIM /mm TOE GAIN 5 /mm RIDE HEIGHT 2 /mm FF 5 /mm FR 2 /mm <input type="checkbox"/> SERVO SAVER <input checked="" type="checkbox"/> SERVO HORN	<input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1.5° <input type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° Adjust with eccentric bushings RIDE HEIGHT 2.5 /mm RF 5.2 /mm RR 2.5 /mm

1.5 /deg. CAMBER Left = Right	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	FRONT SUSPENSION	FRONT HUB COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
	/mm	SHIM 1.5 /mm 2 /mm FRONT SHOCK POSITION 1 2 3 4 BULKHEAD SHIMS YES <input type="checkbox"/> 3mm <input type="checkbox"/> NO DRIVE SHAFT 58mm 59mm STD. BEARING <input checked="" type="checkbox"/>	SHIM 0.5 /mm
		#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 6 /mm DOWNSTOP	

1 /deg. CAMBER Left = Right	BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>	REAR SUSPENSION	REAR HUB COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
		SHIM 1.5 /mm 2 /mm REAR SHOCK POSITION 1 2 3 4 DRIVE SHAFT 52mm 54mm STD. BEARING <input checked="" type="checkbox"/>	SHIM 0.5 /mm
		#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.8 /mm DOWNSTOP	

FRONT TOP VIEW	REAR
1 TOE OUT Left = Right ACKERMANN SHIM 1 /mm DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> SHIM/mm TOP DECK STANDARD <input checked="" type="checkbox"/> SPLITTED <input type="checkbox"/> TOP DECK FLEX NONE <input checked="" type="checkbox"/> BEARING <input type="checkbox"/> TOP DECK CUTTING	2.5 TOE IN Left = Right SHIM 0.5 /mm DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> UPPER ARM STANDARD <input checked="" type="checkbox"/> OFFSET STANDARD <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> SHIM/mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK /deg. STEER. SHIM SIZE /mm FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> FR RE SERVO HOLDER CHASSIS GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input checked="" type="checkbox"/>	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/> MOTOR MOUNT CHASSIS T-BRACE REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>