

SET-UP SHEET

X4'23 SET-UP SHEET VER.1 ©XRAY

XRAY X4'23

RACE	ETS Startsetup		
TRACK	Hann Münden		
NAME	Marco Kaufmann	DATE	Nov 22

QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
		/sec	/	

TRACK			
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT	
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED	<input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	SPUR GEAR	FINAL DRIVE RATIO
27 /T	110 /T	

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.7
350	OIL /Cst	350
	REBOUND %	
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH	8.5 /mm	8.5 /mm	SHOCK LENGTH

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

	TIRES	Matrix
	ADDITIVE	MR33 V4
	ADDITIVE TIMING	2x 5min

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	1285 /g	WEIGHT BALANCE	FRONT 49 % REAR 51 %
--------------	---------	----------------	----------------------

MOTOR	5.0 12.1mm Rotor	TIMING	
ESC		BATTERIES	Gensace 4000
BODY	Twister Speciale 0,5	WING	Std

	Dimension from body post to window bottom line	BODY POSITION
	Dimension from body post to upper holder	WING SIDE PLATE
	Dimension from edge to surface	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>

X4'23	<input checked="" type="checkbox"/> 1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
X4'22	<input type="checkbox"/> 2.0mm	<input type="checkbox"/> 2.0mm	<input type="checkbox"/> 1.6mm
X4'22	<input type="checkbox"/> 2.0mm	<input type="checkbox"/> 1.6mm	<input type="checkbox"/> BEARING

COMMENTS

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
Adjust with eccentric bushings		Adjust with eccentric bushings
UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm		UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm
2 /mm FF	5 /mm FR	2 /mm RF
5 /mm RIDE HEIGHT	3 /mm	5.2 /mm RIDE HEIGHT
	<input type="checkbox"/> SERVO SAVER	
	<input type="checkbox"/> SERVO HORN	

2 /deg. CAMBER	FRONT SUSPENSION	FRONT HUB
Left = Right		
BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	HARD <input type="checkbox"/>
	BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm NO <input type="checkbox"/>	GRAPHITE <input checked="" type="checkbox"/>
	DRIVE SHAFT 58mm 59mm BEARING BLADE	ALU <input type="checkbox"/>
	#107702 Chassis Droop Gauge Blocks	SHIM 0.5 /mm
	#107712 Chassis Droop Gauge	6.2 /mm DOWNSTOP

2 /deg. CAMBER	REAR SUSPENSION	REAR HUB
Left = Right		
BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>	REAR SHOCK POSITION	HARD <input type="checkbox"/>
	SHIM 1.5 /mm	GRAPHITE <input checked="" type="checkbox"/>
	SHIM 2.5 /mm	ALU <input type="checkbox"/>
	DRIVE SHAFT 52mm 54mm BEARING BLADE	SHIM 1 /mm
	#107702 Chassis Droop Gauge Blocks	4.4 /mm DOWNSTOP
	#107712 Chassis Droop Gauge	

FRONT TOP VIEW	REAR
1 TOE OUT Left = Right	2.5 TOE IN Left = Right
ACKERMANN SHIM 0.5 /mm	SHIM /mm
DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>
UPPER ARM SOFT <input type="checkbox"/> MEDIUM STD. <input checked="" type="checkbox"/>	UPPER ARM SOFT <input type="checkbox"/> MEDIUM STD. <input checked="" type="checkbox"/>
STEERING BRIDGE YES <input type="checkbox"/> NO <input type="checkbox"/>	STEERING PLATE 8.0mm <input checked="" type="checkbox"/> STD. 7.5mm
HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK 26 /deg.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
STEER. SHIM SIZE 8 /mm	MOTOR MOUNT
FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	CHASSIS T-BRACE
SERVO HOLDER	CHASSIS GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input checked="" type="checkbox"/>
FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>