

SET-UP SHEET

X4'23 SET-UP SHEET VER.1 ©XRAY

XRAY X4'23

RACE	Club Race 1/16			
TRACK	Fastlane RC Raceway			
NAME	Max Kuenning	DATE	1/15/23	

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
1	1	9.0 /sec	/	

TRACK			
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT	
TRACK LAYOUT	<input checked="" type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED	<input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	SPUR GEAR	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
Prog Med	XRAY SPRINGS	2.7
475	OIL /Cst	475
25	REBOUND %	25
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH	8.5 /mm	8.5 /mm	SHOCK LENGTH

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Gravity	TIRES	Gravity
SXT	ADDITIVE	SXT
15min	ADDITIVE TIMING	15min

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT
------------	-------------	--------------	-----------	------------

TOTAL WEIGHT	1320 /g	WEIGHT BALANCE	FRONT 50 % REAR 50 %
--------------	---------	----------------	----------------------

MOTOR	R1 21.5	TIMING	
ESC	R1	BATTERIES	EAM 6000
BODY	Twister OG LW	WING	Twister

	BODY POSITION Dimension from body post to window bottom line /mm
	WING SIDE PLATE YES <input type="checkbox"/> NO <input type="checkbox"/> Dimension from body post to upper holder /mm Dimension from edge to surface /mm

X4'23	1.6mm <input checked="" type="checkbox"/> 2.0mm <input checked="" type="checkbox"/> 1.6mm
X4'22	2.0mm <input type="checkbox"/> 2.0mm <input type="checkbox"/> 1.6mm
X4'22	2.0mm <input type="checkbox"/> 1.6mm <input type="checkbox"/> BEARING

COMMENTS

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
5° <input checked="" type="checkbox"/> 4° <input type="checkbox"/> 3° <input type="checkbox"/> Adjust with eccentric bushings	BUMP STEER 2.5 /mm HEIGHT /mm SHIM 4 /mm UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm	0.5° <input type="checkbox"/> 1.5° <input type="checkbox"/> 2.5° <input checked="" type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° <input type="checkbox"/> Adjust with eccentric bushings
2 /mm FF 5.2 /mm RIDE HEIGHT FR 2 /mm <input checked="" type="checkbox"/> SERVO SAVER <input type="checkbox"/> SERVO HORN		TOE GAIN 6 /mm 2 /mm RF 5.2 /mm RIDE HEIGHT RR 2 /mm

-1 /degr. CAMBER	BODY STOP YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	FRONT SUSPENSION	FRONT HUB
Left = Right	/mm	2.5 /mm SHIM 2.5 /mm FRONT SHOCK POSITION 1 2 FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm NO <input type="checkbox"/>	HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
		DRIVE SHAFT	SHIM
		58mm 59mm BEARING BLADE #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge	1 /mm

-2 /degr. CAMBER	BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>	REAR SUSPENSION	REAR HUB
Left = Right		2 /mm SHIM 2.5 /mm REAR SHOCK POSITION 1 2 REAR BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm NO <input type="checkbox"/>	HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
		DRIVE SHAFT	SHIM
		52mm 54mm BEARING BLADE #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge	1 /mm

FRONT TOP VIEW	REAR
1 TOE OUT Left = Right ACKERMANN SHIM 0.5 /mm 10 15 BRASS WEIGHT FOR MOTOR MOUNT DIFF POSITION UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> UPPER ARM SOFT <input type="checkbox"/> MEDIUM STD. <input checked="" type="checkbox"/> STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> STEERING PLATE 8.0mm <input checked="" type="checkbox"/> STD. 7.5mm <input type="checkbox"/> HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm	3 TOE IN Left = Right SHIM 0 /mm DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN UPPER ARM SOFT <input type="checkbox"/> MEDIUM STD. <input checked="" type="checkbox"/> STEERING PLATE 8.0mm <input checked="" type="checkbox"/> STD. 7.5mm <input type="checkbox"/> HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK 26 /degr. STEER. SHIM SIZE FR RE FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> SERVO HOLDER FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/> MOTOR MOUNT CHASSIS T-BRACE CHASSIS GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU FLEX <input type="checkbox"/> REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>