

SET-UP SHEET

X4'23 SET-UP SHEET VER.1 ©XRAY

XRAY X4'23

RACE	Toni Onroad Series		
TRACK	Speedracer Burning Wheels		
NAME	Stefan Schulz	DATE	19.03.2023

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
1	1	11.80/12.34 /sec	/	

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	7k /cst <input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL /cst
PINION	38 /T	SPUR GEAR
	100 /T	FINAL DRIVE RATIO
		5,00

FRONT	SHOCKS	REAR
2,5-2,8	XRAY SPRINGS	2,6
425	OIL /Cst	425
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input type="checkbox"/> 4 HOLES	1.1mm	1.1mm	<input type="checkbox"/> 4 HOLES
<input checked="" type="checkbox"/> PSS	1.2mm	1.2mm	<input checked="" type="checkbox"/> PSS
0,8			0,8
SHOCK LENGTH	8,5 /mm	8,5 /mm	SHOCK LENGTH

1,2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1,2
-----	--------------	---------------	--------------	-----

Matrix	TIRES	Matrix
MR33	ADDITIVE	MR33
10	ADDITIVE TIMING	10

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT	1300 /g	WEIGHT BALANCE	FRONT 49 % REAR 51 %
--------------	---------	----------------	----------------------

MOTOR	ETS 17.5 & 13.5	TIMING	
ESC	ORCA ETS	BATTERIES	GensAce 5800
BODY	Wolverine	WING	std

69 /mm	Dimension from body post to window bottom line	BODY POSITION
24mm /mm	Dimension from body post to upper holder	WING SIDE PLATE
		YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
61 /mm	Dimension from edge to surface	

X4'23	1.6mm <input checked="" type="checkbox"/> 2.0mm <input checked="" type="checkbox"/> 1.6mm	TOP DECK CUTTING
X4'22	2.0mm <input type="checkbox"/> 2.0mm <input type="checkbox"/> 1.6mm	
X4'22	2.0mm <input type="checkbox"/> 1.6mm <input type="checkbox"/> BEARING	

COMMENTS

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
5° <input checked="" type="checkbox"/> 4° <input type="checkbox"/> 3° <input type="checkbox"/> Adjust with eccentric bushings	BUMP STEER 4 /mm HEIGHT 19 /mm SHIM 6 /mm	0.5° <input type="checkbox"/> 1.5° <input checked="" type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° <input type="checkbox"/> Adjust with eccentric bushings
UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm	UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm	
2 /mm FF 5,0 /mm FR 2 /mm	TOE GAIN 5 /mm	3 /mm RF 5,2 /mm RR 3 /mm
<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> SERVO SAVER	<input checked="" type="checkbox"/> RIDE HEIGHT
<input checked="" type="checkbox"/> SERVO HORN		

FRONT CAMBER	FRONT SUSPENSION	FRONT HUB
2 /deg. Left=Right	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> 17 /mm	HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
	FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	SHIM 0,5 /mm
	BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm NO <input type="checkbox"/>	
	DRIVE SHAFT 58mm <input checked="" type="checkbox"/> 59mm <input type="checkbox"/> BEARING BLADE	
	#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
		6,4 /mm DOWNSTOP

REAR CAMBER	REAR SUSPENSION	REAR HUB
2 /deg. Left=Right	BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>	HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
	REAR SHOCK POSITION	SHIM 1 /mm
	DRIVE SHAFT 52mm <input checked="" type="checkbox"/> 54mm <input type="checkbox"/> BEARING BLADE	
	#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
		4,4 /mm DOWNSTOP

FRONT TOP VIEW	REAR
1 TOE OUT Left=Right	2 TOE IN Left=Right
ACKERMANN SHIM 0 /mm	SHIM 2 /mm
DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>	DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN
UPPER ARM SOFT <input type="checkbox"/> MEDIUM STD. <input checked="" type="checkbox"/>	UPPER ARM SOFT <input type="checkbox"/> MEDIUM STD. <input checked="" type="checkbox"/>
STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEERING PLATE 8.0mm <input checked="" type="checkbox"/> STD. <input type="checkbox"/> 7.5mm
HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK 24 /deg.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
STEER. SHIM SIZE 7,5 /mm	MOTOR MOUNT
FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	CHASSIS T-BRACE
SERVO HOLDER	CHASSIS
FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>
	ALU FLEX <input checked="" type="checkbox"/>