

SET-UP SHEET

X4'23 SET-UP SHEET VER.1 ©XRAY

XRAY X4'23

RACE			
TRACK	HOBBY.SHOP.F1-Japan		
NAME	shin.sawada	DATE	

QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
		/sec	/	

TRACK			
TRACK SURFACE	<input type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT	
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED	<input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL 7000 /cSt
PINION 36 /T	SPUR GEAR 100 /T	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
2.4-2.7	XRAY SPRINGS	2.8
400	OIL /cSt	400
8.5	REBOUND %	8.7
<input type="checkbox"/> YES <input type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH 8.5 /mm			SHOCK LENGTH 8.7 /mm

1.1	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

TIRES	
	ADDITIVE
	ADDITIVE TIMING

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	/g	WEIGHT BALANCE	FRONT %	REAR %
--------------	----	----------------	---------	--------

MOTOR	HW-G4/17.5	TIMING	
ESC	HW-G2S	BATTERIES	sunpadow
BODY		WING	

	BODY POSITION
	WING SIDE PLATE
	YES <input type="checkbox"/> NO <input type="checkbox"/>

	TOP DECK CUTTING

COMMENTS

FRONT & REAR SUSPENSION	
FRONT CASTER <input type="checkbox"/> 5° <input checked="" type="checkbox"/> 4° <input type="checkbox"/> 3° Adjust with eccentric bushings BUMP STEER 3 /mm HEIGHT /mm SHIM 5 /mm UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm	REAR CASTER <input type="checkbox"/> 0.5° <input checked="" type="checkbox"/> 1.5° <input type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° Adjust with eccentric bushings UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm TOE GAIN 3 /mm 3 /mm RF 5.4 /mm RR RIDE HEIGHT <input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>

2 /deg. CAMBER Left = Right BODY STOP YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> /mm FRONT SUSPENSION FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm <input type="checkbox"/> NO DRIVE SHAFT <input checked="" type="checkbox"/> 58mm <input type="checkbox"/> 59mm <input type="checkbox"/> BEARING <input type="checkbox"/> BLADE #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.5 /mm DOWNSTOP	1 /mm SHIM 3 /mm FRONT HUB HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> SHIM 0.5 /mm
---	--

2 /deg. CAMBER Left = Right BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/> REAR SUSPENSION REAR SHOCK POSITION 1 2 DRIVE SHAFT <input type="checkbox"/> 52mm <input checked="" type="checkbox"/> 54mm <input checked="" type="checkbox"/> BEARING <input type="checkbox"/> BLADE #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.5 /mm DOWNSTOP	1.5 /mm SHIM 3 /mm REAR HUB HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> SHIM 0.5 /mm
---	---

1.0 TOE OUT Left = Right ACKERMANN SHIM 0.5 /mm DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM STD. <input type="checkbox"/> STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm STEERING PLATE 8.0mm <input checked="" type="checkbox"/> STD. <input type="checkbox"/> 7.5mm	2.0 TOE IN Left = Right SHIM /mm DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> UPPER ARM SOFT <input type="checkbox"/> MEDIUM STD. <input checked="" type="checkbox"/> HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm
--	---

FRONT BOTTOM VIEW STEER. LOCK /deg. STEER. SHIM SIZE 0 /mm FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> SERVO HOLDER FR RE FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	REAR T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/> MOTOR MOUNT CHASSIS GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input type="checkbox"/> REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>
--	---