

XRAY XB4'22

FRONT
APPLIED ☒ NOT APPLIED ☐
REAR

ALU C-HUB SHIM

UP /mm
DOWN /mm

LONGER BUSHINGS

UP ☐
DOWN ☒

DRIVE SHAFT

CVD ☒ ECS ☐
Lenght 83 /mm

REAR UPRIGHT

SHIMS 2 /mm
HARD ☒
GRAPHITE ☐
ALU ☐
#325341 ADJ. DRIVE AXLE
1 2 3 4

STEERING BLOCK

MEDIUM ☐
HARD ☒
GRAPHITE ☐
ALU ☐

SHIM

0 mm

LOWER SHOCK POSITION

DOWNSTOP

DOWNSTOP

#107711 GAUGE

HUDY

#107701 SUPPORT BLOCKS

WING CUTTING LINE

OFFSET 3 /slots
UPRIGH WHEELBASE
SHIM 3 /mm
IN FRONT OF ARM

WING SIDE LINE

HIGHER ☐
LOWER ☒
WING POSITION
UP ☐
MIDDLE ☒
DOWN ☐
WING THICKNESS
0.75 ☐ 1 ☒ 1.5 ☐
TYPE

CASTER

6° ☐
7° ☐
9° ☒
12° ☐

CASTER BLOCK

MEDIUM ☐
HARD ☒
GRAPHITE ☐
ALU ☐

BUMP STEER

SHIM 2 mm

ROLL CENTER ECCENTRIC BUSHINGS

1° ☒
0.5° ☐
1° ☒
0.5° ☐

FF

RF

FR

RR 2°

UP ☐ **DOWN** ☐

FRONT TOE

1

REAR TOE

1

STEER. PLATE

HARD ☒
GRAPHITE ☐
ALU ☐
BUMP STEER
SHIM 5 mm
SERVO SAVER
SOFT ☐
MEDIUM ☒
TIGHT ☐
MATERIAL
STANDARD ☒
GRAPHITE ☐

GRAPHITE FOR REAR BRACE

YES ☒
NO ☐
REAR BRACE
MEDIUM ☐
HARD ☒

ARM SHIM

0 mm

ARM SHIM

2 mm

FRONT CAMBER

2

FRONT DIFF HEIGHT

RIDE HEIGHT 16 mm

DOWNSTOP

SHIM 0 mm
LENGTH 22 mm
UPSTOP
SHIM 2 mm

REAR DIFF HEIGHT

RIDE HEIGHT 16 mm

COLLAR

STANDARD ☒ -2mm

REAR CAMBER

2

DOWNSTOP

SHIM 0 mm
LENGTH 29 mm
UPSTOP
SHIM 0 mm

COLLAR

STANDARD ☒ -2mm

FRONT ARMS

LONG ☐
SHORT ☒
MEDIUM ☐
HARD ☒
GRAPHITE ☐

REAR ARMS

LONG ☒
SHORT ☐
MEDIUM ☐
HARD ☒
GRAPHITE ☐

BALANCE

0 g

BALANCE

0 g

SIDE GUARDS

HARD ☐
GRAPHITE ☐

CHASSIS FLEX

SCREW USED ☒
SCREW NOT USED ☐

T-BRACE

BALANCE 0 g

XRAY

FRONT BATTERY POST
REAR BATTERY POST
BALANCE 0 g