

SET-UP SHEET

VER.01 ©XRAY

XRAY X4'22

RACE	mjs cup		
TRACK	brno		
NAME	Filip bortoli	DATE	30.4

TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
23	1	1	17,8 /sec	18	5min. 22s.

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
SOLID AXLE	<input checked="" type="checkbox"/> YES	
GEAR DIFFERENTIAL - OIL	/cSt	GEAR DIFFERENTIAL - OIL 7K /cSt
PINION 38 /T	SPUR GEAR 100 /T	FINAL DRIVE RATIO 5:1

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.6
425	OIL /cSt	425
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

PISTONS	
<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS	<input type="checkbox"/> 3 HOLES <input checked="" type="checkbox"/> 4 HOLES <input type="checkbox"/> PSS
1.0mm 1.1mm 1.2mm	1.0mm 1.1mm 1.2mm

SHOCK LENGTH FRONT	9 /mm	SHOCK LENGTH REAR	9 /mm
--------------------	-------	-------------------	-------

1.1	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.1
-----	--------------	---------------	--------------	-----

hudy 36	TIRES	hudy 36
hudy asfalt	ADDITIVE	hudy asfalt
10min.	ADDITIVE TIMING	10min.

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT
------------	-------------	--------------	-----------	------------

TOTAL WEIGHT 1306 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
----------------------	----------------	------------	-----------

MOTOR	Muchmore 13,5	TIMING
-------	---------------	--------

ESC	HW	BATTERIES	ruddog 6200
-----	----	-----------	-------------

BODY	Wolverine	WING	STD.
------	-----------	------	------

66 /mm	Dimension from body post to window bottom line	BODY POSITION
6+2 O ring /mm	Dimension from body post to upper holder	WING SIDE PLATE
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		
65 /mm	Dimension from edge to surface	

COMMENTS	front topdeck 301079
----------	----------------------

FRONT CASTER	BUMP STEER	HEIGHT	SHIM	REAR CASTER	TOE GAIN
5° 4° 3°	3 /mm	19 /mm	7 /mm	0.5° 1.5° 2.5° 3.5° 4.5° 5.5°	5 /mm
Adjust with eccentric bushings				Adjust with eccentric bushings	
2 /mm FF	5,2 /mm	FR 2 /mm	<input type="checkbox"/> SERVO SAVER	2 /mm RF	5,4 /mm
<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> SERVO HORN	<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT

FRONT CAMBER	FRONT SUSPENSION	FRONT HUB
2 /deg. Left=Right	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> 19,5 /mm FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm NO <input type="checkbox"/> DRIVE SHAFT 58mm 59mm STD. BEARING <input checked="" type="checkbox"/> <input type="checkbox"/> #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5,6 /mm DOWNSTOP	SHIM 0,5 /mm COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>

REAR CAMBER	REAR SUSPENSION	REAR HUB
2 /deg. Left=Right	BODY POST VERTICAL <input checked="" type="checkbox"/> HORIZONTAL <input type="checkbox"/> SHIM 2 /mm 3 /mm REAR SHOCK POSITION 1 2 3 4 DRIVE SHAFT 52mm 54mm STD. BEARING <input checked="" type="checkbox"/> <input type="checkbox"/> #107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4,4 /mm DOWNSTOP	SHIM 0,5 /mm COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>

FRONT TOP VIEW	REAR TOP VIEW
1 TOE OUT Left=Right ACKERMANN SHIM 1 /mm 15 5 DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> UPPER ARM STANDARD <input checked="" type="checkbox"/> STEERING BRIDGE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> TOP DECK STANDARD <input type="checkbox"/> SPLITTED <input checked="" type="checkbox"/> OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm	2,5 TOE IN Left=Right SHIM 0 /mm BRASS WEIGHT FOR MOTOR MOUNT DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> UPPER ARM STANDARD <input checked="" type="checkbox"/> TOP DECK FLEX NONE <input type="checkbox"/> BEARING <input type="checkbox"/> TOP DECK 1.6mm <input checked="" type="checkbox"/> 2.0mm TOP DECK CUTTING OFFSET STANDARD <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> SHIM/mm

FRONT BOTTOM VIEW	REAR BOTTOM VIEW
STEER. LOCK 26 /deg. STEER. SHIM SIZE 7,5 /mm FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> FR RE SERVO HOLDER CHASSIS GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input type="checkbox"/> FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/> STEER. PLATE STANDARD <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>	T-BRACE ALU <input type="checkbox"/> BRASS <input checked="" type="checkbox"/> MOTOR MOUNT CHASSIS T-BRACE REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>