

SET-UP SHEET

XRAY XB4'23

RACE	Practice	
TRACK	HOECO	
NAME	Max	DATE 7.5.2023

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION		FINAL POSITION	

TRACK		
SIZE	<input type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM <input type="checkbox"/> TIGHT
TRACTION	<input type="checkbox"/> VERY-LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> VERY-HIGH	
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM <input type="checkbox"/> BUMPY
TYPE	<input type="checkbox"/> CLAY	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASTRO
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED <input checked="" type="checkbox"/> DRY
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY <input type="checkbox"/> WET

DIFFERENTIAL TYPE		
FRONT ↓	MIDDLE ↓	REAR ↓
GEAR DIFF <input type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
BALL DIFF <input type="checkbox"/>	SLIPPER <input type="checkbox"/>	BALL DIFF <input type="checkbox"/>
ACTIVE DIFF <input checked="" type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>
60° 90° 120°	60° 90° 120°	60° 90° 120°
OIL 8k cSt	OIL 200k cSt	OIL 8k cSt

SATELLITE GEARS		
COMPOSITE <input type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/>	COMPOSITE <input type="checkbox"/>
STEEL <input checked="" type="checkbox"/>	STEEL <input type="checkbox"/>	STEEL <input checked="" type="checkbox"/>
40T <input checked="" type="checkbox"/> 41T	CROWN GEAR	40T <input checked="" type="checkbox"/> 41T

CENTRAL SLIPPER & ONE-WAY SETTING	
	ONE-WAY TIGHTNESS
SLIPPING ADJUSTMENT	LOOSE 1 CW TURN (BASIC SETUP) FULLY TIGHTEN

GEARING	
PINION 20 T	81 T CENTER DIFF SPUR

FRONT	SHOCKS	REAR
2 dot	SPRINGS	2 dot
cSt 650	OIL	cSt 550
% 0	REBOUND	% 0
<input type="checkbox"/> 2 HOLES <input checked="" type="checkbox"/> 3 HOLES <input type="checkbox"/> 6 HOLES	PISTONS <input type="checkbox"/> ø1.2mm <input type="checkbox"/> ø1.3mm <input type="checkbox"/> ø1.4mm <input checked="" type="checkbox"/> ø1.6mm <input type="checkbox"/> ø1.7mm CUSTOM PISTONS ø mm 1.8 mm	<input checked="" type="checkbox"/> 2 HOLES <input type="checkbox"/> 3 HOLES <input type="checkbox"/> 6 HOLES

FRONT	ANTI ROLL BAR	REAR
1,8 mm	THICKNESS	1,8 mm

FRONT	TIRES	REAR
Dart	BRAND	
Yellow	COMPOUND	
	INSERTS	
	WHEELS	

ELECTRONICS		
MOTOR 5,5T	Nitride	SPEEDO
MOTOR TIMING 30		BATTERY
BATTERY SIZE		
STD. SHORT <input type="checkbox"/> LOW SHORT <input checked="" type="checkbox"/>		

BODY	
TYPE	Gamma 4DL STANDARD <input type="checkbox"/> LIGHT <input checked="" type="checkbox"/>

COMMENTS
Wide rear pivot holders

FRONT	APPLIED <input type="radio"/> <input checked="" type="checkbox"/> APPLIED	REAR
ALU C-HUB SHIM UP /mm DOWN /mm LONGER BUSHINGS UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> DRIVE SHAFT CVD <input type="checkbox"/> ECS <input checked="" type="checkbox"/> Length 83 /mm SHIM 0 mm LOWER SHOCK POSITION #107711 GAUGE	SHIM 0 mm DRIVE SHAFT Length 77 /mm SHIM 3 mm SHIMS 2 /mm HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU HIGH <input type="checkbox"/> ALU LOW <input type="checkbox"/> #325341 ADJ. DRIVE AXLE 1 2 3 4 #107711 GAUGE	REAR UPRIGHT SHIM 3 mm SHIMS 2 /mm HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU HIGH <input type="checkbox"/> ALU LOW <input type="checkbox"/> #325341 ADJ. DRIVE AXLE 1 2 3 4 #107711 GAUGE

FRONT	CASTER	CASTER BLOCK	WING CUTTING LINE	WING SIDE LINE
CASTER 6° <input type="checkbox"/> 7° <input checked="" type="checkbox"/> 9° <input type="checkbox"/> 12° <input type="checkbox"/> OFFSET 2 /slots BUMP STEER SHIM 2 mm	CASTER BLOCK MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>	WING CUTTING LINE 1 2 3 4 5 OFFSET 3 /slots UPRIGHT WHEELBASE SHIM 0 /mm IN FRONT OF ARM	WING SIDE LINE HIGHER <input type="checkbox"/> LOWER <input checked="" type="checkbox"/> WING POSITION UP <input checked="" type="checkbox"/> MIDDLE <input type="checkbox"/> DOWN <input type="checkbox"/> WING THICKNESS 0.75 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 1.5 TYPE TEC	

FF	FR	RF	RR 2°
1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>	1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>	1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>	1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>

FRONT	STEER. PLATE	REAR TOE	GRAPHITE FOR REAR BRACE	REAR BRACE	ARM SHIM
FRONT TOE 2 OUT ALU STEERING PLATE #362574 SHIM UNDER STEER. PLATE SHIM 2 mm SERVO SAVER SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> TIGHT <input type="checkbox"/> MATERIAL STANDARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	REAR TOE 3 IN #36242 PIVOT BALL ECCENTRIC FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/>	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	ARM SHIM 2 mm

FRONT	FRONT CAMBER	FRONT DIFF HEIGHT	REAR DIFF HEIGHT	REAR CAMBER
FRONT CAMBER 2 DOWNSTOP SHIM 0 mm LENGTH 22 mm UPSTOP SHIM 0 mm COLLAR STANDARD <input checked="" type="checkbox"/> -2mm	FRONT DIFF HEIGHT 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100	REAR DIFF HEIGHT 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100	REAR CAMBER 2 DOWNSTOP SHIM 2 mm LENGTH 28,5 mm UPSTOP SHIM 2 mm COLLAR STANDARD <input type="checkbox"/> -2mm	

FRONT ARMS	BALANCE	MOTOR MOUNT	BALANCE	REAR ARMS
LONG <input type="checkbox"/> SHORT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>	BALANCE g	FRONT <input checked="" type="checkbox"/> REAR <input type="checkbox"/>	BALANCE g	LONG <input type="checkbox"/> SHORT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>
CHASSIS ALU <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/>				