

XRAY XB4'23

FRONT

APPLIED ☒ **APPLIED** ☒

ALU C-HUB SHIM
UP ☒ /mm
DOWN ☐ /mm

LONGER BUSHINGS
UP ☒
DOWN ☐

DRIVE SHAFT
CVD ☐ ECS ☒
Length 83 /mm

SHIM
2 mm

STEERING BLOCK
MEDIUM ☐
HARD ☐
GRAPHITE ☐

LOWER SHOCK POSITION

DOWNSTOP
#107711 GAUGE

REAR UPRIGHT
SHIMS 2 /mm
HARD ☐
GRAPHITE ☐
ALU HIGH ☒
ALU LOW ☐
#325341 ADJ. DRIVE AXLE
1 2 3 4

ROLL ENTER

DRIVE SHAFT
Length /mm

SHIM
4 mm

DOWNSTOP
#107711 GAUGE

CASTER
6° ☐
7° ☐
9° ☐
12° ☒

CASTER BLOCK
MEDIUM ☐
HARD ☐
GRAPHITE ☐
ALU ☒

BUMP STEER
SHIM 2 mm

WING CUTTING LINE
1 2 3 4 5

OFFSET
3 /slots

UPRIGHT WHEELBASE
SHIM 2 /mm
IN FRONT OF ARM

WING SIDE LINE
HIGHER ☒
LOWER ☐
WING POSITION
UP ☐
MIDDLE ☒
DOWN ☐
WING THICKNESSES
0.75 ☐ 1 ☐ 1.5 ☐
TYPE Kit

FF ☐ 1° ☒ 0.5°
FR ☐ 1° ☒ 0.5°

ROLL CENTER
ECCENTRIC BUSHINGS
☒ 1° ☐ 0.5°

RF ☐ 1° ☒ 0.5°
RR 2° ☐ 1° ☒ 0.5°

UP ☒ **DOWN** ☐

FRONT TOE
OUT ☐ IN ☒
1

ARM SHIM
mm

STEER. PLATE
HARD ☐
GRAPHITE ☐
ALU ☒
BUMP STEER
SHIM 2 mm
SHIM UNDER STEER. PLATE

SERVO SAVER
SOFT ☐
MEDIUM ☐
TIGHT ☒
MATERIAL
STANDARD ☐
GRAPHITE ☒

REAR TOE
2

GRAPHITE FOR REAR BRACE
YES ☒
NO ☐

REAR BRACE
MEDIUM ☐
HARD ☒

ARM SHIM
0 mm

FRONT CAMBER
2

DOWNSTOP
SHIM mm

LENGTH
mm

UPSTOP
SHIM 2 mm

COLLAR
STANDARD ☒ -2mm

FRONT DIFF HEIGHT
RIDE HEIGHT 14 mm
#107720 GAUGE

REAR DIFF HEIGHT
2

REAR CAMBER
DOWNSTOP
SHIM 2 mm
LENGTH
mm
UPSTOP
SHIM 2 mm
COLLAR
STANDARD ☒ -2mm

RIDE HEIGHT
14 mm

FRONT ARMS
LONG ☐
SHORT ☒
MEDIUM ☐
HARD ☐
GRAPHITE ☒

BALANCE
g

MOTOR MOUNT
FRONT ☒ REAR ☐

T-BRACE

REAR ARMS
LONG ☒
SHORT ☐
MEDIUM ☐
HARD ☐
GRAPHITE ☒

CHASSIS
ALU ☒
GRAPHITE ☐

BATTERY POSTS
FRONT BATTERY POST
REAR BATTERY POST
35g

SIDE GUARDS
HARD ☒
GRAPHITE ☐

BALANCE
g