

SET-UP SHEET

XRAY GTX8'23 SET-UP VER. 01 ©XRAY

XRAY GTX8'23 C-HUB

RACE	U.I.S.P. Italian Championship Rd.3		
TRACK	Miniautodromo Teramo - ITALY		
NAME	Natanaele Senesi	DATE	16/07/2023

TEMPERATURE AIR	35°	TEMPERATURE TRACK	2nd
LAPS	N/D	FINAL POS.	2nd
BEST LAPTIME	5.76 ^s	RACE LENGTH	5 /min

TRACKS			
CONDITION	<input type="checkbox"/> SMOOTH	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> HIGH

1ST	GEARING	2ND
13T 14T 15T 16T 17T 18T	PINION GEARS	17T 18T 19T 20T 21T
SPUR GEARS		
48T 49T 50T	STANDARD <input type="checkbox"/> GRAPHITE <input type="checkbox"/>	45T 46T 47T

CLUTCH	
CLUTCH	STANDARD <input type="checkbox"/> OTHER <input type="checkbox"/>
SHOE	Graphite 500.000
	Graphite 50.000
	SPRING

FRONT	DIFFERENTIAL	REAR
	CASE MATERIAL	
20 /cSt	OIL	45 /cSt

FRONT	SHOCKS	REAR
2 DOTZ - 1 STRIPE	SPRINGS	2 DOTZ - 1 STRIPE
2.000 /cSt	OIL	2.000 /cSt
STD	MEMBRANE	STD
2.5 /%	REBOUND	2.8 /%
<input checked="" type="checkbox"/> 6 HOLES	PISTONS	<input checked="" type="checkbox"/> 6 HOLES
<input type="checkbox"/> 8 HOLES	1.1 mm	<input type="checkbox"/> 8 HOLES
<input type="checkbox"/> 10 HOLES	1.2 mm	<input type="checkbox"/> 10 HOLES
BLITZ GT6 - 1.0 MM	OTHER PISTONS	3820

FRONT	ANTI-ROLL BAR	REAR
	THICKNESS	

FRONT	TIRES	REAR
	TIRES TYPE: P.M.T. Tyres	
	Q3 ← COMPOUND → Q3	
	Q3 ← COMPOUND → Q3	

ENGINE	
TYPE	Hobbywing XERUN 2.800 KV
MUFFLER	Hobbywing XR8 PRO G2S
MANIFOLD	Nosram 9.400 mAh - 135C
PLUG	
FUEL	

BODY TYPE	TOTAL WEIGHT
N/D	N/D /g

COMMENTS
I used X-RAY #355086 to have a more durable and cosistent DIFF. feeling. I used X-RAY #351460 to have a more stable body.

FRONT	REAR
STEERING BLOCK COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>	C-HUB COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>
FRONT ARM SOFT <input type="checkbox"/> MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> X-HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/>
OFFSET 0 <input type="checkbox"/> +1 <input checked="" type="checkbox"/> +2 <input type="checkbox"/>	CASTER 16° <input type="checkbox"/> 6° <input checked="" type="checkbox"/> 2° <input type="checkbox"/>
CASTER BUSHINGS +2° <input type="checkbox"/> +1° <input type="checkbox"/> 0° <input checked="" type="checkbox"/> -1° <input type="checkbox"/> -2° <input type="checkbox"/>	UPPER SHOCK POSITION 6 5 4 3 2 1
FRONT DROOP 28	UPRIGHT ROLL CENTER 4 3 2 1
MEASURE UNDER WHEEL AXLE #107717 GAUGE	REAR SHOCK PLATE POSITION IN <input checked="" type="checkbox"/> OUT <input type="checkbox"/>
	LOWER ROLL CENTER 3 2 1
	REAR DROOP 28
	MEASURE UNDER WHEEL AXLE #107717 HUDY GAUGE

FRONT	REAR
BUMP STEER SHIM /mm	WING HIGH 33 /mm
STEERING BLOCK	GRAPHITE BRACE WITHOUT <input type="checkbox"/> 1-PIECE <input type="checkbox"/> 2-PIECES <input checked="" type="checkbox"/>
STEERING PLATE	REAR DIFFUSOR YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
SHIMS PLACE ALWAYS UNDER	
WHEELBASE SHIM POSITION <input checked="" type="checkbox"/> 0 mm <input type="checkbox"/> 2 mm	SHIMS IN FRONT OF REAR ARM 2 mm 4 mm
SHIMS BEHIND FRONT ARM	
FF 1° <input checked="" type="checkbox"/> 0.5°	RF 1° <input type="checkbox"/> 0.5°
FR 1° <input checked="" type="checkbox"/> 0.5°	RR 1° <input type="checkbox"/> 0.5°
FRONT LOWER ROLL CENTER	REAR LOWER ROLL CENTER
ECCENTRIC BUSHINGS	

FRONT	REAR
2° FRONT TOE OUT	3° REAR TOE IN
ACKERMANN POSITION 3 2 1	
TIGHTEN SERVO SAVER MATERIAL TIGHT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> MEDIUM <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> SOFT <input type="checkbox"/>	UPPER PLATE COMPOSITE <input type="checkbox"/> GRAPHITE <input type="checkbox"/>
	WHEELBASE 0 mm 1 mm 2 mm 3 mm 4 mm <input checked="" type="checkbox"/> 0 mm <input type="checkbox"/> 1 mm <input type="checkbox"/> 2 mm <input type="checkbox"/> 3 mm <input type="checkbox"/> 4 mm
	SHIMS IN FRONT OF UPRIGHT
	ENGINE MOUNT STANDARD <input type="checkbox"/> MONOBLOCK <input type="checkbox"/>

FRONT	REAR
2° FRONT CAMBER	REAR CAMBER 3.5°
REAR DIFF HEIGHT UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	
LENGTH 22,5 mm	LENGTH 22,5 mm
RISE HEIGHT 8 /mm	RISE HEIGHT 9 /mm