

SET-UP SHEET

X4'23 SET-UP SHEET VER.1 ©XRAY

XRAY X4'23

RACE	PTS #3			
TRACK	CRB Monsanto			
NAME	Alexander Hagberg	DATE	23/07/23	

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
1	1	16.3 /sec	/	

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL 5000 /cSt
PINION 48 /T	SPUR GEAR 100 /T	FINAL DRIVE RATIO 3.958

FRONT	SHOCKS	REAR
2.8	XRAY SPRINGS	2.7
425	OIL /cSt	450
25	REBOUND %	25
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH 8.5 /mm			SHOCK LENGTH 8.5 /mm

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

TPro 36	TIRES	TPro 36
LSB (Spec)	ADDITIVE	LSB (Spec)
15	ADDITIVE TIMING	15

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT 1330 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
----------------------	----------------	------------	-----------

MOTOR	HW G4 13.5T	TIMING	
ESC	HW XR10 PRO G2S	BATTERIES	Nosram 9400
BODY	Lens Ghibli L	WING	Twister L

65 /mm	Dimension from body post to window bottom line	BODY POSITION
1/8 hole, 0, o-rings /mm	Dimension from body post to upper holder	WING SIDE PLATE
		YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
64 /mm	Dimension from edge to surface	

X4'23	1.6mm <input checked="" type="checkbox"/> 2.0mm <input checked="" type="checkbox"/> 1.6mm	TOP DECK CUTTING
X4'22	2.0mm <input type="checkbox"/> 2.0mm <input type="checkbox"/>	
X4'22	2.0mm <input type="checkbox"/> 1.6mm <input type="checkbox"/>	
	NONE <input type="checkbox"/> BEARING <input type="checkbox"/>	

COMMENTS
Tire warmers 65 deg C, cleaned with brake cleaner.

FRONT & REAR SUSPENSION	
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER 2 /mm	HEIGHT 19 /mm
SHIM 6.5 /mm	
UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm	UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm
2.5 /mm FF	5.0 /mm FR
5.0 /mm RIDE HEIGHT	2.5 /mm RR
<input checked="" type="checkbox"/> SERVO SAVER	<input type="checkbox"/> SERVO HORN
TOE GAIN 6.0 /mm	3.0 /mm RF
	5.2 /mm RR
	RIDE HEIGHT

2.0 /deg. CAMBER	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	FRONT SUSPENSION	0.5 /mm SHIM	3.0 /mm	FRONT HUB
Left = Right		FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	FRONT SHOCK POSITION		HARD <input checked="" type="checkbox"/>
		BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm NO <input type="checkbox"/>			GRAPHITE <input type="checkbox"/>
		DRIVE SHAFT 58mm 59mm BEARING BLADE			ALU <input type="checkbox"/>
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	5.6 /mm	SHIM 0.5 /mm
					DOWNSTOP

2.0 /deg. CAMBER	BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>	REAR SUSPENSION	0.5 /mm SHIM	3.0 /mm	REAR HUB
Left = Right		REAR SHOCK POSITION			HARD <input checked="" type="checkbox"/>
		DRIVE SHAFT 52mm 54mm BEARING BLADE			GRAPHITE <input type="checkbox"/>
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	4.4 /mm	ALU <input type="checkbox"/>
					SHIM 0.5 /mm
					DOWNSTOP

FRONT TOP VIEW		REAR
1.25 TOE OUT	ACKERMANN SHIM 0.5 /mm	3.0 TOE IN
Left = Right		Left = Right
DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>	BRASS WEIGHT FOR MOTOR MOUNT	SHIM 0 /mm
UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM STD. <input type="checkbox"/>	STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEERING PLATE 8.0mm STD. <input checked="" type="checkbox"/> 7.5mm
HUB OFFSET STD. <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> +0.5mm SHIM/mm		HUB OFFSET STD. <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> +0.5mm SHIM/mm

FRONT BOTTOM VIEW		REAR
STEER. LOCK 27 /deg.	STEER. SHIM SIZE 7.5 /mm	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	FR SERVO HOLDER	MOTOR MOUNT
FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	CHASSIS GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input type="checkbox"/>	REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>