

XRAY GTX8'23 C-HUB

FRONT

STEERING BLOCK
COMPOSITE ☒
ALU ☐

OFFSET
0 ☐ +1 ☒ +2 ☐

CASTER BUSHINGS
+2° ☐
+1° ☐
0° ☐
-1° ☒
-2° ☐

FRONT DROOP
26

MEASURE UNDER WHEEL AXLE #107717 GAUGE

C-HUB
COMPOSITE ☒
ALU ☐
CASTER
16° ☐
6° ☒
2° ☐

FRONT ARM
SOFT ☐
MEDIUM ☒
HARD ☐
GRAPHITE ☐

UPPER SHOCK POSITION

UPRIGHT ROLL CENTER

REAR SHOCK PLATE POSITION
IN ☐ OUT ☒

REAR ROLL CENTER

REAR DROOP
29

MEASURE UNDER WHEEL AXLE #107717 HUDDY GAUGE

REAR ARMS
MEDIUM ☐
HARD ☒
X-HARD ☐
GRAPHITE ☐

LOWER ROLL CENTER
ALU ☐
UPRIGHT
MEDIUM ☐
HARD ☒
GRAPHITE ☐
OFFSET
STANDARD ☐
+1 ☒ +2 ☐

FRONT

BUMP STEER SHIM /mm
STEERING BLOCK 0
STEERING PLATE 3
SHIMS PLACE ALWAYS UNDER

WHEELBASE SHIM POSITION
0 mm ☐ 2 mm ☒
SHIMS BEHIND FRONT ARM

GRAPHITE BRACE
WITHOUT ☐
1-PIECE ☐
2-PIECES ☒

REAR DIFFUSOR
YES ☐ NO ☒

WHEELBASE SHIM POSITION
2 mm ☐ 4 mm ☒
SHIMS IN FRONT OF REAR ARM

FF 1° ☐ 0.5° ☐
FR 1° ☒ 0.5° ☐
RR 1° ☒ 0.5° ☐
RF 1° ☒ 0.5° ☐

FRONT LOWER ROLL CENTER REAR
ECCENTRIC BUSHINGS

FRONT TOE OUT 1

REAR TOE IN 3

TIGHTEN SERVO SAVER MATERIAL
TIGHT ☒
MEDIUM ☐
SOFT ☐
MEDIUM ☐
GRAPHITE ☒

UPPER PLATE
COMPOSITE ☐
GRAPHITE ☐

WHEELBASE
0 mm ☐ 1 mm ☐ 2 mm ☒ 3 mm ☐ 4 mm ☐
SHIMS IN FRONT OF UPRIGHT

ACKERMANN POSITION
3 2 1

ENGINE MOUNT
STANDARD ☐
MONOBLOCK ☐

FRONT CAMBER 1.5

REAR CAMBER 3

REAR DIFF HEIGHT
UP ☒
DOWN ☐

LENGTH 22.5 mm

FRONT RIDE HEIGHT 7 /mm

REAR RIDE HEIGHT 9 /mm

LENGTH 22.5 mm

FRONT

REAR