

SET-UP SHEET

XRAY XB4'23

RACE	Austrian Nationals R4 DRY	
TRACK	HOECO	
NAME	Max	DATE 6.8.2023

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION	4	FINAL POSITION	2

TRACK	
SIZE	<input type="checkbox"/> OPEN <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> TIGHT
TRACTION	<input type="checkbox"/> VERY-LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> VERY-HIGH
SURFACE	<input type="checkbox"/> SMOOTH <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> BUMPY
TYPE	<input type="checkbox"/> CLAY <input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASTRO
CONDITION	<input type="checkbox"/> BLUE GROOVE <input type="checkbox"/> HARD PACKED <input checked="" type="checkbox"/> DRY
	<input type="checkbox"/> DUSTY <input type="checkbox"/> LOAMY <input type="checkbox"/> WET

DIFFERENTIAL TYPE		
FRONT ↓	MIDDLE ↓	REAR ↓
GEAR DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
BALL DIFF <input type="checkbox"/>	SLIPPER <input type="checkbox"/>	BALL DIFF <input type="checkbox"/>
ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>
60° 90° 120°	60° 90° 120°	60° 90° 120°
OIL 7k cst	OIL 200k cst	OIL 5k cst

SATELLITE GEARS		
COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>	COMPOSITE <input type="checkbox"/>
STEEL <input checked="" type="checkbox"/>	STEEL <input checked="" type="checkbox"/>	STEEL <input checked="" type="checkbox"/>
40T <input checked="" type="checkbox"/> 41T	CROWN GEAR	40T <input checked="" type="checkbox"/> 41T

CENTRAL SLIPPER & ONE-WAY SETTING	
SLIPPING ADJUSTMENT	ONE-WAY TIGHTNESS
LOOSE	1 CW TURN (BASIC SETUP)
	FULLY TIGHTEN

GEARING	
PINION 20 T	81 T CENTER DIFF SPUR

FRONT	SHOCKS	REAR
2 dot Dirt	SPRINGS	1 dot Dirt
cst 500	OIL	cst 375
%	REBOUND	%
<input checked="" type="checkbox"/> 2 HOLES	PISTONS	<input checked="" type="checkbox"/> 2 HOLES
<input type="checkbox"/> 3 HOLES	ø1.2mm <input type="checkbox"/>	<input type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	ø1.3mm <input type="checkbox"/>	<input type="checkbox"/> 6 HOLES
1,8 HOLES	ø1.4mm <input type="checkbox"/>	2,2 HOLES
	ø1.6mm <input type="checkbox"/>	
	ø1.7mm <input type="checkbox"/>	
	CUSTOM PISTONS	
	a mm	

FRONT	ANTI ROLL BAR	REAR
1,8	THICKNESS	1,8

FRONT	TIRES	REAR
JC handout	BRAND	JC handout
	COMPOUND	
	INSERTS	
XRAY	WHEELS	XRAY

ELECTRONICS		
MOTOR	5,5T	Nitride
MOTOR TIMING	30	LCG
BATTERY SIZE		SPEEDO
STD. SHORT <input type="checkbox"/> LOW SHORT <input checked="" type="checkbox"/>		BATTERY

BODY	
TYPE	Gamma 4CL
	STANDARD <input type="checkbox"/> LIGHT <input checked="" type="checkbox"/>

COMMENTS	

FRONT	APPLIED <input type="radio"/> <input checked="" type="checkbox"/> APPLIED	REAR
ALU C-HUB SHIM	LONGER BUSHINGS	DRIVE SHAFT
UP /mm	UP <input type="checkbox"/>	CVD <input type="checkbox"/> ECS <input checked="" type="checkbox"/>
DOWN /mm	DOWN <input checked="" type="checkbox"/>	Length 83 /mm
SHIM 2 mm	SHIM 2 mm	SHIM 2 mm
STEERING BLOCK	ROLL ENTER	SHIMS 2 /mm
MEDIUM <input type="checkbox"/>		HARD <input checked="" type="checkbox"/>
HARD <input type="checkbox"/>		GRAPHITE <input type="checkbox"/>
GRAPHITE <input checked="" type="checkbox"/>		ALU HIGH <input type="checkbox"/>
		ALU LOW <input type="checkbox"/>
LOWER SHOCK POSITION		1° 0.5°
#107711 GAUGE	DOWNSTOP	#107711 GAUGE

FRONT	CASTER	CASTER BLOCK	WING CUTTING LINE	WING SIDE LINE
CASTER	6° <input type="checkbox"/>	MEDIUM <input type="checkbox"/>	1 2 3 4 5	HIGHER <input type="checkbox"/>
	7° <input type="checkbox"/>	HARD <input type="checkbox"/>		LOWER <input checked="" type="checkbox"/>
	9° <input checked="" type="checkbox"/>	GRAPHITE <input checked="" type="checkbox"/>		
	12° <input type="checkbox"/>	ALU <input type="checkbox"/>		
OFFSET 2 /slots	BUMP STEER	UP <input checked="" type="checkbox"/>	MIDDLE <input type="checkbox"/>	DOWN <input type="checkbox"/>
	SHIM 2 mm	WING THICKNESS	0.75 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 1.5	TYPE TEC

FF	RF	RR 2°
1° <input type="checkbox"/>	1° <input checked="" type="checkbox"/>	1° <input type="checkbox"/>
0.5° <input type="checkbox"/>	0.5° <input type="checkbox"/>	0.5° <input checked="" type="checkbox"/>
1° <input checked="" type="checkbox"/>	1° <input type="checkbox"/>	1° <input type="checkbox"/>
0.5° <input type="checkbox"/>	0.5° <input checked="" type="checkbox"/>	0.5° <input type="checkbox"/>
	UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>	

FRONT	STEER. PLATE	REAR TOE	GRAPHITE FOR REAR BRACE	REAR BRACE	ARM SHIM
FRONT TOE 1	HARD <input checked="" type="checkbox"/>	2.5	YES <input checked="" type="checkbox"/>	MEDIUM <input type="checkbox"/>	0 mm
	GRAPHITE <input type="checkbox"/>		NO <input type="checkbox"/>	HARD <input checked="" type="checkbox"/>	
	ALU <input type="checkbox"/>				
	BUMP STEER				
	SHIM 4 mm				
	SHIM UNDER STEER. PLATE				
	SERVO SAVER				
	SOFT <input type="checkbox"/>				
	MEDIUM <input checked="" type="checkbox"/>				
	TIGHT <input type="checkbox"/>				
	MATERIAL				
	STANDARD <input checked="" type="checkbox"/>				
	GRAPHITE <input type="checkbox"/>				

FRONT	FRONT CAMBER	FRONT DIFF HEIGHT	REAR DIFF HEIGHT	REAR CAMBER
FRONT CAMBER	2			2
DOWNSTOP	SHIM mm			DOWNSTOP
LENGTH	22 mm			LENGTH
UPSTOP	SHIM mm			UPSTOP
COLLAR	STANDARD <input checked="" type="checkbox"/> -2mm			COLLAR

FRONT ARMS	BALANCE	MOTOR MOUNT	BALANCE	REAR ARMS
LONG <input type="checkbox"/>		FRONT <input type="checkbox"/> REAR <input type="checkbox"/>	10 g	LONG <input checked="" type="checkbox"/>
SHORT <input checked="" type="checkbox"/>				SHORT <input type="checkbox"/>
MEDIUM <input type="checkbox"/>				MEDIUM <input type="checkbox"/>
HARD <input checked="" type="checkbox"/>				HARD <input checked="" type="checkbox"/>
GRAPHITE <input type="checkbox"/>				GRAPHITE <input type="checkbox"/>