

# SET-UP SHEET

# XRAY XB4'22

RACE	
TRACK	
NAME	DATE

LAPS	BEST LAP TIME	sec
QUALIFYING POSITION	FINAL POSITION	

TRACK	
SIZE	<input type="checkbox"/> OPEN <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> TIGHT
TRACTION	<input type="checkbox"/> VERY-LOW <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> VERY-HIGH
SURFACE	<input type="checkbox"/> SMOOTH <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> BUMPY
TYPE	<input type="checkbox"/> CLAY <input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASTRO
CONDITION	<input type="checkbox"/> BLUE GROOVE <input type="checkbox"/> HARD PACKED <input checked="" type="checkbox"/> DRY
	<input type="checkbox"/> DUSTY <input type="checkbox"/> LOAMY <input type="checkbox"/> WET

DIFFERENTIAL TYPE		
FRONT ↓	MIDDLE ↓	REAR ↓
GEAR DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
BALL DIFF <input type="checkbox"/>	SLIPPER <input type="checkbox"/>	BALL DIFF <input type="checkbox"/>
ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>
60° 90° 120°	60° 90° 120°	60° 90° 120°
OIL 20k cst	OIL 200k cst	OIL 15k cst

SATELLITE GEARS		
COMPOSITE <input type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/>	COMPOSITE <input type="checkbox"/>
STEEL <input checked="" type="checkbox"/>	STEEL <input type="checkbox"/>	STEEL <input checked="" type="checkbox"/>
40T <input type="checkbox"/> 41T	CROWN GEAR	40T <input type="checkbox"/> 41T

CENTRAL SLIPPER & ONE-WAY SETTING	
SLIPPING ADJUSTMENT	ONE-WAY TIGHTNESS
<input checked="" type="checkbox"/>	<input type="checkbox"/>
1 CCW TURN (BASIC SETUP)	FULLY TIGHTEN

GEARING	
PINION 19 T	20 T CENTER DIFF SPUR

FRONT	SHOCKS	REAR
4	SPRINGS	3
cst 600	OIL	cst 400
%	REBOUND	%
<input checked="" type="checkbox"/> 2 HOLES	PISTONS	<input checked="" type="checkbox"/> 2 HOLES
<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> ø1.2mm	<input type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	<input type="checkbox"/> ø1.3mm	<input type="checkbox"/> 6 HOLES
	<input checked="" type="checkbox"/> ø1.4mm	
	<input type="checkbox"/> ø1.6mm	
	<input checked="" type="checkbox"/> ø1.7mm	
	CUSTOM PISTONS	
	mm	

FRONT	ANTI ROLL BAR	REAR
1,8	THICKNESS	1,8

FRONT	TIRES	REAR
	BRAND	
	COMPOUND	
	INSERTS	
	WHEELS	

ELECTRONICS	
MOTOR HW G3 5,5T	HW G2S
MOTOR TIMING st	BATTERY
BATTERY SIZE	
STD. SHORT <input type="checkbox"/> LOW SHORT <input checked="" type="checkbox"/>	

BODY	
TYPE	STANDARD <input checked="" type="checkbox"/> LIGHT

COMMENTS	
----------	--

FRONT	APPLIED <input type="checkbox"/> <input checked="" type="checkbox"/> APPLIED	REAR
-------	--	------

ALU C-HUB SHIM	LONGER BUSHINGS	DRIVE SHAFT
UP /mm	UP <input checked="" type="checkbox"/>	CVD <input checked="" type="checkbox"/> ECS
DOWN /mm	DOWN <input type="checkbox"/>	Length st /mm

SHIM	SHIMS	HARD
2 mm	2 /mm	GRAPHITE
ALU <input type="checkbox"/>		ALU <input checked="" type="checkbox"/>

STEERING BLOCK	LOWER SHOCK POSITION	ROLL ENTER
MEDIUM <input type="checkbox"/>		
HARD <input checked="" type="checkbox"/>		
GRAPHITE <input type="checkbox"/>		

REAR UPRIGHT	SHIM	SHIMS
	4 mm	2 /mm

WING CUTTING LINE	WING SIDE LINE
1 2 3 4 5	HIGHER <input type="checkbox"/> LOWER <input checked="" type="checkbox"/>

CASTER	CASTER BLOCK
6° <input type="checkbox"/>	MEDIUM <input type="checkbox"/>
7° <input type="checkbox"/>	HARD <input checked="" type="checkbox"/>
9° <input checked="" type="checkbox"/>	GRAPHITE <input type="checkbox"/>
12° <input type="checkbox"/>	ALU <input type="checkbox"/>

OFFSET	BUMP STEER
3	SHIM 2 mm

UPRIGHT WHEELBASE	SHIM
SHIM 1 /mm	

FF	FR	RR 2°

ROLL CENTER	ECCENTRIC BUSHINGS
1° <input checked="" type="checkbox"/> 0.5° <input type="checkbox"/>	

FRONT TOE	REAR TOE
1	

STEER. PLATE	BUMP STEER
HARD <input checked="" type="checkbox"/>	SHIM 2 mm
GRAPHITE <input type="checkbox"/>	
ALU <input type="checkbox"/>	

ARM SHIM	REAR BRACE
0 mm	MEDIUM <input type="checkbox"/>
	HARD <input checked="" type="checkbox"/>

FRONT CAMBER	FRONT DIFF HEIGHT
2	

REAR DIFF HEIGHT	REAR CAMBER
	2

DOWNSTOP	DOWNSTOP
SHIM 0 mm	SHIM 1 mm

LENGTH	LENGTH
23 mm	28,5 mm

UPSTOP	UPSTOP
SHIM 0 mm	SHIM-rin (mm)

COLLAR	COLLAR
STANDARD <input checked="" type="checkbox"/> -2mm	STANDARD <input type="checkbox"/> -2mm

FRONT ARMS	BALANCE	SIDE GUARDS	BALANCE	REAR ARMS
LONG <input type="checkbox"/>		HARD <input type="checkbox"/>		LONG <input checked="" type="checkbox"/>
SHORT <input checked="" type="checkbox"/>		GRAPHITE <input checked="" type="checkbox"/>		SHORT <input type="checkbox"/>
MEDIUM <input type="checkbox"/>				MEDIUM <input type="checkbox"/>
HARD <input type="checkbox"/>				HARD <input type="checkbox"/>
GRAPHITE <input checked="" type="checkbox"/>				GRAPHITE <input checked="" type="checkbox"/>

CHASSIS FLEX
SCREW USED <input checked="" type="checkbox"/>
SCREW NOT USED <input type="checkbox"/>