

SET-UP SHEET

X4'23 SET-UP SHEET VER.1 ©XRAY

XRAY X4'23

RACE	Guangdong-H.K-Macau Greater Bay Area 3rd Round		
TRACK	Tom Racing Circuit		
NAME	Kimi Yam	DATE	27-8-2023

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
1st	A1	15.911 /sec	20	5:12.826

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL 5000 /cSt
PINION 28 /T	SPUR GEAR 110 /T	FINAL DRIVE RATIO 7.46

FRONT	SHOCKS	REAR
Race OPT2.9	XRAY SPRINGS	Race OPT 2.9
459	OIL /cSt	475
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input type="checkbox"/> 4 HOLES <input checked="" type="checkbox"/> 1.1mm	<input type="checkbox"/> 4 HOLES <input checked="" type="checkbox"/> 1.1mm
<input type="checkbox"/> PSS <input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS <input type="checkbox"/> 1.2mm
SHOCK LENGTH 8.5 /mm	SHOCK LENGTH 8.5 /mm

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Team Powers	TIRES	Team Powers
Red Spider	ADDITIVE	Red spider
10	ADDITIVE TIMING	10

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT 1325 /g	WEIGHT BALANCE	FRONT 49 %	REAR 51 %
----------------------	----------------	------------	-----------

MOTOR	Team Powers V5 4.5T	TIMING	
ESC	Team Powers V5bt	BATTERIES	Coddar 6300mah
BODY	Bittydesign Epton UL	WING	STD

66 /mm	Dimension from body post to window bottom line	BODY POSITION
7 /mm	Dimension from body post to upper holder	WING SIDE PLATE
		YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
	Dimension from edge to surface	

1.6mm <input checked="" type="checkbox"/> 2.0mm <input type="checkbox"/> 1.6mm	
X4'23 <input checked="" type="checkbox"/>	
X4'22 <input type="checkbox"/>	
X4'22 <input type="checkbox"/>	
NONE <input type="checkbox"/> BEARING <input type="checkbox"/>	

COMMENTS

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
Adjust with eccentric bushings		Adjust with eccentric bushings
UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm		UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm
2.5 /mm FF	5 /mm FR	2.5 /mm RF
5 /mm RIDE HEIGHT	2.5 /mm RIDE HEIGHT	5.4 /mm RIDE HEIGHT
	SERVO SAVER <input type="checkbox"/> SERVO HORN <input checked="" type="checkbox"/>	

1.5 /degr. CAMBER	BODY STOP YES <input checked="" type="checkbox"/> NO	FRONT SUSPENSION	2 /mm SHIM 3 /mm	FRONT HUB
Left = Right				HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>
		FRONT BRACE YES <input checked="" type="checkbox"/> NO	FRONT SHOCK POSITION	SHIM 0.5 /mm
		BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm NO		
		DRIVE SHAFT 58mm 59mm BEARING BLADE		
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	5.6 /mm DOWNSTOP

2 /degr. CAMBER	BODY POST VERTICAL <input checked="" type="checkbox"/> HORIZONTAL	REAR SUSPENSION	1 /mm SHIM 3 /mm	REAR HUB
Left = Right				HARD <input checked="" type="checkbox"/> GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/>
		REAR SHOCK POSITION		SHIM 0.5 /mm
		DRIVE SHAFT 52mm 54mm BEARING BLADE		
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	4.4 /mm DOWNSTOP

FRONT TOP VIEW	REAR
1 TOE OUT Left = Right	2 TOE IN Left = Right
ACKERMANN SHIM 1 /mm	SHIM /mm
DIFF POSITION UP <input checked="" type="checkbox"/> DOWN	DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN
UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM STD.	UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM STD.
STEERING BRIDGE YES <input checked="" type="checkbox"/> NO	STEERING PLATE 8.0mm <input checked="" type="checkbox"/> STD. 7.5mm
HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK 26 /degr.	T-BRACE ALU <input type="checkbox"/> BRASS
STEER. SHIM SIZE 7.5 /mm	MOTOR MOUNT
FRONT BRACE YES <input checked="" type="checkbox"/> NO	CHASSIS T-BRACE
SERVO HOLDER	CHASSIS
FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD	REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD