

SET-UP SHEET

X4'23 SET-UP SHEET VER.1 ©XRAY

XRAY X4'23

RACE	Pre setup for HKRCSA Rd 3		
TRACK	TRC		
NAME	Chan Ka Lok Joey	DATE	15/09/2023

QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME
		/sec	/	

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	SPUR GEAR	FINAL DRIVE RATIO
38 /T	91 /T	4.55

FRONT	SHOCKS	REAR
2.7	XRAY SPRINGS	2.7
400	OIL /Cst	400
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH	8.5 /mm	9 /mm	SHOCK LENGTH

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Rush 40 VS	TIRES	Rush 40 VS
V3 Black	ADDITIVE	V3 Black
5mins / 10mins 65c	ADDITIVE TIMING	5mins / 10mins 65c

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT	1325 /g	WEIGHT BALANCE	FRONT %	REAR %
--------------	---------	----------------	---------	--------

MOTOR	Orca 13.5t Handout	TIMING	
ESC	Orca Totem	BATTERIES	Coddar 6600mah
BODY	Lensbodies Ghibli 0.5	WING	Std

65 /mm	Dimension from body post to window bottom line	BODY POSITION
/mm	Dimension from body post to upper holder	WING SIDE PLATE
/mm	Dimension from edge to surface	YES <input type="checkbox"/> NO <input type="checkbox"/>

X4'23	1.6mm <input checked="" type="checkbox"/> 2.0mm <input checked="" type="checkbox"/> 1.6mm	TOP DECK CUTTING
X4'22	2.0mm <input type="checkbox"/> 2.0mm <input type="checkbox"/> 1.6mm	
X4'22	2.0mm <input type="checkbox"/> 1.6mm <input type="checkbox"/> NONE <input type="checkbox"/> BEARING	

SpeedDome-RC rear +1 Chassis.
SpeedDome-RC Split top deck (Both Soft type at front and rear)
5g beside servo , under front belt..

FRONT CASTER	FRONT & REAR SUSPENSION	REAR CASTER
Adjust with eccentric bushings		Adjust with eccentric bushings
UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm		UPPER CLAMP STD. <input checked="" type="checkbox"/> -1.5mm
2.5 /mm FF	5.2 /mm FR	2.5 /mm RF
RIDE HEIGHT	RIDE HEIGHT	RIDE HEIGHT
<input checked="" type="checkbox"/> SERVO SAVER	<input checked="" type="checkbox"/> SERVO HORN	
TOE GAIN 6 /mm		TOE GAIN 6 /mm

2 /deg. CAMBER	Left = Right	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	FRONT SUSPENSION	2 /mm SHIM 3 /mm	FRONT HUB
			FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	FRONT SHOCK POSITION	HARD <input type="checkbox"/>
			BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm NO <input type="checkbox"/>		GRAPHITE <input checked="" type="checkbox"/>
			DRIVE SHAFT 58mm 59mm BEARING BLADE		ALU <input type="checkbox"/>
			#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	SHIM 0.5 /mm
					DOWNSTOP 5.4 /mm

2 /deg. CAMBER	Left = Right	BODY POST VERTICAL <input checked="" type="checkbox"/> HORIZONTAL <input type="checkbox"/>	REAR SUSPENSION	1.5 /mm SHIM 3 /mm	REAR HUB
			REAR SHOCK POSITION		HARD <input type="checkbox"/>
			DRIVE SHAFT 52mm 54mm BEARING BLADE		GRAPHITE <input checked="" type="checkbox"/>
			#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	ALU <input type="checkbox"/>
					SHIM 1 /mm
					DOWNSTOP 4.6 /mm

1 TOE OUT	Left = Right	ACKERMANN SHIM 0 /mm	FRONT TOP VIEW	3 TOE IN	Right = Left
DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>			BRASS WEIGHT FOR MOTOR MOUNT	SHIM 2 /mm	DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>
UPPER ARM SOFT <input type="checkbox"/> MEDIUM STD. <input checked="" type="checkbox"/>			STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>		UPPER ARM SOFT <input type="checkbox"/> MEDIUM STD. <input checked="" type="checkbox"/>
HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm			STEERING PLATE 8.0mm <input checked="" type="checkbox"/> STD. <input type="checkbox"/> 7.5mm		HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK 26 /deg.	T-BRACE ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/>
STEER. SHIM SIZE 7.5 /mm	
FRONT BRACE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	MOTOR MOUNT
FRONT ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	CHASSIS GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU FLEX <input type="checkbox"/>
	REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>