

SET-UP SHEET

X4F'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4F'24

RACE	ETS RD6		
TRACK	Daun		
NAME	Jan Gehrig	DATE	29.01.23

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAPTIME	LAPS	TIME
	9	11	19,9 /sec	/	

TRACK	
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET <input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFFERENTIAL - OIL 200k /cSt		
PINION / T 38	SPUR GEAR / T 100	FINAL DRIVE RATIO 5

FRONT	SHOCKS	REAR
2,5-2,8	XRAY SPRINGS	2,6
425	OIL /cSt	350
20	REBOUND %	20
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input type="checkbox"/> 4 HOLES	<input type="checkbox"/> 1.1mm	<input type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input checked="" type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input checked="" type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS
2x0.8			
SHOCK LENGTH 9 /mm		SHOCK LENGTH 9 /mm	

1,3 THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm 1,8
-------------------------	----------------------	-------------------------

Ride ETS	TIRES
CS	ADDITIVE
30	ADDITIVE TIMING

FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT 1260 /g	WEIGHT BALANCE	FRONT 64 %	REAR 36 %
-----------------------------	----------------	-------------------	------------------

MOTOR Justock 17.5	TIMING
ESC Justock Ets	BATTERIES Nosram 4200
BODY Blitz YRS	WING Stock

54 /mm	Dimension from body post to window bottom line	BODY POSITION
WING SIDE PLATE	YES <input type="checkbox"/> NO <input type="checkbox"/>	
WING SIDE PLATE	YES <input type="checkbox"/> NO <input type="checkbox"/>	
WING SIDE PLATE	YES <input type="checkbox"/> NO <input type="checkbox"/>	

TOP DECK CUTTING	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
TOP DECK FLEX	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>

30g weight in bumper. Rear XLP shocks with Ulp shock ballend to accomodate rear droop

COMMENTS

FRONT CASTER	BUMP STEER	HEIGHT	SHIM	FRONT & REAR SUSPENSION	REAR CASTER
<input checked="" type="checkbox"/> 5° <input type="checkbox"/> 4° <input type="checkbox"/> 3°	1 /mm	19 /mm	4 /mm		<input checked="" type="checkbox"/> 0.5° <input type="checkbox"/> 1.5° <input type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5°
Adjust with eccentric bushings					Adjust with eccentric bushings
.5 /mm FF	5 /mm	FR .5 /mm	<input type="checkbox"/> SERVO SAVER		TOE GAIN 4 /mm
<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> RIDE HEIGHT	<input checked="" type="checkbox"/> SERVO HORN		3 /mm RF
					5.5 /mm RR
					3 /mm

FRONT CAMBER	BODY STOP	FRONT SUSPENSION	FRONT SHOCK POSITION	FRONT HUB
2 /deg. Left = Right	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	1 /mm SHIM 2 /mm	1 2	HARD <input checked="" type="checkbox"/>
		FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>		GRAPHITE <input type="checkbox"/>
		BULKHEAD SHIMS YES <input checked="" type="checkbox"/> 3mm <input type="checkbox"/> NO <input type="checkbox"/>		ALU <input type="checkbox"/>
		DRIVE SHAFT <input checked="" type="checkbox"/> 58mm <input type="checkbox"/> 59mm		SHIM .5 /mm
		BEARING BLADE <input checked="" type="checkbox"/>		
		#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	5.6 /mm DOWNSTOP

REAR CAMBER	REAR SUSPENSION	REAR SHOCK POSITION	REAR HUB
1,5 /deg. Left = Right	2 /mm SHIM 1 /mm	1 2	HARD <input checked="" type="checkbox"/>
			GRAPHITE <input type="checkbox"/>
			ALU <input type="checkbox"/>
			SHIM 1.5 /mm
			0 /mm DOWNSTOP

FRONT TOP VIEW	REAR
1 TOE OUT Left = Right	2 TOE IN Left = Right
DIFF POSITION UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/>	STEERING ARM & BRIDGE <input checked="" type="checkbox"/> DUAL STD. <input type="checkbox"/> BRIDGE
SHIMS 0 /mm	SHIMS 0 /mm
UPPER ARM SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/>	UPPER ARM SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>
ACKERMANN SHIM 0 /mm	STEERING PLATE 8.0mm <input checked="" type="checkbox"/> STD. 7.5mm <input type="checkbox"/>
HUB OFFSET STD. <input type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm <input checked="" type="checkbox"/> SHIM /mm	HUB OFFSET STD. <input type="checkbox"/> -0.5mm <input checked="" type="checkbox"/> +0.5mm <input type="checkbox"/> SHIM /mm

FRONT BOTTOM VIEW	REAR
WEIGHT LEFT & RIGHT #309825 YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	STEER. LOCK 25 /deg.
BUMPER WEIGHT #309824 YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEER. SHIM SIZE /mm
FRONT BRACE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	MOTOR MOUNT
	CHASSIS GRAPHITE <input checked="" type="checkbox"/>
	REAR ARMS MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>