

XRAY X4'23

FRONT

FRONT CASTER

Adjust with eccentric bushings

5° ☒ 4° ☐ 3° ☐

UPPER CLAMP

STD. ☒ ☐ -1.5mm

BUMP STEER

3 /mm

HEIGHT

/mm

SHIM

4 /mm

2.5 /mm **FF**

5.2 /mm **FR**

RIDE HEIGHT

2.5 /mm **FR**

SERVO SAVER

SERVO HORN

REAR

REAR CASTER

Adjust with eccentric bushings

0.5° ☒ 1.5° ☐ 2.5° ☐ 3.5° ☐ 4.5° ☐ 5.5° ☐

UPPER CLAMP

STD. ☒ ☐ -1.5mm

TOE GAIN

6 /mm

SHIM

2 /mm

2.5 /mm **RF**

5.4 /mm **RR**

RIDE HEIGHT

2.5 /mm **RF**

SERVO SAVER

SERVO HORN

FRONT SUSPENSION

2 /deg. **CAMBER**

Left = Right

BODY STOP

YES ☒ NO ☐

/mm

FRONT BRACE

YES ☐ NO ☒

BULKHEAD SHIMS

YES ☐ 3mm ☒ NO ☐

FRONT SHOCK POSITION

1 2

SHIM

0.5 /mm

DRIVE SHAFT

58mm ☒ 59mm ☐ **BEARING BLADE**

#107702 Chassis Droop Gauge Blocks

#107712 Chassis Droop Gauge

6 /mm **DOWNSTOP**

REAR SUSPENSION

2 /deg. **CAMBER**

Left = Right

BODY POST

VERTICAL ☒ HORIZONTAL ☐

REAR SHOCK POSITION

1 2

SHIM

0.5 /mm

#107702 Chassis Droop Gauge Blocks

#107712 Chassis Droop Gauge

4 /mm **DOWNSTOP**

FRONT TOP VIEW

1 **TOE OUT**

Left = Right

ACKERMANN

SHIM 0.5 /mm

DIFF POSITION

UP ☒ DOWN ☐

SHIM

/mm

UPPER ARM

SOFT ☐ MEDIUM STD. ☒

STEERING BRIDGE

YES ☐ NO ☒

HUB OFFSET

STD. ☒ -0.5mm ☐ +0.5mm ☐ SHIM/mm

STEERING PLATE

8.0mm ☒ STD. ☐ 7.5mm ☐

REAR TOP VIEW

2 **TOE IN**

Left = Right

SHIM

/mm

DIFF POSITION

UP ☐ DOWN ☒

UPPER ARM

SOFT ☒ MEDIUM STD. ☐

HUB OFFSET

STD. ☒ -0.5mm ☐ +0.5mm ☐ SHIM/mm

CHASSIS T-BRACE

ALU ☐ BRASS ☐

FRONT BOTTOM VIEW

STEER. LOCK

/deg.

STEER. SHIM

SIZE /mm

FRONT BRACE

YES ☐ NO ☒

FRONT ARMS

MEDIUM ☐ HARD ☒

CHASSIS

GRAPHITE ☐ ALU ☐ ALU FLEX ☒

REAR BOTTOM VIEW

T-BRACE

ALU ☐ BRASS ☐

REAR ARMS

MEDIUM ☐ HARD ☐

STEER. LOCK

/deg.

STEER. SHIM

SIZE /mm

REAR BRACE

YES ☐ NO ☒