

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	CCTE Rd5 Amsa Trinitat				
TRACK	Sentido Antihorario				
NAME	Luis Moreno		DATE	12/11/2023	
QUAL POSITION	2	FINAL POSITION	2	BEST LAPTIME	19.2 /sec
LAPS	/				

TRACK	
TRACK SURFACE	<input type="checkbox"/> CARPET <input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT		TRANSMISSION		REAR	
GEAR DIFF OIL	/cst	<input type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL	5	/cst
PINION	47 /T	SPUR GEAR	99 /T	FINAL DRIVE RATIO	4

FRONT		SHOCKS		REAR	
2.5/2.8	XRAY SPRINGS	2.7			
425	OIL /cst	450			
	REBOUND %				
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO			

<input type="checkbox"/> 4 HOLES	1.1mm	1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input checked="" type="checkbox"/> PSS	1.2mm	1.2mm	<input type="checkbox"/> PSS
2x0.8			
SHOCK LENGTH	8.5 /mm	8.5 /mm	SHOCK LENGTH

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Hot Race 36		TIRES		Hot Race 36	
7+7		ADDITIVE		7+7	
Timing: 15		TIRE WARMERS		Timing: 15	
Temp.: 70				Temp.: 70	
FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT	TREATED AREA	

TOTAL WEIGHT	1350 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
--------------	---------	----------------	------------	-----------

MOTOR	Hw Jstck	TIMING	Fix
ESC	Hw Jstck	BATTERIES	XTR
BODY	Wolverine 0.5	WING	Std

64 /mm	Dimension from body post to window bottom line	BODY POSITION
6+oring	Dimension from body post to upper holder	WING SIDE PLATE
7h /mm	Dimension from edge to surface	

1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
2.0mm	<input type="checkbox"/> 1.6mm	
NONE	<input type="checkbox"/> BEARING	

Puesta a punto buscada para paliar las complicaciones de la rueda. Lo que está entre paréntesis es con rueda nueva.

Setup sought to alleviate tyre complications. What is in parentheses is with a new tyre

FRONT & REAR SUSPENSION	
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER	SHIM
2 /mm	6 /mm
HEIGHT	SHIM
19 /mm	6 /mm
TOE GAIN	TOE GAIN
2 (2.5) /mm	2 (2.5) /mm
FRIDE HEIGHT	RRIDE HEIGHT
5.1 /mm	5.3 /mm
FR 2.5 /mm	RR 3 /mm
<input type="checkbox"/> SERVO SAVER	<input checked="" type="checkbox"/> SERVO HORN

FRONT	
2 (1.5) /deg. CAMBER	Left = Right
BODY STOP	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
SHOCK HOLDERS	SHIM 2.5 /mm
SUSPENSION FLEX	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
DRIVE SHAFT	58mm 59mm BEARING BLADE
FRONT HUB	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
SHIM	0 /mm
DOWNSTOP	6 /mm

REAR	
2 (2.5) /deg. CAMBER	Left = Right
BODY POST	VERTICAL <input checked="" type="checkbox"/> HORIZONTAL <input type="checkbox"/>
SHOCK HOLDERS	FIXED <input checked="" type="checkbox"/> ACTIVE <input type="checkbox"/>
SUSPENSION FLEX	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
DRIVE SHAFT	52mm 54mm BEARING BLADE
REAR HUB	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
SHIM	0.5 /mm
DOWNSTOP	5.2 /mm

FRONT TOP VIEW		REAR	
1.25	TOE OUT	3 (3.5)	TOE IN
Left = Right		Left = Right	
ACKERMANN	SHIM 0 /mm	SHORT LiPo BRASS WEIGHT	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
DIFF POSITION	<input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm	BRASS WEIGHT FOR MOTOR MOUNT	40g
UPPER ARM	SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>	STEERING BRIDGE	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
HUB OFFSET	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	STEERING	SHIM/mm
		PLATE	8.0mm 7.5mm STD.

FRONT BOTTOM VIEW		REAR	
STEER. LOCK	26 /deg.	T-BRACE	ALU <input checked="" type="checkbox"/> BRASS <input type="checkbox"/>
SERVO HOLDER	FR RE	MOTOR MOUNT	CHASSIS T-BRACE
FRONT ARMS	MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>	CHASSIS	GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/> ALU 1.5mm
		REAR ARMS	MEDIUM <input checked="" type="checkbox"/> HARD <input type="checkbox"/>