

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	ETS Rd.4				
TRACK	Hann. Münden				
NAME	Jacques Libar		DATE	19/11/23	
QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME	
/	/	/ /sec	/ /	/	

TRACK			
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT	
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> HIGH

FRONT		TRANSMISSION		REAR	
GEAR DIFF OIL	/cSt	<input checked="" type="checkbox"/> FRONT SOLID AXLE		GEAR DIFF OIL	8K /cSt
PINION	38 /T	SPUR GEAR	90 /T	FINAL DRIVE RATIO	4.5

FRONT		SHOCKS		REAR	
2.5-2.8		XRAY SPRINGS		2.7	
350		OIL /cSt		350	
/		REBOUND %		/	
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		FOAM INSERTS		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	
<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input type="checkbox"/> 1.1mm	<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	<input type="checkbox"/> 1.1mm
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	<input type="checkbox"/> 1.2mm
SHOCK LENGTH 8.5 /mm				SHOCK LENGTH 8.5 /mm	

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Matrix 28		TIRES	
Mr33 V4		ADDITIVE	
2*10 min		ADDITIVE TIMING	
		WIPE OFF TIME	
		TIRE WARMERS	
Timing:	Temp.:	Timing:	Temp.:
FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	1302 /g	WEIGHT BALANCE	FRONT 49 % REAR 51 %
--------------	---------	----------------	----------------------

MOTOR		TIMING	
ESC		BATTERIES	LRP 5100
BODY	Wolverine	WING	std

65 /mm	Dimension from body post to window bottom line	BODY POSITION
WING SIDE PLATE	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
Dimension from body post to upper holder		Dimension from edge to surface

X4'23	<input checked="" type="checkbox"/> 1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
X4'22	<input type="checkbox"/> 2.0mm	<input type="checkbox"/> 2.0mm	<input type="checkbox"/> 1.6mm
X4'22	<input type="checkbox"/> 2.0mm	<input type="checkbox"/> 1.6mm	<input type="checkbox"/> NONE
			<input type="checkbox"/> BEARING

COMMENTS

FRONT & REAR SUSPENSION	
FRONT CASTER <input type="checkbox"/> 5° <input checked="" type="checkbox"/> 4° <input type="checkbox"/> 3° Adjust with eccentric bushings	REAR CASTER <input type="checkbox"/> 0.5° <input type="checkbox"/> 1.5° <input checked="" type="checkbox"/> 2.5° <input type="checkbox"/> 3.5° <input type="checkbox"/> 4.5° <input type="checkbox"/> 5.5° Adjust with eccentric bushings
BUMP STEER 1.5 /mm	HEIGHT 19 /mm
SHIM 6 /mm	
TOE GAIN 1.5 /mm	TOE LOSS 1.5 /mm
RIDE HEIGHT 2.5 /mm FF <input checked="" type="checkbox"/> 2.0 /mm FR <input checked="" type="checkbox"/> 2.5 /mm	RIDE HEIGHT 3.0 /mm RF <input checked="" type="checkbox"/> 5.2 /mm RR <input checked="" type="checkbox"/> 3.0 /mm
<input type="checkbox"/> SERVO SAVER <input type="checkbox"/> SERVO HORN	

FRONT	
1.75 /deg. CAMBER Left = Right	BODY STOP YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> /mm
SHOCK HOLDERS SHIM 4 /mm	SHOCK HOLDERS SHIM 4 /mm
SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT <input checked="" type="checkbox"/> 58mm <input type="checkbox"/> 59mm <input checked="" type="checkbox"/> BEARING <input type="checkbox"/> BLADE	DRIVE SHAFT <input checked="" type="checkbox"/> 58mm <input type="checkbox"/> 59mm <input checked="" type="checkbox"/> BEARING <input type="checkbox"/> BLADE
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
6.6 /mm DOWNSTOP	

REAR	
2.0 /deg. CAMBER Left = Right	BODY POST VERTICAL <input type="checkbox"/> HORIZONTAL <input checked="" type="checkbox"/>
SHOCK HOLDERS SHIM 2 /mm	SHOCK HOLDERS SHIM 2 /mm
SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	SUSPENSION FLEX YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT <input type="checkbox"/> 52mm <input checked="" type="checkbox"/> 54mm <input checked="" type="checkbox"/> BEARING <input type="checkbox"/> BLADE	DRIVE SHAFT <input type="checkbox"/> 52mm <input checked="" type="checkbox"/> 54mm <input checked="" type="checkbox"/> BEARING <input type="checkbox"/> BLADE
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge
4.2 /mm DOWNSTOP	

FRONT TOP VIEW		REAR TOP VIEW	
1.2 /deg. TOE OUT Left = Right	ACKERMANN SHIM 0.5 /mm	2.5 /deg. TOE IN Left = Right	SHORT LiPo BRASS WEIGHT YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm	DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm	DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm	DIFF POSITION <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm
UPPER ARM SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/>	UPPER ARM SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/>	UPPER ARM SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/>	UPPER ARM SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/>
STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEERING BRIDGE YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm +0.5	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm +0.5	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm +0.5	HUB OFFSET STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm +0.5

FRONT BOTTOM VIEW		REAR BOTTOM VIEW	
STEER. LOCK 25 /deg.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>	STEER. LOCK 25 /deg.	T-BRACE ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
SERVO HOLDER FR RE	MOTOR MOUNT	SERVO HOLDER FR RE	MOTOR MOUNT
FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	CHASSIS GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU 1.5mm <input type="checkbox"/>	FRONT ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	CHASSIS GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU 1.5mm <input type="checkbox"/>
REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	REAR ARMS MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>