

# SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

# XRAY X4'24

RACE	USIC				
TRACK	Embassy Suites				
NAME	Alexander Hagberg		DATE	26/11/23	
QUAL POSITION	4	FINAL POSITION	4	BEST LAP TIME	11.3 /sec
LAPS	/				

TRACK		
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM
	<input type="checkbox"/> FAST	<input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL 8000 /cSt
PINION 28 /T	SPUR GEAR 110 /T	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.6
500	OIL /cSt	500
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input type="checkbox"/> NO
<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm
<input checked="" type="checkbox"/> PSS	<input checked="" type="checkbox"/> PSS	<input checked="" type="checkbox"/> PSS
2x0.8	2x0.8	2x0.8
SHOCK LENGTH 8.75 /mm	SHOCK LENGTH 8.75 /mm	SHOCK LENGTH 8.75 /mm
1.2 THICKNESS/mm	ANTI-ROLL BAR	1.2 THICKNESS/mm

Gravity RC	TIRES	Gravity RC
SXT 3.0	ADDITIVE	SXT 3.0
10	ADDITIVE TIMING	10
Timing:	WIPE OFF TIME	Timing:
Temp.:	TIRE WARMERS	Temp.:
FRONT LEFT	TREATED AREA	REAR LEFT
FRONT RIGHT		REAR RIGHT

TOTAL WEIGHT 1330 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
MOTOR HW G3 5.0T	TIMING	32.5	
ESC HW XR10 PRO G2S	BATTERIES	Nosram 4200	
BODY Speciale UL	WING	Speciale L	

67 /mm	Dimension from body post to window bottom line	BODY POSITION
7th hole, o-ring, +2	Dimension from body post to upper holder	WING SIDE PLATE
63 /mm	Dimension from edge to surface	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>

1.6mm <input checked="" type="checkbox"/> 2.0mm <input checked="" type="checkbox"/> 1.6mm	TOP DECK CUTTING
2.0mm <input type="checkbox"/> 2.0mm <input type="checkbox"/> 1.6mm	
NONE <input type="checkbox"/> BEARING <input type="checkbox"/>	

Weight bias 10g more in the front. COMMENTS  
Cleaned tires with additive.

FRONT & REAR	SUSPENSION
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER 2 /mm	HEIGHT 19 /mm
SHIM 1.5 /mm	SHIM 1.5 /mm
2.0 /mm FF	5.2 /mm FR
5.2 /mm RIDE HEIGHT	2.0 /mm FR
FR 2.0 /mm	<input checked="" type="checkbox"/> SERVO SAVER
<input type="checkbox"/> SERVO HORN	
TOE GAIN 1.5 /mm	2.5 /mm RF
5.4 /mm RR	5.4 /mm RIDE HEIGHT
	RR 2.5 /mm

FRONT	SHOCK HOLDERS	SHIM	3 /mm	SHOCK FLEX	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	DRIVE SHAFT	58mm <input checked="" type="checkbox"/> 59mm <input type="checkbox"/>	BEARING <input checked="" type="checkbox"/> BLADE <input type="checkbox"/>	#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	5.8 /mm	DOWNSTOP		
2.0 /deg. CAMBER	Left = Right	2.5 /mm	SHIM 3.0 /mm	SHOCK HOLDERS	SHIM 3 /mm	SHOCK FLEX	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	DRIVE SHAFT	58mm <input checked="" type="checkbox"/> 59mm <input type="checkbox"/>	BEARING <input checked="" type="checkbox"/> BLADE <input type="checkbox"/>	#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	5.8 /mm	DOWNSTOP

REAR	SHOCK HOLDERS	SHIM	4 /mm	SHOCK FLEX	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	DRIVE SHAFT	52mm <input checked="" type="checkbox"/> 54mm <input type="checkbox"/>	BEARING <input checked="" type="checkbox"/> BLADE <input type="checkbox"/>	#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	4.6 /mm	DOWNSTOP		
2.0 /deg. CAMBER	Left = Right	2.5 /mm	SHIM 3.0 /mm	SHOCK HOLDERS	SHIM 4 /mm	SHOCK FLEX	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	DRIVE SHAFT	52mm <input checked="" type="checkbox"/> 54mm <input type="checkbox"/>	BEARING <input checked="" type="checkbox"/> BLADE <input type="checkbox"/>	#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	4.6 /mm	DOWNSTOP

FRONT TOP VIEW	REAR
1.25	3.0
TOE OUT	TOE IN
Left = Right	Left = Right
ACKERMANN	SHORT LiPo BRASS WEIGHT
SHIM 0.5 /mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
10	40g
10	40g
BRASS WEIGHT FOR MOTOR MOUNT	
DIFF POSITION	DIFF POSITION
<input type="checkbox"/> UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> +1mm	<input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm
UPPER ARM	UPPER ARM
SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>	SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>
STEERING BRIDGE	STEERING
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	SHIM /mm
HUB OFFSET	PLATE
STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm	SHIM 7.5 /mm
	8.0mm 7.5mm STD.

FRONT BOTTOM VIEW	REAR
STEER. LOCK 26 /deg.	T-BRACE
FR RE	ALU BRASS
SERVO HOLDER	CHASSIS T-BRACE
MOTOR MOUNT	
FRONT ARMS	REAR ARMS
MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>
CHASSIS	
GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU 1.5mm	