

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	Winter Race				
TRACK	La Nave				
NAME	Luis Moreno		DATE	2/3-12-2023	
QUAL POSITION	5	FINAL POSITION	5	BEST LAP TIME	14.2 /sec
LAPS		21 / 5:13			

TRACK		
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input checked="" type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	SPUR GEAR	FINAL DRIVE RATIO
38 /T	100 /T	7K /St

FRONT	SHOCKS	REAR
2.5/2.8	XRAY SPRINGS	2.6
450	OIL /Cst	450
REBOUND %		
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm	<input type="checkbox"/> 4 HOLES <input type="checkbox"/> 1.1mm <input type="checkbox"/> 1.2mm
<input checked="" type="checkbox"/> PSS	<input checked="" type="checkbox"/> PSS	<input checked="" type="checkbox"/> PSS
2 x 0.8		2 x 0.8
SHOCK LENGTH		SHOCK LENGTH
8.5 /mm		8.5 /mm
1.3	THICKNESS/mm	1.2

Matrix 28	TIRES	Matrix 28
Hudy Red	ADDITIVE	Hudy Red
10 (4:30+4:30)	ADDITIVE TIMING	15 (4:30+4:30+4:30)
Timing:	WIPE OFF TIME	Timing:
Temp.:	TIRE WARMERS	Temp.:
FRONT LEFT	TREATED AREA	REAR LEFT
FRONT RIGHT		REAR RIGHT

TOTAL WEIGHT	1305 /g	WEIGHT BALANCE	FRONT 50 % REAR 50 %
--------------	---------	----------------	----------------------

MOTOR	TIMING
ESC	BATTERIES
BODY	WING
Wolverine 0.5	Std

66 /mm	Dimension from body post to window bottom line	BODY POSITION
WING SIDE PLATE	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
Dimension from body post to upper holder		
Dimension from edge to surface		

1.6mm <input checked="" type="checkbox"/> 2.0mm <input checked="" type="checkbox"/> 1.6mm
X4'23
X4'22
X4'22
NONE <input type="checkbox"/> BEARING <input type="checkbox"/>

COMMENTS

FRONT & REAR	SUSPENSION
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER	SHIM
3 /mm	6 /mm
HEIGHT	SHIM
18 /mm	6 /mm
2 /mm FF	TOE GAIN
5.2 /mm	1.5 /mm
FR 2 /mm	2.5 /mm RF
SHIM	5.4 /mm
SERVO SAVER	RR 2.5 /mm
SERVO HORN	

FRONT	SHOCK HOLDERS	SHOCK LENGTH	SHOCK LENGTH
2 /deg. CAMBER	SHIM 3 /mm	1.5 /mm	2 /mm
Left = Right	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		
DRIVE SHAFT	SUSPENSION FLEX		
58mm 59mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		
BEARING BLADE	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		

REAR	SHOCK HOLDERS	SHOCK LENGTH	SHOCK LENGTH
2 /deg. CAMBER	SHIM 4.5 /mm	1.5 /mm	2 /mm
Left = Right	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		
DRIVE SHAFT	SUSPENSION FLEX		
52mm 54mm	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		
BEARING BLADE	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		

FRONT TOP VIEW	REAR
1.25	3
TOE OUT	TOE IN
Left = Right	Left = Right
ACKERMANN	SHIM 1 /mm
SHIM	
SHORT LiPo BRASS WEIGHT	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
BRASS WEIGHT FOR MOTOR MOUNT	40g
40g	
DIFF POSITION	DIFF POSITION
UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>	UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/> +1mm <input type="checkbox"/>
UPPER ARM	UPPER ARM
SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/>	SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/>
STEERING BRIDGE	STEERING
YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	SHIM /mm
	PLATE
	8.0mm 7.5mm
HUB OFFSET	HUB OFFSET
STD. <input type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm <input checked="" type="checkbox"/> SHIM /mm	STD. <input type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm <input checked="" type="checkbox"/> SHIM /mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK	T-BRACE
26 /deg.	ALU BRASS
FR RE	CHASSIS T-BRACE
SERVO HOLDER	
MOTOR MOUNT	
FRONT ARMS	REAR ARMS
MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>
CHASSIS	
GRAPHITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/> ALU 1.5mm <input type="checkbox"/>	